
python-binance Documentation

Release 0.2.0

Sam McHardy

Sep 27, 2021

Contents

1	Features	3
2	Upgrading to v1.0.0+	5
3	Quick Start	7
4	Async Example	11
5	Donate	13
6	Other Exchanges	15
6.1	Contents	15
6.2	Index	203
	Python Module Index	205
	Index	207

Updated 27th Sept 2021

This is an unofficial Python wrapper for the [Binance exchange REST API v3](#). I am in no way affiliated with Binance, use at your own risk.

If you came here looking for the [Binance exchange](#) to purchase cryptocurrencies, then [go here](#). If you want to automate interactions with Binance stick around.

If you're interested in Binance's new DEX Binance Chain see my [python-binance-chain](#) library

Source code <https://github.com/sammchardy/python-binance>

Documentation <https://python-binance.readthedocs.io/en/latest/>

Binance API Telegram https://t.me/binance_api_english

Blog with examples including async <https://sammchardy.github.io>

- [Async basics for Binance](#)
- [Understanding Binance Order Filters](#)

Make sure you update often and check the [Changelog](#) for new features and bug fixes.

CHAPTER 1

Features

- Implementation of all General, Market Data and Account endpoints.
- Asyncio implementation
- Testnet support for Spot, Futures and Vanilla Options
- Simple handling of authentication
- No need to generate timestamps yourself, the wrapper does it for you
- Response exception handling
- Websocket handling with reconnection and multiplexed connections
- Symbol Depth Cache
- Historical Kline/Candle fetching function
- Withdraw functionality
- Deposit addresses
- Margin Trading
- Futures Trading
- Vanilla Options
- Support other domains (.us, .jp, etc)

CHAPTER 2

Upgrading to v1.0.0+

The breaking changes include the migration from wapi to sapi endpoints which related to the wallet endpoints detailed in the [Binance Docs](#)

The other breaking change is for websocket streams and the Depth Cache Manager which have been converted to use Asynchronous Context Managers. See examples in the Async section below or view the [websockets](#) and [depth cache docs](#).

CHAPTER 3

Quick Start

Register an account with Binance.

Generate an API Key and assign relevant permissions.

If you are using an exchange from the US, Japan or other TLD then make sure pass *tld='us'* when creating the client.

To use the Spot or Vanilla Options Testnet, pass *testnet=True* when creating the client.

```
pip install python-binance
```

```
from binance import Client, ThreadedWebsocketManager, ThreadedDepthCacheManager
client = Client(api_key, api_secret)

# get market depth
depth = client.get_order_book(symbol='BNBBTC')

# place a test market buy order, to place an actual order use the create_order_
↪function
order = client.create_test_order(
    symbol='BNBBTC',
    side=Client.SIDE_BUY,
    type=Client.ORDER_TYPE_MARKET,
    quantity=100)

# get all symbol prices
prices = client.get_all_tickers()

# withdraw 100 ETH
# check docs for assumptions around withdrawals
from binance.exceptions import BinanceAPIException
try:
    result = client.withdraw(
        asset='ETH',
        address='<eth_address>',
        amount=100)
```

(continues on next page)

(continued from previous page)

```
except BinanceAPIException as e:
    print(e)
else:
    print("Success")

# fetch list of withdrawals
withdraws = client.get_withdraw_history()

# fetch list of ETH withdrawals
eth_withdraws = client.get_withdraw_history(coin='ETH')

# get a deposit address for BTC
address = client.get_deposit_address(coin='BTC')

# get historical kline data from any date range

# fetch 1 minute klines for the last day up until now
klines = client.get_historical_klines("BNBBTC", Client.KLINE_INTERVAL_1MINUTE, "1 day_
↳ago UTC")

# fetch 30 minute klines for the last month of 2017
klines = client.get_historical_klines("ETHBTC", Client.KLINE_INTERVAL_30MINUTE, "1_
↳Dec, 2017", "1 Jan, 2018")

# fetch weekly klines since it listed
klines = client.get_historical_klines("NEOBTC", Client.KLINE_INTERVAL_1WEEK, "1 Jan,_
↳2017")

# socket manager using threads
twm = ThreadedWebsocketManager()
twm.start()

# depth cache manager using threads
dcm = ThreadedDepthCacheManager()
dcm.start()

def handle_socket_message(msg):
    print(f"message type: {msg['e']}")
    print(msg)

def handle_dcm_message(depth_cache):
    print(f"symbol {depth_cache.symbol}")
    print("top 5 bids")
    print(depth_cache.get_bids()[:5])
    print("top 5 asks")
    print(depth_cache.get_asks()[:5])
    print("last update time {}".format(depth_cache.update_time))

twm.start_kline_socket(callback=handle_socket_message, symbol='BNBBTC')

dcm.start_depth_cache(callback=handle_dcm_message, symbol='ETHBTC')

# replace with a current options symbol
options_symbol = 'BTC-210430-36000-C'
dcm.start_options_depth_cache(callback=handle_dcm_message, symbol=options_symbol)

# join the threaded managers to the main thread
```

(continues on next page)

(continued from previous page)

```
twm.join()  
dcm.join()
```

For more check out the [documentation](#).

CHAPTER 4

Async Example

Read Async basics for Binance for more information.

```
import asyncio
import json

from binance import AsyncClient, DepthCacheManager, BinanceSocketManager

async def main():

    # initialise the client
    client = await AsyncClient.create()

    # run some simple requests
    print(json.dumps(await client.get_exchange_info(), indent=2))

    print(json.dumps(await client.get_symbol_ticker(symbol="BTCUSDT"), indent=2))

    # initialise websocket factory manager
    bsm = BinanceSocketManager(client)

    # create listener using async with
    # this will exit and close the connection after 5 messages
    async with bsm.trade_socket('ETHBTC') as ts:
        for _ in range(5):
            res = await ts.recv()
            print(f'recv {res}')

    # get historical kline data from any date range

    # fetch 1 minute klines for the last day up until now
    klines = client.get_historical_klines("BNBBTC", AsyncClient.KLINE_INTERVAL_
↪1MINUTE, "1 day ago UTC")

    # use generator to fetch 1 minute klines for the last day up until now
```

(continues on next page)

(continued from previous page)

```
    async for kline in await client.get_historical_klines_generator("BNBBTC",
↳ AsyncClient.KLINE_INTERVAL_1MINUTE, "1 day ago UTC"):
        print(kline)

    # fetch 30 minute klines for the last month of 2017
    klines = client.get_historical_klines("ETHBTC", Client.KLINE_INTERVAL_30MINUTE,
↳ "1 Dec, 2017", "1 Jan, 2018")

    # fetch weekly klines since it listed
    klines = client.get_historical_klines("NEOBTC", Client.KLINE_INTERVAL_1WEEK, "1_
↳ Jan, 2017")

    # setup an async context the Depth Cache and exit after 5 messages
    async with DepthCacheManager(client, symbol='ETHBTC') as dcm_socket:
        for _ in range(5):
            depth_cache = await dcm_socket.recv()
            print(f"symbol {depth_cache.symbol} updated:{depth_cache.update_time}")
            print("Top 5 asks:")
            print(depth_cache.get_asks()[:5])
            print("Top 5 bids:")
            print(depth_cache.get_bids()[:5])

    # Vanilla options Depth Cache works the same, update the symbol to a current one
    options_symbol = 'BTC-210430-36000-C'
    async with OptionsDepthCacheManager(client, symbol=options_symbol) as dcm_socket:
        for _ in range(5):
            depth_cache = await dcm_socket.recv()
            count += 1
            print(f"symbol {depth_cache.symbol} updated:{depth_cache.update_time}")
            print("Top 5 asks:")
            print(depth_cache.get_asks()[:5])
            print("Top 5 bids:")
            print(depth_cache.get_bids()[:5])

    await client.close_connection()

if __name__ == "__main__":

    loop = asyncio.get_event_loop()
    loop.run_until_complete(main())
```


CHAPTER 5

Donate

If this library helped you out feel free to donate.

- ETH: 0xD7a7fDdCfA687073d7cC93E9E51829a727f9fE70
- LTC: LPC5vw9ajR1YndE1hYVeo3kJ9LdHjcRCUZ
- NEO: AVJB4ZgN7VgSUtArCt94y7ZYT6d5NDfpBo
- BTC: 1Dknp6L6oRZrHDECRedihPzx2sSfmvEBys

If you use [Binance Chain](#) check out my [python-binance-chain](#) library.

If you use [Kucoin](#) check out my [python-kucoin](#) library.

If you use [IDEX](#) check out my [python-idex](#) library.

6.1 Contents

6.1.1 Getting Started

Installation

`python-binance` is available on [PYPI](#). Install with `pip`:

```
pip install python-binance
```

Register on Binance

Firstly [register](#) an account with [Binance](#).

Generate an API Key

To use signed account methods you are required to [create an API Key](#).

Initialise the client

Pass your [API Key](#) and [Secret](#)

```
from binance.client import Client
client = Client(api_key, api_secret)
```

or for Asynchronous client

```
async def main():
    # initialise the client
    client = await AsyncClient.create(api_key, api_secret)

if __name__ == "__main__":
    loop = asyncio.get_event_loop()
    loop.run_until_complete(main())
```

Using the Spot, Futures or Vanilla Options Testnet

Binance offers a [Spot](#), [Futures](#) and [Vanilla Options](#) Testnet, to test interacting with the exchange.

To enable this set the *testnet* parameter passed to the Client to True.

The testnet parameter will also be used by any websocket streams when the client is passed to the `BinanceSocketManager`.

```
client = Client(api_key, api_secret, testnet=True)
```

or for Asynchronous client

```
client = await AsyncClient.create(api_key, api_secret, testnet=True)
```

Using a different TLD

If you are interacting with a regional version of Binance which has a different TLD such as *.us* or *‘.jp’* then you will need to pass this when creating the client, see examples below.

This tld will also be used by any websocket streams when the client is passed to the `BinanceSocketManager`.

```
client = Client(api_key, api_secret, tld='us')
```

or for Asynchronous client

```
client = await AsyncClient.create(api_key, api_secret, tld='us')
```

Making API Calls

Every method supports the passing of arbitrary parameters via keyword matching those in the [Binance API documentation](#). These keyword arguments will be sent directly to the relevant endpoint.

Each API method returns a dictionary of the JSON response as per the [Binance API documentation](#). The docstring of each method in the code references the endpoint it implements.

The Binance API documentation references a *timestamp* parameter, this is generated for you where required.

Some methods have a *recvWindow* parameter for [timing security](#), see [Binance documentation](#).

API Endpoints are rate limited by Binance at 20 requests per second, ask them if you require more.

Async API Calls

aiohhttp is used to handle asyncio REST requests.

Each function available in the normal client is available in the AsyncClient class.

The only difference is to run within an asyncio event loop and await the function like below.

```
import asyncio
from binance import AsyncClient

async def main():
    client = await AsyncClient.create()

    # fetch exchange info
    res = await client.get_exchange_info()
    print(json.dumps(res, indent=2))

    await client.close_connection()

if __name__ == "__main__":
    loop = asyncio.get_event_loop()
    loop.run_until_complete(main())
```

Read [Async basics for Binance](#) for more information about asynchronous patterns.

API Rate Limit

Check the `get_exchange_info()` call for up to date rate limits.

At the current time Binance rate limits are:

- 1200 requests per minute
- 10 orders per second
- 100,000 orders per 24hrs

Some calls have a higher weight than others especially if a call returns information about all symbols. Read the [official Binance documentation](#) for specific information.

On each request Binance returns `X-MBX-USED-WEIGHT-(intervalNum)(intervalLetter)` and `X-MBX-ORDER-COUNT-(intervalNum)` headers.

Here are examples to access these

Asynchronous example

```
import asyncio
from binance import AsyncClient

api_key = '<api_key>'
api_secret = '<api_secret>'

async def main():
    client = await AsyncClient.create(api_key, api_secret)

    res = await client.get_exchange_info()
    print(client.response.headers)
```

(continues on next page)

(continued from previous page)

```

    await client.close_connection()

if __name__ == "__main__":
    loop = asyncio.get_event_loop()
    loop.run_until_complete(main())

```

Synchronous example

```

from binance import Client

api_key = '<api_key>'
api_secret = '<api_secret>'

def main():
    client = Client(api_key, api_secret)

    res = client.get_exchange_info()
    print(client.response.headers)

if __name__ == "__main__":
    main()

```

Requests Settings

python-binance uses the `requests` library.

You can set custom requests parameters for all API calls when creating the client.

```
client = Client("api-key", "api-secret", {"verify": False, "timeout": 20})
```

You may also pass custom requests parameters through any API call to override default settings or the above settings specify new ones like the example below.

```

# this would result in verify: False and timeout: 5 for the get_all_orders call
client = Client("api-key", "api-secret", {"verify": False, "timeout": 20})
client.get_all_orders(symbol='BNBBTC', requests_params={'timeout': 5})

```

Check out the [requests documentation](#) for all options.

Proxy Settings

You can use the Requests Settings method above

```

proxies = {
    'http': 'http://10.10.1.10:3128',
    'https': 'http://10.10.1.10:1080'
}

# in the Client instantiation
client = Client("api-key", "api-secret", {'proxies': proxies})

# or on an individual call
client.get_all_orders(symbol='BNBBTC', requests_params={'proxies': proxies})

```

Or set an environment variable for your proxy if required to work across all requests.

An example for Linux environments from the [requests Proxies](#) documentation is as follows.

```
$ export HTTP_PROXY="http://10.10.1.10:3128"
$ export HTTPS_PROXY="http://10.10.1.10:1080"
```

For Windows environments

```
C:\>set HTTP_PROXY=http://10.10.1.10:3128
C:\>set HTTPS_PROXY=http://10.10.1.10:1080
```

6.1.2 Binance Constants

Binance requires specific string constants for Order Types, Order Side, Time in Force, Order response and Kline intervals these are found on *binance.client.Client*.

```
SYMBOL_TYPE_SPOT = 'SPOT'

ORDER_STATUS_NEW = 'NEW'
ORDER_STATUS_PARTIALLY_FILLED = 'PARTIALLY_FILLED'
ORDER_STATUS_FILLED = 'FILLED'
ORDER_STATUS_CANCELED = 'CANCELED'
ORDER_STATUS_PENDING_CANCEL = 'PENDING_CANCEL'
ORDER_STATUS_REJECTED = 'REJECTED'
ORDER_STATUS_EXPIRED = 'EXPIRED'

KLINE_INTERVAL_1MINUTE = '1m'
KLINE_INTERVAL_3MINUTE = '3m'
KLINE_INTERVAL_5MINUTE = '5m'
KLINE_INTERVAL_15MINUTE = '15m'
KLINE_INTERVAL_30MINUTE = '30m'
KLINE_INTERVAL_1HOUR = '1h'
KLINE_INTERVAL_2HOUR = '2h'
KLINE_INTERVAL_4HOUR = '4h'
KLINE_INTERVAL_6HOUR = '6h'
KLINE_INTERVAL_8HOUR = '8h'
KLINE_INTERVAL_12HOUR = '12h'
KLINE_INTERVAL_1DAY = '1d'
KLINE_INTERVAL_3DAY = '3d'
KLINE_INTERVAL_1WEEK = '1w'
KLINE_INTERVAL_1MONTH = '1M'

SIDE_BUY = 'BUY'
SIDE_SELL = 'SELL'

ORDER_TYPE_LIMIT = 'LIMIT'
ORDER_TYPE_MARKET = 'MARKET'
ORDER_TYPE_STOP_LOSS = 'STOP_LOSS'
ORDER_TYPE_STOP_LOSS_LIMIT = 'STOP_LOSS_LIMIT'
ORDER_TYPE_TAKE_PROFIT = 'TAKE_PROFIT'
ORDER_TYPE_TAKE_PROFIT_LIMIT = 'TAKE_PROFIT_LIMIT'
ORDER_TYPE_LIMIT_MAKER = 'LIMIT_MAKER'

TIME_IN_FORCE_GTC = 'GTC'
TIME_IN_FORCE_IOC = 'IOC'
TIME_IN_FORCE_FOK = 'FOK'
```

(continues on next page)

(continued from previous page)

```
ORDER_RESP_TYPE_ACK = 'ACK'
ORDER_RESP_TYPE_RESULT = 'RESULT'
ORDER_RESP_TYPE_FULL = 'FULL'

# For accessing the data returned by Client.aggregate_trades().
AGG_ID = 'a'
AGG_PRICE = 'p'
AGG_QUANTITY = 'q'
AGG_FIRST_TRADE_ID = 'f'
AGG_LAST_TRADE_ID = 'l'
AGG_TIME = 'T'
AGG_BUYER_MAKES = 'm'
AGG_BEST_MATCH = 'M'
```

For Websocket Depth these are found on *binance.websockets.BinanceSocketManager*

```
WEBSOCKET_DEPTH_5 = '5'
WEBSOCKET_DEPTH_10 = '10'
WEBSOCKET_DEPTH_20 = '20'
```

To use in your code reference either `binance.client.Client` or `binance.websockets.BinanceSocketManager`

```
from binance.client import Client
from binance.websockets import BinanceSocketManager

side = Client.SIDE_BUY
```

6.1.3 General Endpoints

Ping the server

```
client.ping()
```

Get the server time

```
time_res = client.get_server_time()
```

Get system status

```
status = client.get_system_status()
```

Returns

```
{
    "status": 0,          # 0: normal system maintenance
    "msg": "normal"      # normal or System maintenance.
}
```


Get Exchange Info

```
info = client.get_exchange_info()
```

Get Symbol Info

Get the exchange info for a particular symbol

```
info = client.get_symbol_info('BNBBTC')
```

Get All Coins Info

Get information of coins (available for deposit and withdraw) for user

```
info = client.get_all_tickers()
```

Get Get Daily Account Snapshot

Get daily account snapshot of specific type. Valid types: SPOT/MARGIN/FUTURES.

```
info = client.get_account_snapshot(type='SPOT')
```

Get Current Products

This call is deprecated, use the above Exchange Info call

```
products = client.get_products()
```

6.1.4 Market Data Endpoints

Get Market Depth

```
depth = client.get_order_book(symbol='BNBBTC')
```

Get Recent Trades

```
trades = client.get_recent_trades(symbol='BNBBTC')
```

Get Historical Trades

```
trades = client.get_historical_trades(symbol='BNBBTC')
```

Get Aggregate Trades

```
trades = client.get_aggregate_trades(symbol='BNBBTC')
```

Aggregate Trade Iterator

Iterate over aggregate trades for a symbol from a given date or a given order id.

```
agg_trades = client.aggregate_trade_iter(symbol='ETHBTC', start_str='30 minutes ago_
↳UTC')

# iterate over the trade iterator
for trade in agg_trades:
    print(trade)
    # do something with the trade data

# convert the iterator to a list
# note: generators can only be iterated over once so we need to call it again
agg_trades = client.aggregate_trade_iter(symbol='ETHBTC', '30 minutes ago UTC')
agg_trade_list = list(agg_trades)

# example using last_id value
agg_trades = client.aggregate_trade_iter(symbol='ETHBTC', last_id=23380478)
agg_trade_list = list(agg_trades)
```

Get Kline/Candlesticks

```
candles = client.get_klines(symbol='BNBBTC', interval=Client.KLINE_INTERVAL_30MINUTE)
```

Get Historical Kline/Candlesticks

Fetch klines for any date range and interval

```
# fetch 1 minute klines for the last day up until now
klines = client.get_historical_klines("BNBBTC", Client.KLINE_INTERVAL_1MINUTE, "1 day_
↳ago UTC")

# fetch 30 minute klines for the last month of 2017
klines = client.get_historical_klines("ETHBTC", Client.KLINE_INTERVAL_30MINUTE, "1_
↳Dec, 2017", "1 Jan, 2018")

# fetch weekly klines since it listed
klines = client.get_historical_klines("NEOBT", Client.KLINE_INTERVAL_1WEEK, "1 Jan,_
↳2017")
```

Get Historical Kline/Candlesticks using a generator

Fetch klines using a generator

```

for kline in client.get_historical_klines_generator("BNBBTC", Client.KLINE_INTERVAL_
↳ 1MINUTE, "1 day ago UTC")
    print(kline)
    # do something with the kline

```

Get average price for a symbol

```
avg_price = client.get_avg_price(symbol='BNBBTC')
```

Get 24hr Ticker

```
tickers = client.get_ticker()
```

Get All Prices

Get last price for all markets.

```
prices = client.get_all_tickers()
```

Get Orderbook Tickers

Get first bid and ask entry in the order book for all markets.

```
tickers = client.get_orderbook_tickers()
```

6.1.5 Account Endpoints

Orders

Order Validation

Binance has a number of rules around symbol pair orders with validation on minimum price, quantity and total order value.

Read more about their specifics in the [Filters](#) section of the official API.

Read [Understanding Binance Order Filters](#) for more information about price and quantity filters on [Binance](#).

It can be helpful to format the output using formatting

```

amount = 0.000234234
precision = 5
amt_str = "{:0.0{}}f".format(amount, precision)

```

Or if you have the tickSize or stepSize then use the helper to round to step size

```
from binance.helpers import round_step_size

amount = 0.000234234
tick_size = 0.00001
rounded_amount = round_step_size(amount, tick_size)
```

Fetch all orders

```
orders = client.get_all_orders(symbol='BNBBTC', limit=10)
```

Place an order

Place an order

Use the `create_order` function to have full control over creating an order

```
from binance.enums import *
order = client.create_order(
    symbol='BNBBTC',
    side=SIDE_BUY,
    type=ORDER_TYPE_LIMIT,
    timeInForce=TIME_IN_FORCE_GTC,
    quantity=100,
    price='0.00001')
```

Place a limit order

Use the helper functions to easily place a limit buy or sell order

```
order = client.order_limit_buy(
    symbol='BNBBTC',
    quantity=100,
    price='0.00001')

order = client.order_limit_sell(
    symbol='BNBBTC',
    quantity=100,
    price='0.00001')
```

Place a market order

Use the helper functions to easily place a market buy or sell order

```
order = client.order_market_buy(
    symbol='BNBBTC',
    quantity=100)

order = client.order_market_sell(
    symbol='BNBBTC',
    quantity=100)
```

Place an OCO order

Use the `create_oco_order` function to have full control over creating an OCO order

```

from binance.enums import *
order = client.create_oco_order(
    symbol='BNBBTC',
    side=SIDE_SELL,
    stopLimitTimeInForce=TIME_IN_FORCE_GTC,
    quantity=100,
    stopPrice='0.00001',
    price='0.00002')

```

Place a test order

Creates and validates a new order but does not send it into the exchange.

```

from binance.enums import *
order = client.create_test_order(
    symbol='BNBBTC',
    side=SIDE_BUY,
    type=ORDER_TYPE_LIMIT,
    timeInForce=TIME_IN_FORCE_GTC,
    quantity=100,
    price='0.00001')

```

Check order status

```

order = client.get_order(
    symbol='BNBBTC',
    orderId='orderId')

```

Cancel an order

```

result = client.cancel_order(
    symbol='BNBBTC',
    orderId='orderId')

```

Get all open orders

```

orders = client.get_open_orders(symbol='BNBBTC')

```

Get all orders

```

orders = client.get_all_orders(symbol='BNBBTC')

```

Account

Get account info

```
info = client.get_account()
```

Get asset balance

```
balance = client.get_asset_balance(asset='BTC')
```

Get account status

```
status = client.get_account_status()
```

Get account API trading status

```
status = client.get_account_api_trading_status()
```

Get trades

```
trades = client.get_my_trades(symbol='BNBBTC')
```

Get trade fees

```
# get fees for all symbols  
fees = client.get_trade_fee()  
  
# get fee for one symbol  
fees = client.get_trade_fee(symbol='BNBBTC')
```

Get asset details

```
details = client.get_asset_details()
```

Get dust log

```
log = client.get_dust_log()
```

Transfer dust

```
transfer = client.transfer_dust(asset='BNZ')
```

Get Asset Dividend History

```
history = client.get_asset_dividend_history()
```

Disable Fast Withdraw Switch

```
client.disable_fast_withdraw_switch()
```

Enable Fast Withdraw Switch

```
client.enable_fast_withdraw_switch()
```

6.1.6 Sub Account Endpoints

Get Sub Account list

```
accounts = client.get_sub_account_list()
```

Get Sub Account Transfer History

```
history = client.get_sub_account_transfer_history(fromEmail='blah@gmail.com', toEmail=
↳ 'foo@gmail.com')
```

Get Sub Account Assets

```
assets = client.get_sub_account_assets(email='blah@gmail.com')
```

6.1.7 Margin Trading Endpoints

Note: Cross-margin vs isolated margin trading

Binance offers both *cross-margin* trading (where all margin is in one account) and *isolated margin* trading (where each pair is a separate margin account). Make sure you are interacting with the right one.

Some of the API endpoints apply to the cross-margin or isolated margin accounts only. Other endpoints, such as the trade execution endpoints, are used for the cross-margin account trades by default, but you can use your isolated margin accounts by using the `isIsolated` or `isolatedSymbol` parameters. See the documentation below.

Market Data

Get cross-margin asset info

```
info = client.get_margin_asset(asset='BNB')
```

Get cross-margin symbol info

```
info = client.get_margin_symbol(symbol='BTCUSDT')
```

Get isolated margin symbol info

```
info = client.get_isolated_margin_symbol(symbol='BTCUSDT')
```

Get all isolated margin symbols

```
info = client.get_all_isolated_margin_symbols()
```

Get margin price index

```
info = client.get_margin_price_index(symbol='BTCUSDT')
```

Orders

Cross-margin vs isolated margin orders

By default, these trade execution endpoints will create an order using the *cross-margin* account.

To use the *isolated margin* account for the symbol you have specified, simply add the `isIsolated='TRUE'` parameter to the API calls below in this 'Orders' section.

Order Validation

Binance has a number of rules around symbol pair orders with validation on minimum price, quantity and total order value.

Read more about their specifics in the [Filters](#) section of the official API.

It can be helpful to format the output using the following snippet

```
amount = 0.000234234
precision = 5
amt_str = "{:0.0{}}f".format(amount, precision)
```


Fetch all margin_orders

```
orders = client.get_all_margin_orders(symbol='BNBBTC', limit=10)
```

Place a margin order

Use the `create_margin_order` function to have full control over creating an order

```
from binance.enums import *
order = client.create_margin_order(
    symbol='BNBBTC',
    side=SIDE_BUY,
    type=ORDER_TYPE_LIMIT,
    timeInForce=TIME_IN_FORCE_GTC,
    quantity=100,
    price='0.00001')
```

Check order status

```
order = client.get_margin_order(
    symbol='BNBBTC',
    orderId='orderId')
```

Cancel a margin order

```
result = client.cancel_margin_order(
    symbol='BNBBTC',
    orderId='orderId')
```

Get all open margin orders

```
orders = client.get_open_margin_orders(symbol='BNBBTC')
```

For isolated margin, add the `isIsolated='TRUE'` parameter.

Get all margin orders

```
orders = client.get_all_margin_orders(symbol='BNBBTC')
```

For isolated margin, add the `isIsolated='TRUE'` parameter.

Account

Get cross-margin account info

```
info = client.get_margin_account()
```

Create isolated margin account

```
account = client.create_isolated_margin_account(base='BTC', quote='ETH')
```

Get isolated margin account info

```
info = client.get_isolated_margin_account()
```

Transfer spot to cross-margin account

```
transaction = client.transfer_spot_to_margin(asset='BTC', amount='1.1')
```

Transfer cross-margin account to spot

```
transaction = client.transfer_margin_to_spot(asset='BTC', amount='1.1')
```

Transfer spot to isolated margin account

```
transaction = client.transfer_spot_to_isolated_margin(asset='BTC',  
                                                    symbol='ETHBTC', amount='1.1')
```

Transfer isolated margin account to spot

```
transaction = client.transfer_isolated_margin_to_spot(asset='BTC',  
                                                    symbol='ETHBTC', amount='1.1')
```

Get max transfer amount

```
details = client.get_max_margin_transfer(asset='BTC')
```

This max transfer is for the cross-margin account by default. For isolated margin records, add the `isolatedSymbol=symbol_name` parameter.

Trades

Get all margin trades

```
trades = client.get_margin_trades(symbol='BNBBTC')
```

For isolated margin trades, add the `isIsolated='TRUE'` parameter.

Loans

Create loan

```
transaction = client.create_margin_loan(asset='BTC', amount='1.1')
```

This for the cross-margin account by default. For isolated margin, add the `isIsolated='TRUE'` and the `symbol=symbol_name` parameters.

Repay loan

```
transaction = client.repay_margin_loan(asset='BTC', amount='1.1')
```

This for the cross-margin account by default. For isolated margin, add the `isIsolated='TRUE'` and the `symbol=symbol_name` parameters.

Get loan details

```
details = client.get_margin_loan_details(asset='BTC', txId='100001')
```

This for the cross-margin account by default. For isolated margin records, add the `isolatedSymbol=symbol_name` parameter.

Get repay details

```
details = client.get_margin_repay_details(asset='BTC', txId='100001')
```

This for the cross-margin account by default. For isolated margin records, add the `isolatedSymbol=symbol_name` parameter.

Get max loan amount

```
details = client.get_max_margin_loan(asset='BTC')
```

The max loan is for the cross-margin account by default. For isolated margin records, add the `isolatedSymbol=symbol_name` parameter.

6.1.8 Websockets

There are 2 ways to interact with websockets.

with `ThreadedWebsocketManager` or `BinanceSocketManager`.

`ThreadedWebsocketManager` does not require asyncio programming, while `BinanceSocketManager` does.

`ThreadedWebsocketManager` function begin with `start_`, e.g `start_ticker_socket` while `BinanceSocketManager` is simply `ticker_socket`.

Multiple socket connections can be made through either manager.

Only one instance of each socket type will be created, i.e. only one BNBBTC Depth socket can be created and there can be both a BNBBTC Depth and a BNBBTC Trade socket open at once.

Messages are received as dictionary objects relating to the message formats defined in the [Binance WebSocket API documentation](#).

Websockets are setup to reconnect with a maximum of 5 retries with an exponential backoff strategy.

ThreadedWebsocketManager Websocket Usage

Starting sockets on the `ThreadedWebsocketManager` requires a callback parameter, similar to the old implementations of websockets on python-binance.

`ThreadedWebsocketManager` takes similar parameters to the `Client` class as it creates an `AsyncClient` internally.

For authenticated streams `api_key` and `api_stream` are required.

As these use threads `start()` is required to be called before starting any sockets.

To keep the `ThreadedWebsocketManager` running, use `join()` to join it to the main thread.

```
import time

from binance import ThreadedWebsocketManager

api_key = '<api_key>'
api_secret = '<api_secret>'

def main():

    symbol = 'BNBBTC'

    twm = ThreadedWebsocketManager(api_key=api_key, api_secret=api_secret)
    # start is required to initialise its internal loop
    twm.start()

    def handle_socket_message(msg):
        print(f"message type: {msg['e']}")
        print(msg)

    twm.start_kline_socket(callback=handle_socket_message, symbol=symbol)

    # multiple sockets can be started
    twm.start_depth_socket(callback=handle_socket_message, symbol=symbol)

    # or a multiplex socket can be started like this
    # see Binance docs for stream names
```

(continues on next page)

(continued from previous page)

```

streams = ['bnbbtc@miniTicker', 'bnbbtc@bookTicker']
twm.start_mux_socket(callback=handle_socket_message, streams=streams)

twm.join()

if __name__ == "__main__":
    main()

```

Stop Individual Stream

When starting a stream, a name for that stream will be returned. This can be used to stop that individual stream.

```

from binance import ThreadedWebsocketManager

symbol = 'BNBBTC'

twm = ThreadedWebsocketManager()
# start is required to initialise its internal loop
twm.start()

def handle_socket_message(msg):
    print(f"message type: {msg['e']}")
    print(msg)

    twm.start_kline_socket(callback=handle_socket_message, symbol=symbol)
depth_stream_name = twm.start_depth_socket(callback=handle_socket_message,
↪symbol=symbol)

# some time later

twm.stop_socket(depth_stream_name)

```

Stop All Streams

```

from binance import ThreadedWebsocketManager

twm = ThreadedWebsocketManager()
# start is required to initialise its internal loop
twm.start()

def handle_socket_message(msg):
    print(f"message type: {msg['e']}")
    print(msg)

depth_stream_name = twm.start_depth_socket(callback=handle_socket_message,
↪symbol=symbol)

twm.stop()

```

Attempting to start a stream after *stop* is called will not work.

BinanceSocketManager Websocket Usage

Create the manager like so, passing an AsyncClient.

```
import asyncio
from binance import AsyncClient, BinanceSocketManager

async def main():
    client = await AsyncClient.create()
    bm = BinanceSocketManager(client)
    # start any sockets here, i.e a trade socket
    ts = bm.trade_socket('BNBBTC')
    # then start receiving messages
    async with ts as tscm:
        while True:
            res = await tscm.recv()
            print(res)

    await client.close_connection()

if __name__ == "__main__":
    loop = asyncio.get_event_loop()
    loop.run_until_complete(main())
```

Set a custom timeout for the websocket connections

```
# set a timeout of 60 seconds
bm = BinanceSocketManager(client, user_timeout=60)
```

Manually enter and exit the Asynchronous context manager

```
ts = bm.trade_socket('BNBBTC')
# enter the context manager
await ts.__aenter__()
# receive a message
msg = await ts.recv()
print(msg)
# exit the context manager
await ts.__aexit__(None, None, None)
```

Using a different TLD

The ThreadedWebsocketManager can take the tld when created if required.

```
from binance.streams import ThreadedWebsocketManager

twm = ThreadedWebsocketManager(tld='us')
```

The BinanceSocketManager uses the same tld value as the AsyncClient that is passed in. To use the 'us' tld we can do this.

```
from binance import AsyncClient, BinanceSocketManager

async def x():
    client = await AsyncClient.create(tld='us')
    bm = BinanceSocketManager(client)

    # start a socket...
```

(continues on next page)

(continued from previous page)

```
await client.close_connection()
```

Websocket Errors

If the websocket is disconnected and is unable to reconnect, a message is sent to the callback to indicate this. The format is

```
{
    'e': 'error',
    'm': 'Max reconnect retries reached'
}

# check for it like so
def process_message(msg):
    if msg['e'] == 'error':
        # close and restart the socket
    else:
        # process message normally
```

Multiplex Socket

Create a socket combining multiple streams.

These streams can include the depth, kline, ticker and trade streams but not the user stream which requires extra authentication.

Symbols in socket name must be lowercase i.e `bnbbtc@aggTrade`, `neobtc@ticker`

See the [Binance Websocket Streams API documentation](#) for details on socket names.

```
# pass a list of stream names
ms = bm.multiplex_socket(['bnbbtc@aggTrade', 'neobtc@ticker'])
```

Depth Socket

Depth sockets have an optional depth parameter to receive partial book rather than a diff response. By default this the diff response is returned. Valid depth values are 5, 10 and 20 and defined as enums.

```
# depth diff response
ds = bm.depth_socket('BNBBTC')

# partial book response
ds = bm.depth_socket('BNBBTC', depth=BinanceSocketManager.WEBSOCKET_DEPTH_5)
```

Kline Socket

Kline sockets have an optional interval parameter. By default this is set to 1 minute. Valid interval values are defined as enums.

```
from binance.enums import *
ks = bm.kline_socket('BNBBTC', interval=KLINE_INTERVAL_30MINUTE)
```

Aggregated Trade Socket

```
ats = bm.aggtrade_socket('BNBBTC')
```

Trade Socket

```
ts = bm.trade_socket('BNBBTC')
```

Symbol Ticker Socket

```
sts = bm.symbol_ticker_socket('BNBBTC')
```

Ticker Socket

```
ts = bm.ticker_socket(process_message)
```

Mini Ticker Socket

```
# by default updates every second
mts = bm.miniticker_socket()

# this socket can take an update interval parameter
# set as 5000 to receive updates every 5 seconds
mts = bm.miniticker_socket(5000)
```

User Socket

This watches for 3 different user events

- Account Update Event
- Order Update Event
- Trade Update Event

The Manager handles keeping the socket alive.

There are separate sockets for Spot, Cross-margin and separate Isolated margin accounts.

Spot trading


```
bm.user_socket()
```

Cross-margin

```
bm.margin_socket()
```

Isolated margin

```
bm.isolated_margin_socket(symbol)
```

6.1.9 Depth Cache

To follow the depth cache updates for a symbol there are 2 options similar to websockets.

Use the `DepthCacheManager` (or `OptionsDepthCacheManager` for vanilla options) or use the `ThreadedDepthCacheManager` if you don't want to interact with asyncio.

ThreadedDepthCacheManager Websocket Usage

Starting sockets on the `ThreadedDepthCacheManager` requires a callback parameter, similar to old implementations of depth cache on python-binance pre v1

`ThreadedDepthCacheManager` takes similar parameters to the `Client` class as it creates an `AsyncClient` internally.

As these use threads `start()` is required to be called before starting any depth cache streams.

To keep the `ThreadedDepthCacheManager` running using `join()` to join it to the main thread.

```
from binance import ThreadedDepthCacheManager

def main():

    dcm = ThreadedDepthCacheManager()
    # start is required to initialise its internal loop
    dcm.start()

    def handle_depth_cache(depth_cache):
        print(f"symbol {depth_cache.symbol}")
        print("top 5 bids")
        print(depth_cache.get_bids()[:5])
        print("top 5 asks")
        print(depth_cache.get_asks()[:5])
        print("last update time {}".format(depth_cache.update_time))

    dcm_name = dcm.start_depth_cache(handle_depth_cache, symbol='BNBBTC')

    # multiple depth caches can be started
    dcm_name = dcm.start_depth_cache(handle_depth_cache, symbol='ETHBTC')

    dcm.join()
```

(continues on next page)

(continued from previous page)

```
if __name__ == "__main__":
    main()
```

Stop Individual Depth Cache

When starting a stream, a name for that stream will be returned. This can be used to stop that individual stream

```
from binance import ThreadedDepthCacheManager

symbol = 'BNBBTC'

dcm = ThreadedDepthCacheManager()
dcm.start()

def handle_depth_cache(depth_cache):
    print(f"message type: {msg['e']}")
    print(msg)

dcm_name = dcm.start_depth_cache(handle_depth_cache, symbol='BNBBTC')

# some time later

dcm.stop_socket(dcm_name)
```

Stop All Depth Cache streams

```
from binance import ThreadedDepthCacheManager

symbol = 'BNBBTC'

dcm = ThreadedDepthCacheManager()
dcm.start()

def handle_depth_cache(depth_cache):
    print(f"message type: {msg['e']}")
    print(msg)

dcm_name = dcm.start_depth_cache(handle_depth_cache, symbol='BNBBTC')

# some time later

dcm.stop()
```

Attempting to start a stream after *stop* is called will not work.

DepthCacheManager or OptionsDepthCacheManager Usage

Create the manager like so, passing the async api client, symbol and an optional callback function.

```
import asyncio

from binance import AsyncClient, DepthCacheManager

async def main():
```

(continues on next page)

(continued from previous page)

```

client = await AsyncClient.create()
dcm = DepthCacheManager(client, 'BNBBTC')

async with dcm as dcm_socket:
    while True:
        depth_cache = await dcm_socket.recv()
        print("symbol {}".format(depth_cache.symbol))
        print("top 5 bids")
        print(depth_cache.get_bids()[:5])
        print("top 5 asks")
        print(depth_cache.get_asks()[:5])
        print("last update time {}".format(depth_cache.update_time))

if __name__ == "__main__":
    loop = asyncio.get_event_loop()
    loop.run_until_complete(main())

```

The `DepthCacheManager` returns an Asynchronous Context Manager which can be used with `async for` or by interacting with the `__aenter__` and `__aexit__` functions

By default the depth cache will fetch the order book via REST request every 30 minutes. This duration can be changed by using the `refresh_interval` parameter. To disable the refresh pass 0 or None. The socket connection will stay open receiving updates to be replayed once the full order book is received.

Share a Socket Manager

Here `dcm1` and `dcm2` share the same instance of `BinanceSocketManager`

```

from binance.websockets import BinanceSocketManager
from binance.depthcache import DepthCacheManager
bm = BinanceSocketManager(client)
dcm1 = DepthCacheManager(client, 'BNBBTC', bm=bm)
dcm2 = DepthCacheManager(client, 'ETHBTC', bm=bm)

```

Websocket Errors

If the underlying websocket is disconnected and is unable to reconnect None is returned for the `depth_cache` parameter.

Examples

```

# 1 hour interval refresh
dcm = DepthCacheManager(client, 'BNBBTC', refresh_interval=60*60)

# disable refreshing
dcm = DepthCacheManager(client, 'BNBBTC', refresh_interval=0)

```

```

async with dcm as dcm_socket:
    while True:
        depth_cache = await dcm_socket.recv()
        print("symbol {}".format(depth_cache.symbol))
        print("top 5 bids")

```

(continues on next page)

(continued from previous page)

```

print(depth_cache.get_bids()[:5])
print("top 5 asks")
print(depth_cache.get_asks()[:5])
print("last update time {}".format(depth_cache.update_time))

```

To use the magic `__aenter__` and `__aexit__` functions to use this class without the `async with`

```

dcm = DepthCacheManager(client, 'BNBBTC')

await dcm.__aenter__()
depth_cache = await dcm.recv()
print("symbol {}".format(depth_cache.symbol))
print("top 5 bids")
print(depth_cache.get_bids()[:5])
print("top 5 asks")
print(depth_cache.get_asks()[:5])
print("last update time {}".format(depth_cache.update_time))

# exit the context manager
await dcm.__aexit__(None, None, None)

```

6.1.10 Withdraw Endpoints

Place a withdrawal

Make sure you enable Withdrawal permissions for your API Key to use this call.

You must have withdrawn to the address through the website and approved the withdrawal via email before you can withdraw using the API.

```

from binance.exceptions import BinanceAPIException
try:
    # name parameter will be set to the asset value by the client if not passed
    result = client.withdraw(
        coin='ETH',
        address='<eth_address>',
        amount=100)
except BinanceAPIException as e:
    print(e)
else:
    print("Success")

# passing a name parameter
result = client.withdraw(
    coin='ETH',
    address='<eth_address>',
    amount=100,
    name='Withdraw')

# if the coin requires a extra tag or name such as XRP or XMR then pass an
↪ `addressTag` parameter.
result = client.withdraw(
    coin='XRP',
    address='<xrp_address>',

```

(continues on next page)

(continued from previous page)

```
addressTag='<xrp_address_tag>',
amount=10000)
```

Fetch deposit history

```
deposits = client.get_deposit_history()
btc_deposits = client.get_deposit_history(coin='BTC')
```

Fetch withdraw history

```
withdraws = client.get_withdraw_history()
btc_withdraws = client.get_withdraw_history(coin='BTC')
```

Get deposit address

```
address = client.get_deposit_address(coin='BTC')
```

6.1.11 Helper Functions

`binance.helpers`
alias of `binance.helpers`

6.1.12 Exceptions

`BinanceRequestException`

Raised if a non JSON response is returned

`BinanceAPIException`

On an API call error a `binance.exceptions.BinanceAPIException` will be raised.

The exception provides access to the

- `status_code` - response status code
- `response` - response object
- `code` - Binance error code
- `message` - Binance error message
- `request` - request object if available

```
try:
    client.get_all_orders()
except BinanceAPIException as e:
    print e.status_code
    print e.message
```

6.1.13 FAQ

Q: Why do I get “Timestamp for this request is not valid”

A: This occurs in 2 different cases.

The timestamp sent is outside of the serverTime - recvWindow value The timestamp sent is more than 1000ms ahead of the server time

Check that your system time is in sync. See [this issue](#) for some sample code to check the difference between your local time and the Binance server time.

Q: Why do I get “Signature for this request is not valid”

A1: One of your parameters may not be in the correct format.

Check recvWindow is an integer and not a string.

A2: You may need to regenerate your API Key and Secret

A3: You may be attempting to access the API from a Chinese IP address, these are now restricted by Binance.

6.1.14 Changelog

v1.0.15 - 2021-09-27

Added

- Enable/disable margin account for symbol endpoints
- Top trader long/short positions endpoint
- Global long/short ratio endpoint

Fixed

- fix websockets to 9.1
- websocket reconnect updates
- fix futures kline sockets

v1.0.14 - 2021-09-08

Fixed

- websocket reconnecting

v1.0.13 - 2021-09-08

Added

- Futures Depth Cache Manager
- Futures kline websocket stream
- Coin Futures User websocket stream
- New Margin endpoints
- Margin OCO order endpoints

- Fiat endpoints
- C2C endpoints
- Account API permissions endpoint

Fixed

- changed *asset* to *coin* in withdraw endpoint

v1.0.12 - 2021-06-03

Added

- coin futures batch order function

Fixed

- threaded websockets on python3.9
- filter out None params in request kwargs
- deconflict streams with same name on different websocket urls
- reduce close timeout on websocket close to short time to reduce waiting

v1.0.10 - 2021-05-13

Added

- futures multi-asset margin mode endpoints
- optional symbol param to `get_all_tickers`

Fixed

- `start_multiplex_socket` remove lower case filter on stream names

v1.0.9 - 2021-05-12

Fixed

- `start_book_ticker_socket` and `start_multiplex_socket` to call correct async function

v1.0.8 - 2021-05-11

Added

- old style websocket and depth cache managers as option without interacting with asyncio

Fixed

- fixed issue with `get_historical_klines` in Client
- remove print debug line

v1.0.7

Fixed

- remove version param from `get_sub_account_assets`

v1.0.6

Fixed

- fix time for authenticated stream keepalive

v1.0.5

Fixed

- Restored access to last response on client

v1.0.4

Added

- Futures Testnet support
- Kline type for fetching historical klines

Fixed

- Spot Testnet websocket URL

v1.0.3

Added

- Spot Testnet support

v1.0.2

Added

- start of typing to client and websockets

Fixed

- end_str, limit, spot params in kline fetching
- drop None values in params passed

Updated

- more examples in docs

v1.0.1

Fixed

- restored params for Client and AsyncClient classes

v1.0.0

Added

- Async support for all REST endpoints
- USD-M and Coin-M Futures websocket streams
- Websockets use same tld as Client
- convert type option for DepthCache

Breaking Changes

- Supports only py3.6+
- All wapi calls changed to sapi
- Websockets have changed to use Asynchronous context managers

Fixed

- get_historical_klines params

v0.7.11

Added - Vanilla Options REST endpoints - Vanilla Options websockets - Futures order type enums

Updated

- websocket keep-alive functions for different socket types
- dependencies

Fixed

- change to User-Agent to avoid connection issues

v0.7.5.dev

Changed - Stock json lib to ujson (<https://github.com/sammchardy/python-binance/pull/383>)

v0.7.5 - 2020-02-06

Added

- Futures REST endpoints
- Lending REST endpoints
- OCO Orders function *create_oco_order*, *order_oco_buy*, *order_oco_sell*
- Average Price function *get_avg_price*
- Support for other domains (.us, .jp, etc)

Updated

- dependencies

Fixed

- websocket keepalive callback not found

v0.7.4 - 2019-09-22

Added

- symbol book ticker websocket streams
- margin websocket stream

Updated

- can call Client without any params
- make response a property of the Client class so you can access response properties after a request

Fixed

- issue with None value params causing errors

v0.7.3 - 2019-08-12

Added

- sub account endpoints
- dust transfer endpoint
- asset dividend history endpoint

Removed

- deprecated withdraw fee endpoint

v0.7.2 - 2019-08-01

Added

- margin trading endpoints

Fixed

- depth cache clearing bug

v0.7.1 - 2019-01-23

Added

- limit param to DepthCacheManager
- limit param to get_historical_klines
- update_time to DepthCache class

Updated

- test coverage

Fixed

- super init in Websocket class
- removal of request params from signature
- empty set issue in aggregate_trade_iter

v0.7.0 - 2018-08-08

Added

- `get_asset_details` endpoint
- `get_dust_log` endpoint
- `get_trade_fee` endpoint
- ability for multiple `DepthCacheManagers` to share a `BinanceSocketManager`
- `get_historical_klines_generator` function
- custom socket timeout param for `BinanceSocketManager`

Updated

- general dependency version
- removed support for python3.3

Fixed

- add a super init on `BinanceClientProtocol`

v0.6.9 - 2018-04-27

Added

- timestamp in milliseconds to `get_historical_klines` function
- timestamp in milliseconds to `aggregate_trade_iter` function

Fixed

- Don't close user stream listen key on socket close

v0.6.8 - 2018-03-29

Added

- `get_withdraw_fee` function

Fixed

- Remove unused `LISTENKEY_NOT_EXISTS`
- Optimise the historical klines function to reduce requests
- Issue with `end_time` in aggregate trade iterator

v0.6.7 - 2018-03-14

Fixed

- Issue with `get_historical_klines` when response had exactly 500 results
- Changed `BinanceResponseException` to `BinanceRequestException`
- Set default code value in `BinanceApiException` properly

v0.6.6 - 2018-02-17

Fixed

- User stream websocket keep alive strategy updated

v0.6.5 - 2018-02-13

Fixed

- *get_historical_klines* response for month interval

v0.6.4 - 2018-02-09

Added

- system status endpoint *get_system_status*

v0.6.3 - 2018-01-29

Added

- mini ticker socket function *start_miniticker_socket*
- aggregate trade iterator *aggregate_trade_iter*

Fixes

- clean up *interval_to_milliseconds* logic
- general doc and file cleanups

v0.6.2 - 2018-01-12

Fixes

- fixed handling Binance errors that aren't JSON objects

v0.6.1 - 2018-01-10

Fixes

- added missing dateparser dependency to setup.py
- documentation fixes

v0.6.0 - 2018-01-09

New version because why not.

Added

- *get_historical_klines* function to fetch klines for any date range
- ability to override requests parameters globally
- error on websocket disconnect

- example related to blog post

Fixes

- documentation fixes

v0.5.17 - 2018-01-08

Added

- check for name parameter in withdraw, set to asset parameter if not passed

Update

- Windows install error documentation

Removed

- reference to disable_validation in documentation

v0.5.16 - 2018-01-06

Added

- addressTag documentation to withdraw function
- documentation about requests proxy environment variables

Update

- FAQ for signature error with solution to regenerate API key
- change create_order to create_test_order in example

Fixed

- reference to BinanceAPIException in documentation

v0.5.15 - 2018-01-03

Fixed

- removed all references to WEBSOCKET_DEPTH_1 enum

v0.5.14 - 2018-01-02

Added

- Wait for depth cache socket to start
- check for sequential depth cache messages

Updated

- documentation around depth websocket and diff and partial responses

Removed

- Removed unused WEBSOCKET_DEPTH_1 enum
- removed unused libraries and imports

v0.5.13 - 2018-01-01

Fixed

- Signature invalid error

v0.5.12 - 2017-12-29

Added

- `get_asset_balance` helper function to fetch an individual asset's balance

Fixed

- added timeout to requests call to prevent hanging
- changed variable type to str for price parameter when creating an order
- documentation fixes

v0.5.11 - 2017-12-28

Added

- refresh interval parameter to depth cache to keep it fresh, set default at 30 minutes

Fixed

- watch depth cache socket before fetching order book to replay any messages

v0.5.10 - 2017-12-28

Updated

- updated dependencies `certifi` and `cryptography` to help resolve signature error

v0.5.9 - 2017-12-26

Fixed

- fixed websocket reconnecting, was no distinction between manual close or network error

v0.5.8 - 2017-12-25

Changed

- change symbol parameter to optional for `get_open_orders` function
- added `listenKey` parameter to `stream_close` function

Added

- `get_account_status` function that was missed

v0.5.7 - 2017-12-24

Changed

- change depth cache callback parameter to optional

Added

- note about stopping Twisted reactor loop to exit program

v0.5.6 - 2017-12-20

Added

- `get_symbol_info` function to simplify getting info about a particular symbol

v0.5.5 - 2017-12-19

Changed

- Increased default limit for order book on depth cache from 10 to 500

v0.5.4 - 2017-12-14

Added

- `symbol` property made public on `DepthCache` class

Changed

- Enums now also accessible from `binance.client.Client` and `binance.websockets.BinanceSocketManager`

v0.5.3 - 2017-12-09

Changed

- User stream refresh timeout from 50 minutes to 30 minutes
- User stream socket listen key change check simplified

v0.5.2 - 2017-12-08

Added

- `start_multiplex_socket` function to `BinanceSocketManager` to create multiplexed streams

v0.5.1 - 2017-12-06

Added

- `Close` method for `DepthCacheManager`

Fixes

- Fixed modifying array error message when closing the `BinanceSocketManager`

v0.5.0 - 2017-12-05

Updating to match new API documentation

Added

- Recent trades endpoint
- Historical trades endpoint
- Order response type option
- Check for invalid user stream listen key in socket to keep connected

Fixes

- Fixed exchange info endpoint as it was renamed slightly

v0.4.3 - 2017-12-04

Fixes

- Fixed stopping sockets where they were reconnecting
- Fixed websockets unable to be restarted after close
- Exception in parsing non-JSON websocket message

v0.4.2 - 2017-11-30

Removed

- Removed websocket update time as Oms option is not available

v0.4.1 - 2017-11-24

Added

- Reconnecting websockets, automatic retry on disconnect

v0.4.0 - 2017-11-19

Added

- Get deposit address endpoint
- Upgraded withdraw endpoints to v3
- New exchange info endpoint with rate limits and full symbol info

Removed

- Order validation to return at a later date

v0.3.8 - 2017-11-17

Fixes

- Fix order validation for market orders
- WEBSOCKET_DEPTH_20 value, 20 instead of 5
- General tidy up

v0.3.7 - 2017-11-16

Fixes

- Fix multiple depth caches sharing a cache by initialising bid and ask objects each time

v0.3.6 - 2017-11-15

Fixes

- check if Reactor is already running

v0.3.5 - 2017-11-06

Added

- support for BNB market

Fixes

- fixed error if new market type is created that we don't know about

v0.3.4 - 2017-10-31

Added

- depth parameter to depth socket
- interval parameter to kline socket
- update time parameter for compatible sockets
- new enums for socket depth and update time values
- better websocket documentation

Changed

- Depth Cache Manager uses 0ms socket update time
- connection key returned when creating socket, this key is then used to stop it

Fixes

- General fixes

v0.3.3 - 2017-10-31

Fixes

- Fixes for broken tests

v0.3.2 - 2017-10-30

Added

- More test coverage of requests

Fixes

- Order quantity validation fix

v0.3.1 - 2017-10-29

Added

- Withdraw exception handler with translation of obscure error

Fixes

- Validation fixes

v0.3.0 - 2017-10-29

Added

- Withdraw endpoints
- Order helper functions

v0.2.0 - 2017-10-27

Added

- Symbol Depth Cache

v0.1.6 - 2017-10-25

Changes

- Upgrade to v3 signed endpoints
- Update function documentation

v0.1.5 - 2017-09-12

Changes

- Added get_all_tickers call
- Added get_orderbook_tickers call
- Added some FAQs

Fixes

- Fix error in enum value

v0.1.4 - 2017-09-06

Changes

- Added parameter to disable client side order validation

v0.1.3 - 2017-08-26

Changes

- Updated documentation

Fixes

- Small bugfix

v0.1.2 - 2017-08-25

Added

- Travis.CI and Coveralls support

Changes

- Validation for pairs using public endpoint

v0.1.1 - 2017-08-17

Added

- Validation for HSR/BTC pair

v0.1.0 - 2017-08-16

Websocket release

Added

- Websocket manager
- Order parameter validation
- Order and Symbol enums
- API Endpoints for Data Streams

v0.0.2 - 2017-08-14

Initial version

Added

- General, Market Data and Account endpoints

6.1.15 Binance API

client module

```
class binance.client.AsyncClient (api_key: Optional[str] = None, api_secret: Optional[str] =  
None, requests_params: Dict[str, str] = None, tld: str =  
'com', testnet: bool = False, loop=None)
```

Bases: `binance.client.BaseClient`

```
__init__ (api_key: Optional[str] = None, api_secret: Optional[str] = None, requests_params:  
Dict[str, str] = None, tld: str = 'com', testnet: bool = False, loop=None)  
Binance API Client constructor
```

Parameters

- **api_key** (*str.*) – Api Key
- **api_secret** (*str.*) – Api Secret
- **requests_params** (*dict.*) – optional - Dictionary of requests params to use for all calls
- **testnet** (*bool*) – Use testnet environment - only available for vanilla options at the moment

```
aggregate_trade_iter (symbol, start_str=None, last_id=None)
```

Iterate over aggregate trade data from (start_time or last_id) to the end of the history so far.

If start_time is specified, start with the first trade after start_time. Meant to initialise a local cache of trade data.

If last_id is specified, start with the trade after it. This is meant for updating a pre-existing local trade data cache.

Only allows start_str or last_id—not both. Not guaranteed to work right if you're running more than one of these simultaneously. You will probably hit your rate limit.

See dateparser docs for valid start and end string formats <http://dateparser.readthedocs.io/en/latest/>

If using offset strings for dates add “UTC” to date string e.g. “now UTC”, “11 hours ago UTC”

Parameters

- **symbol** (*str*) – Symbol string e.g. ETHBTC
- **start_str** – Start date string in UTC format or timestamp in milliseconds. The iterator will

return the first trade occurring later than this time. :type start_str: str :param last_id: aggregate trade ID of the last known aggregate trade. Not a regular trade ID. See <https://binance-docs.github.io/apidocs/spot/en/#compressed-aggregate-trades-list>

Returns an iterator of JSON objects, one per trade. The format of each object is identical to `Client.aggregate_trades()`.

```
cancel_margin_oco_order (**params)
```

```
cancel_margin_order (**params)
```

```
cancel_order (**params)
```

Cancel an active order. Either orderId or origClientId must be sent.

<https://binance-docs.github.io/apidocs/spot/en/#cancel-order-trade>

Parameters

- **symbol** (*str*) – required
- **orderId** (*int*) – The unique order id
- **origClientId** (*str*) – optional
- **newClientId** (*str*) – Used to uniquely identify this cancel. Automatically generated by default.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "symbol": "LTCBTC",
  "origClientId": "myOrder1",
  "orderId": 1,
  "clientOrderId": "cancelMyOrder1"
}
```

Raises BinanceRequestException, BinanceAPIException

change_fixed_activity_to_daily_position (**params)

close_connection ()

classmethod create (*api_key: Optional[str] = None, api_secret: Optional[str] = None, requests_params: Dict[str, str] = None, tld: str = 'com', testnet: bool = False, loop=None*)

create_isolated_margin_account (**params)

create_margin_loan (**params)

create_margin_oco_order (**params)

create_margin_order (**params)

create_oco_order (**params)

Send in a new OCO order

<https://binance-docs.github.io/apidocs/spot/en/#new-oco-trade>

Parameters

- **symbol** (*str*) – required
- **listClientId** (*str*) – A unique id for the list order. Automatically generated if not sent.
- **side** (*str*) – required
- **quantity** (*decimal*) – required
- **limitClientId** (*str*) – A unique id for the limit order. Automatically generated if not sent.
- **price** (*str*) – required
- **limitIcebergQty** (*decimal*) – Used to make the LIMIT_MAKER leg an iceberg order.
- **stopClientId** (*str*) – A unique id for the stop order. Automatically generated if not sent.

- **stopPrice** (*str*) – required
- **stopLimitPrice** (*str*) – If provided, stopLimitTimeInForce is required.
- **stopIcebergQty** (*decimal*) – Used with STOP_LOSS_LIMIT leg to make an iceberg order.
- **stopLimitTimeInForce** (*str*) – Valid values are GTC/FOK/IOC.
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

Response ACK:

```
{
}
```

Response RESULT:

```
{
}
```

Response FULL:

```
{
}
```

Raises BinanceRequestException, BinanceAPIException, BinanceOrderException, BinanceOrderMinAmountException, BinanceOrderMinPriceException, BinanceOrderMinTotalException, BinanceOrderUnknownSymbolException, BinanceOrderInactiveSymbolException

create_order (***params*)

Send in a new order

Any order with an icebergQty MUST have timeInForce set to GTC.

<https://binance-docs.github.io/apidocs/spot/en/#new-order-trade>

Parameters

- **symbol** (*str*) – required
- **side** (*str*) – required
- **type** (*str*) – required
- **timeInForce** (*str*) – required if limit order
- **quantity** (*decimal*) – required
- **quoteOrderQty** (*decimal*) – amount the user wants to spend (when buying) or receive (when selling) of the quote asset, applicable to MARKET orders
- **price** (*str*) – required
- **newClientOrderId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **icebergQty** (*decimal*) – Used with LIMIT, STOP_LOSS_LIMIT, and TAKE_PROFIT_LIMIT to create an iceberg order.

- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

Response ACK:

```
{
  "symbol": "LTCBTC",
  "orderId": 1,
  "clientOrderId": "myOrder1" # Will be newClientOrderId
  "transactTime": 1499827319559
}
```

Response RESULT:

```
{
  "symbol": "BTCUSDT",
  "orderId": 28,
  "clientOrderId": "6gCrw2kRUAf9CvJDGP16IP",
  "transactTime": 1507725176595,
  "price": "0.00000000",
  "origQty": "10.00000000",
  "executedQty": "10.00000000",
  "status": "FILLED",
  "timeInForce": "GTC",
  "type": "MARKET",
  "side": "SELL"
}
```

Response FULL:

```
{
  "symbol": "BTCUSDT",
  "orderId": 28,
  "clientOrderId": "6gCrw2kRUAf9CvJDGP16IP",
  "transactTime": 1507725176595,
  "price": "0.00000000",
  "origQty": "10.00000000",
  "executedQty": "10.00000000",
  "status": "FILLED",
  "timeInForce": "GTC",
  "type": "MARKET",
  "side": "SELL",
  "fills": [
    {
      "price": "4000.00000000",
      "qty": "1.00000000",
      "commission": "4.00000000",
      "commissionAsset": "USDT"
    },
    {
      "price": "3999.00000000",
      "qty": "5.00000000",
      "commission": "19.99500000",
      "commissionAsset": "USDT"
    }
  ],
}
```

(continues on next page)

(continued from previous page)

```

    {
        "price": "3998.00000000",
        "qty": "2.00000000",
        "commission": "7.99600000",
        "commissionAsset": "USDT"
    },
    {
        "price": "3997.00000000",
        "qty": "1.00000000",
        "commission": "3.99700000",
        "commissionAsset": "USDT"
    },
    {
        "price": "3995.00000000",
        "qty": "1.00000000",
        "commission": "3.99500000",
        "commissionAsset": "USDT"
    }
]
}

```

Raises `BinanceRequestException`, `BinanceAPIException`, `BinanceOrderException`, `BinanceOrderMinAmountException`, `BinanceOrderMinPriceException`, `BinanceOrderMinTotalException`, `BinanceOrderUnknownSymbolException`, `BinanceOrderInactiveSymbolException`

create_sub_account_futures_transfer (***params*)

create_test_order (***params*)

Test new order creation and signature/recvWindow long. Creates and validates a new order but does not send it into the matching engine.

<https://binance-docs.github.io/apidocs/spot/en/#test-new-order-trade>

Parameters

- **symbol** (*str*) – required
- **side** (*str*) – required
- **type** (*str*) – required
- **timeInForce** (*str*) – required if limit order
- **quantity** (*decimal*) – required
- **price** (*str*) – required
- **newClientOrderId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **icebergQty** (*decimal*) – Used with iceberg orders
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – The number of milliseconds the request is valid for

Returns API response

```
{}
```


Raises `BinanceRequestException`, `BinanceAPIException`, `BinanceOrderException`, `BinanceOrderMinAmountException`, `BinanceOrderMinPriceException`, `BinanceOrderMinTotalException`, `BinanceOrderUnknownSymbolException`, `BinanceOrderInactiveSymbolException`

`disable_fast_withdraw_switch (**params)`
`disable_isolated_margin_account (**params)`
`enable_fast_withdraw_switch (**params)`
`enable_isolated_margin_account (**params)`
`enable_subaccount_futures (**params)`
`enable_subaccount_margin (**params)`
`futures_account (**params)`
`futures_account_balance (**params)`
`futures_account_trades (**params)`
`futures_account_transfer (**params)`
`futures_adl_quantile_estimate (**params)`
`futures_aggregate_trades (**params)`
`futures_cancel_all_open_orders (**params)`
`futures_cancel_order (**params)`
`futures_cancel_orders (**params)`
`futures_change_leverage (**params)`
`futures_change_margin_type (**params)`
`futures_change_multi_assets_mode (multiAssetsMargin: bool)`
`futures_change_position_margin (**params)`
`futures_change_position_mode (**params)`
`futures_coin_account (**params)`
`futures_coin_account_balance (**params)`
`futures_coin_account_trades (**params)`
`futures_coin_aggregate_trades (**params)`
`futures_coin_cancel_all_open_orders (**params)`
`futures_coin_cancel_order (**params)`
`futures_coin_cancel_orders (**params)`
`futures_coin_change_leverage (**params)`
`futures_coin_change_margin_type (**params)`
`futures_coin_change_position_margin (**params)`
`futures_coin_change_position_mode (**params)`
`futures_coin_continuous_klines (**params)`
`futures_coin_create_order (**params)`

```
futures_coin_exchange_info ()
futures_coin_funding_rate (**params)
futures_coin_get_all_orders (**params)
futures_coin_get_open_orders (**params)
futures_coin_get_order (**params)
futures_coin_get_position_mode (**params)
futures_coin_historical_trades (**params)
futures_coin_income_history (**params)
futures_coin_index_price_klines (**params)
futures_coin_klines (**params)
futures_coin_leverage_bracket (**params)
futures_coin_liquidation_orders (**params)
futures_coin_mark_price (**params)
futures_coin_mark_price_klines (**params)
futures_coin_open_interest (**params)
futures_coin_open_interest_hist (**params)
futures_coin_order_book (**params)
futures_coin_orderbook_ticker (**params)
futures_coin_ping ()
futures_coin_place_batch_order (**params)
futures_coin_position_information (**params)
futures_coin_position_margin_history (**params)
futures_coin_recent_trades (**params)
futures_coin_stream_close (listenKey)
futures_coin_stream_get_listen_key ()
futures_coin_stream_keepalive (listenKey)
futures_coin_symbol_ticker (**params)
futures_coin_ticker (**params)
futures_coin_time ()
futures_continuous_klines (**params)
futures_create_order (**params)
futures_exchange_info ()
futures_funding_rate (**params)
futures_get_all_orders (**params)
futures_get_multi_assets_mode ()
futures_get_open_orders (**params)
```

```

futures_get_order (**params)
futures_get_position_mode (**params)
futures_global_longshort_ratio (**params)
futures_historical_klines (symbol, interval, start_str, end_str=None, limit=500)
futures_historical_klines_generator (symbol, interval, start_str, end_str=None)
futures_historical_trades (**params)
futures_income_history (**params)
futures_klines (**params)
futures_leverage_bracket (**params)
futures_liquidation_orders (**params)
futures_mark_price (**params)
futures_open_interest (**params)
futures_open_interest_hist (**params)
futures_order_book (**params)
futures_orderbook_ticker (**params)
futures_ping ()
futures_place_batch_order (**params)
futures_position_information (**params)
futures_position_margin_history (**params)
futures_recent_trades (**params)
futures_stream_close (listenKey)
futures_stream_get_listen_key ()
futures_stream_keepalive (listenKey)
futures_symbol_ticker (**params)
futures_ticker (**params)
futures_time ()
futures_top_longshort_account_ratio (**params)
futures_top_longshort_position_ratio (**params)
get_account (**params)

```

Get current account information.

https://binance-docs.github.io/apidocs/spot/en/#account-information-user_data

Parameters `recvWindow` (*int*) – the number of milliseconds the request is valid for

Returns API response

```

{
  "makerCommission": 15,
  "takerCommission": 15,
  "buyerCommission": 0,

```

(continues on next page)

(continued from previous page)

```

"sellerCommission": 0,
"canTrade": true,
"canWithdraw": true,
"canDeposit": true,
"balances": [
  {
    "asset": "BTC",
    "free": "4723846.89208129",
    "locked": "0.00000000"
  },
  {
    "asset": "LTC",
    "free": "4763368.68006011",
    "locked": "0.00000000"
  }
]
}

```

Raises `BinanceRequestException`, `BinanceAPIException`

get_account_api_permissions (**params)

Fetch api key permissions.

https://binance-docs.github.io/apidocs/spot/en/#get-api-key-permission-user_data

Parameters `recvWindow` (*int*) – the number of milliseconds the request is valid for

Returns API response

```

{
  "ipRestrict": false,
  "createTime": 1623840271000,
  "enableWithdrawals": false, // This option allows you to withdraw via
↪API. You must apply the IP Access Restriction filter in order to enable
↪withdrawals
  "enableInternalTransfer": true, // This option authorizes this key to
↪transfer funds between your master account and your sub account instantly
  "permitsUniversalTransfer": true, // Authorizes this key to be used for a
↪dedicated universal transfer API to transfer multiple supported currencies.
↪Each business's own transfer API rights are not affected by this
↪authorization
  "enableVanillaOptions": false, // Authorizes this key to Vanilla options
↪trading
  "enableReading": true,
  "enableFutures": false, // API Key created before your futures account
↪opened does not support futures API service
  "enableMargin": false, // This option can be adjusted after the Cross
↪Margin account transfer is completed
  "enableSpotAndMarginTrading": false, // Spot and margin trading
  "tradingAuthorityExpirationTime": 1628985600000 // Expiration time for
↪spot and margin trading permission
}

```

get_account_api_trading_status (**params)

Fetch account api trading status detail.

https://binance-docs.github.io/apidocs/spot/en/#account-api-trading-status-sapi-user_data

Parameters `recvWindow` (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "data": {
    // API trading status detail
    "isLocked": false, // API trading function is locked or not
    "plannedRecoverTime": 0, // If API trading function is locked, this_
    ↪ is the planned recover time
    "triggerCondition": {
      "GCR": 150, // Number of GTC orders
      "IFER": 150, // Number of FOK/IOC orders
      "UFR": 300 // Number of orders
    },
    "indicators": { // The indicators updated every 30 seconds
      "BTCUSDT": [ // The symbol
        {
          "i": "UFR", // Unfilled Ratio (UFR)
          "c": 20, // Count of all orders
          "v": 0.05, // Current UFR value
          "t": 0.995 // Trigger UFR value
        },
        {
          "i": "IFER", // IOC/FOK Expiration Ratio (IFER)
          "c": 20, // Count of FOK/IOC orders
          "v": 0.99, // Current IFER value
          "t": 0.99 // Trigger IFER value
        },
        {
          "i": "GCR", // GTC Cancellation Ratio (GCR)
          "c": 20, // Count of GTC orders
          "v": 0.99, // Current GCR value
          "t": 0.99 // Trigger GCR value
        }
      ],
      "ETHUSDT": [
        {
          "i": "UFR",
          "c": 20,
          "v": 0.05,
          "t": 0.995
        },
        {
          "i": "IFER",
          "c": 20,
          "v": 0.99,
          "t": 0.99
        },
        {
          "i": "GCR",
          "c": 20,
          "v": 0.99,
          "t": 0.99
        }
      ]
    },
    "updateTime": 1547630471725
  }
}
```

`get_account_snapshot (**params)`

`get_account_status (**params)`

Get account status detail.

https://binance-docs.github.io/apidocs/spot/en/#account-status-sapi-user_data

Parameters `recvWindow (int)` – the number of milliseconds the request is valid for

Returns API response

```
{
  "data": "Normal"
}
```

`get_aggregate_trades (**params) → Dict[KT, VT]`

Get compressed, aggregate trades. Trades that fill at the time, from the same order, with the same price will have the quantity aggregated.

<https://binance-docs.github.io/apidocs/spot/en/#compressed-aggregate-trades-list>

Parameters

- **symbol** (*str*) – required
- **fromId** (*str*) – ID to get aggregate trades from INCLUSIVE.
- **startTime** (*int*) – Timestamp in ms to get aggregate trades from INCLUSIVE.
- **endTime** (*int*) – Timestamp in ms to get aggregate trades until INCLUSIVE.
- **limit** (*int*) – Default 500; max 1000.

Returns API response

```
[
  {
    "a": 26129,           # Aggregate tradeId
    "p": "0.01633102",  # Price
    "q": "4.70443515",  # Quantity
    "f": 27781,         # First tradeId
    "l": 27781,         # Last tradeId
    "T": 1498793709153, # Timestamp
    "m": true,          # Was the buyer the maker?
    "M": true           # Was the trade the best price match?
  }
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

`get_all_coins_info (**params)`

`get_all_isolated_margin_symbols (**params)`

`get_all_margin_orders (**params)`

`get_all_orders (**params)`

Get all account orders; active, canceled, or filled.

https://binance-docs.github.io/apidocs/spot/en/#all-orders-user_data

Parameters

- **symbol** (*str*) – required

- **orderId** (*int*) – The unique order id
- **startTime** (*int*) – optional
- **endTime** (*int*) – optional
- **limit** (*int*) – Default 500; max 1000.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
[
  {
    "symbol": "LTCBTC",
    "orderId": 1,
    "clientOrderId": "myOrder1",
    "price": "0.1",
    "origQty": "1.0",
    "executedQty": "0.0",
    "status": "NEW",
    "timeInForce": "GTC",
    "type": "LIMIT",
    "side": "BUY",
    "stopPrice": "0.0",
    "icebergQty": "0.0",
    "time": 1499827319559
  }
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_all_tickers (*symbol: Optional[str] = None*) → List[Dict[str, str]]
Latest price for all symbols.

<https://binance-docs.github.io/apidocs/spot/en/#symbol-price-ticker>

Returns List of market tickers

```
[
  {
    "symbol": "LTCBTC",
    "price": "4.00000200"
  },
  {
    "symbol": "ETHBTC",
    "price": "0.07946600"
  }
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_asset_balance (*asset, **params*)
Get current asset balance.

Parameters

- **asset** (*str*) – required
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns dictionary or None if not found

```
{
  "asset": "BTC",
  "free": "4723846.89208129",
  "locked": "0.00000000"
}
```

Raises BinanceRequestException, BinanceAPIException

get_asset_details (**params)

Fetch details on assets.

https://binance-docs.github.io/apidocs/spot/en/#asset-detail-sapi-user_data

Parameters

- **asset** (*str*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "CTR": {
    "minWithdrawAmount": "70.00000000", //min withdraw amount
    "depositStatus": false, //deposit status (false if ALL of networks
↪ ' are false)
    "withdrawFee": 35, // withdraw fee
    "withdrawStatus": true, //withdraw status (false if ALL of ↪
↪ networks' are false)
    "depositTip": "Delisted, Deposit Suspended" //reason
  },
  "SKY": {
    "minWithdrawAmount": "0.02000000",
    "depositStatus": true,
    "withdrawFee": 0.01,
    "withdrawStatus": true
  }
}
```

get_asset_dividend_history (**params)

Query asset dividend record.

https://binance-docs.github.io/apidocs/spot/en/#asset-dividend-record-user_data

Parameters

- **asset** (*str*) – optional
- **startTime** (*long*) – optional
- **endTime** (*long*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

```
result = client.get_asset_dividend_history()
```

Returns API response


```
{
  "rows": [
    {
      "amount": "10.00000000",
      "asset": "BHFT",
      "divTime": 1563189166000,
      "enInfo": "BHFT distribution",
      "tranId": 2968885920
    },
    {
      "amount": "10.00000000",
      "asset": "BHFT",
      "divTime": 1563189165000,
      "enInfo": "BHFT distribution",
      "tranId": 2968885920
    }
  ],
  "total": 2
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_avg_price (**params)

Current average price for a symbol.

<https://binance-docs.github.io/apidocs/spot/en/#current-average-price>

Parameters `symbol` (*str*) –

Returns API response

```
{
  "mins": 5,
  "price": "9.35751834"
}
```

get_bnb_burn_spot_margin (**params)

get_c2c_trade_history (**params)

get_deposit_address (*coin*: *str*, *network*: *Optional[str]* = *None*, **params)

Fetch a deposit address for a symbol

https://binance-docs.github.io/apidocs/spot/en/#deposit-address-supporting-network-user_data

Parameters

- `coin` (*str*) – required
- `network` (*str*) – optional
- `recvWindow` (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "address": "1HPn8Rx2y6nNSfagQBKy27GB99Vbzg89wv",
  "coin": "BTC",
  "tag": "",
  "url": "https://btc.com/1HPn8Rx2y6nNSfagQBKy27GB99Vbzg89wv"
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

`get_deposit_history (**params)`

Fetch deposit history.

https://binance-docs.github.io/apidocs/spot/en/#deposit-history-supporting-network-user_data

Parameters

- `coin` (*str*) – optional
- `startTime` (*long*) – optional
- `endTime` (*long*) – optional
- `offset` (*long*) – optional - default:0
- `limit` (*long*) – optional
- `recvWindow` (*int*) – the number of milliseconds the request is valid for

Returns API response

```
[
  {
    "amount": "0.00999800",
    "coin": "PAXG",
    "network": "ETH",
    "status": 1,
    "address": "0x788cabe9236ce061e5a892e1a59395a81fc8d62c",
    "addressTag": "",
    "txId":
    ↪ "0xaad4654a3234aa6118af9b4b335f5ae81c360b2394721c019b5d1e75328b09f3",
    "insertTime": 1599621997000,
    "transferType": 0,
    "confirmTimes": "12/12"
  },
  {
    "amount": "0.50000000",
    "coin": "IOTA",
    "network": "IOTA",
    "status": 1,
    "address":
    ↪ "SIZ9VLMHWATXKV99LH99CIGFJFUMLEHGWVZVNNZXRJJVWBPHYWPPBOSDORZ9EQSHCZAMPVAPGFYQAUUV9DROOXJLN
    ↪ ",
    "addressTag": "",
    "txId":
    ↪ "ESBFVQUTPIWQNJSPXFNHNYHSQNTGKRVKPRABQWTAXCDWOAKDKYWPTVG9BGXNVNKTLEJGESAVXIKIIZ9999
    ↪ ",
    "insertTime": 1599620082000,
    "transferType": 0,
    "confirmTimes": "1/1"
  }
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

`get_dust_log (**params)`

Get log of small amounts exchanged for BNB.

https://binance-docs.github.io/apidocs/spot/en/#dustlog-sapi-user_data

Parameters

- **startTime** (*int*) – optional
- **endTime** (*int*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "total": 8, //Total counts of exchange
  "userAssetDribblets": [
    {
      "totalTransferredAmount": "0.00132256", // Total transferred BNB_
↪amount for this exchange.
      "totalServiceChargeAmount": "0.00002699", //Total service_
↪charge amount for this exchange.
      "transId": 45178372831,
      "userAssetDribbletDetails": [ //Details of this_
↪exchange.
        {
          "transId": 4359321,
          "serviceChargeAmount": "0.000009",
          "amount": "0.0009",
          "operateTime": 1615985535000,
          "transferredAmount": "0.000441",
          "fromAsset": "USDT"
        },
        {
          "transId": 4359321,
          "serviceChargeAmount": "0.00001799",
          "amount": "0.0009",
          "operateTime": "2018-05-03 17:07:04",
          "transferredAmount": "0.00088156",
          "fromAsset": "ETH"
        }
      ]
    },
    {
      "operateTime":1616203180000,
      "totalTransferredAmount": "0.00058795",
      "totalServiceChargeAmount": "0.000012",
      "transId": 4357015,
      "userAssetDribbletDetails": [
        {
          "transId": 4357015,
          "serviceChargeAmount": "0.00001"
          "amount": "0.001",
          "operateTime": 1616203180000,
          "transferredAmount": "0.00049",
          "fromAsset": "USDT"
        },
        {
          "transId": 4357015,
          "serviceChargeAmount": "0.000002"
          "amount": "0.0001",
          "operateTime": 1616203180000,
          "transferredAmount": "0.00009795",
```

(continues on next page)

(continued from previous page)

```

        "fromAsset": "ETH"
    }
]
}

```

get_exchange_info() → Dict[KT, VT]

Return rate limits and list of symbols

Returns list - List of product dictionaries

```

{
  "timezone": "UTC",
  "serverTime": 1508631584636,
  "rateLimits": [
    {
      "rateLimitType": "REQUESTS",
      "interval": "MINUTE",
      "limit": 1200
    },
    {
      "rateLimitType": "ORDERS",
      "interval": "SECOND",
      "limit": 10
    },
    {
      "rateLimitType": "ORDERS",
      "interval": "DAY",
      "limit": 100000
    }
  ],
  "exchangeFilters": [],
  "symbols": [
    {
      "symbol": "ETHBTC",
      "status": "TRADING",
      "baseAsset": "ETH",
      "baseAssetPrecision": 8,
      "quoteAsset": "BTC",
      "quotePrecision": 8,
      "orderTypes": ["LIMIT", "MARKET"],
      "icebergAllowed": false,
      "filters": [
        {
          "filterType": "PRICE_FILTER",
          "minPrice": "0.00000100",
          "maxPrice": "100000.00000000",
          "tickSize": "0.00000100"
        }, {
          "filterType": "LOT_SIZE",
          "minQty": "0.00100000",
          "maxQty": "100000.00000000",
          "stepSize": "0.00100000"
        }, {
          "filterType": "MIN_NOTIONAL",
          "minNotional": "0.00100000"
        }
      ]
    }
  ]
}

```

(continues on next page)

(continued from previous page)

```

    }
  ]
}

```

Raises `BinanceRequestException`, `BinanceAPIException`

get_fiat_deposit_withdraw_history (**params)

get_fiat_payments_history (**params)

get_fixed_activity_project_list (**params)

get_historical_klines (symbol, interval, start_str, end_str=None, limit=500, klines_type: `binance.enums.HistoricalKlinesType = <HistoricalKlinesType.SPOT: 1>`)

Get Historical Klines from Binance

Parameters

- **symbol** (*str*) – Name of symbol pair e.g BNBBTC
- **interval** (*str*) – Binance Kline interval
- **start_str** (*str/int*) – Start date string in UTC format or timestamp in milliseconds
- **end_str** (*str/int*) – optional - end date string in UTC format or timestamp in milliseconds (default will fetch everything up to now)
- **limit** (*int*) – Default 500; max 1000.
- **klines_type** (`HistoricalKlinesType`) – Historical klines type: SPOT or FUTURES

Returns list of OHLCV values

get_historical_klines_generator (symbol, interval, start_str, end_str=None, klines_type: `binance.enums.HistoricalKlinesType = <HistoricalKlinesType.SPOT: 1>`)

Get Historical Klines generator from Binance

Parameters

- **symbol** (*str*) – Name of symbol pair e.g BNBBTC
- **interval** (*str*) – Binance Kline interval
- **start_str** (*str/int*) – Start date string in UTC format or timestamp in milliseconds
- **end_str** (*str/int*) – optional - end date string in UTC format or timestamp in milliseconds (default will fetch everything up to now)
- **klines_type** (`HistoricalKlinesType`) – Historical klines type: SPOT or FUTURES

Returns generator of OHLCV values

get_historical_trades (**params) → Dict[KT, VT]

Get older trades.

<https://binance-docs.github.io/apidocs/spot/en/#old-trade-lookup>

Parameters

- **symbol** (*str*) – required
- **limit** (*int*) – Default 500; max 1000.
- **fromId** (*str*) – TradeId to fetch from. Default gets most recent trades.

Returns API response

```
[
  {
    "id": 28457,
    "price": "4.00000100",
    "qty": "12.00000000",
    "time": 1499865549590,
    "isBuyerMaker": true,
    "isBestMatch": true
  }
]
```

Raises BinanceRequestException, BinanceAPIException

get_isolated_margin_account (***params*)

get_isolated_margin_symbol (***params*)

get_klines (***params*) → Dict[KT, VT]

Kline/candlestick bars for a symbol. Klines are uniquely identified by their open time.

<https://binance-docs.github.io/apidocs/spot/en/#kline-candlestick-data>

Parameters

- **symbol** (*str*) – required
- **interval** (*str*) –
-
- **limit** (*int*) –
- Default 500; max 1000.
- **startTime** (*int*) –
- **endTime** (*int*) –

Returns API response

```
[
  [
    1499040000000,      # Open time
    "0.01634790",      # Open
    "0.80000000",      # High
    "0.01575800",      # Low
    "0.01577100",      # Close
    "148976.11427815", # Volume
    1499644799999,     # Close time
    "2434.19055334",   # Quote asset volume
    308,               # Number of trades
    "1756.87402397",   # Taker buy base asset volume
    "28.46694368",     # Taker buy quote asset volume
    "17928899.62484339" # Can be ignored
  ]
]
```

(continues on next page)

(continued from previous page)

```
]
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

```
get_lending_account (**params)
get_lending_daily_quota_left (**params)
get_lending_daily_redemption_quota (**params)
get_lending_interest_history (**params)
get_lending_position (**params)
get_lending_product_list (**params)
get_lending_purchase_history (**params)
get_lending_redemption_history (**params)
get_margin_account (**params)
```

Query cross-margin account details

https://binance-docs.github.io/apidocs/spot/en/#query-cross-margin-account-details-user_data

Returns API response

```
{
  "borrowEnabled": true,
  "marginLevel": "11.64405625",
  "totalAssetOfBtc": "6.82728457",
  "totalLiabilityOfBtc": "0.58633215",
  "totalNetAssetOfBtc": "6.24095242",
  "tradeEnabled": true,
  "transferEnabled": true,
  "userAssets": [
    {
      "asset": "BTC",
      "borrowed": "0.00000000",
      "free": "0.00499500",
      "interest": "0.00000000",
      "locked": "0.00000000",
      "netAsset": "0.00499500"
    },
    {
      "asset": "BNB",
      "borrowed": "201.66666672",
      "free": "2346.50000000",
      "interest": "0.00000000",
      "locked": "0.00000000",
      "netAsset": "2144.83333328"
    },
    {
      "asset": "ETH",
      "borrowed": "0.00000000",
      "free": "0.00000000",
      "interest": "0.00000000",
      "locked": "0.00000000",
```

(continues on next page)

(continued from previous page)

```
        "netAsset": "0.00000000"
    },
    {
        "asset": "USDT",
        "borrowed": "0.00000000",
        "free": "0.00000000",
        "interest": "0.00000000",
        "locked": "0.00000000",
        "netAsset": "0.00000000"
    }
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

`get_margin_all_assets (**params)`

`get_margin_all_pairs (**params)`

`get_margin_asset (**params)`

`get_margin_force_liquidation_rec (**params)`

`get_margin_interest_history (**params)`

`get_margin_loan_details (**params)`

`get_margin_oco_order (**params)`

`get_margin_order (**params)`

`get_margin_price_index (**params)`

`get_margin_repay_details (**params)`

`get_margin_symbol (**params)`

`get_margin_trades (**params)`

`get_max_margin_loan (**params)`

`get_max_margin_transfer (**params)`

`get_my_trades (**params)`

Get trades for a specific symbol.

https://binance-docs.github.io/apidocs/spot/en/#account-trade-list-user_data

Parameters

- **symbol** (*str*) – required
- **startTime** (*int*) – optional
- **endTime** (*int*) – optional
- **limit** (*int*) – Default 500; max 1000.
- **fromId** (*int*) – TradeId to fetch from. Default gets most recent trades.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response


```
[
  {
    "id": 28457,
    "price": "4.00000100",
    "qty": "12.00000000",
    "commission": "10.10000000",
    "commissionAsset": "BNB",
    "time": 1499865549590,
    "isBuyer": true,
    "isMaker": false,
    "isBestMatch": true
  }
]
```

Raises BinanceRequestException, BinanceAPIException

get_open_margin_oco_orders (**params)

get_open_margin_orders (**params)

get_open_orders (**params)

Get all open orders on a symbol.

https://binance-docs.github.io/apidocs/spot/en/#current-open-orders-user_data

Parameters

- **symbol** (*str*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
[
  {
    "symbol": "LTCBTC",
    "orderId": 1,
    "clientOrderId": "myOrder1",
    "price": "0.1",
    "origQty": "1.0",
    "executedQty": "0.0",
    "status": "NEW",
    "timeInForce": "GTC",
    "type": "LIMIT",
    "side": "BUY",
    "stopPrice": "0.0",
    "icebergQty": "0.0",
    "time": 1499827319559
  }
]
```

Raises BinanceRequestException, BinanceAPIException

get_order (**params)

Check an order's status. Either orderId or origClientId must be sent.

https://binance-docs.github.io/apidocs/spot/en/#query-order-user_data

Parameters

- **symbol** (*str*) – required
- **orderId** (*int*) – The unique order id
- **origClientId** (*str*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "symbol": "LTCBTC",
  "orderId": 1,
  "clientOrderId": "myOrder1",
  "price": "0.1",
  "origQty": "1.0",
  "executedQty": "0.0",
  "status": "NEW",
  "timeInForce": "GTC",
  "type": "LIMIT",
  "side": "BUY",
  "stopPrice": "0.0",
  "icebergQty": "0.0",
  "time": 1499827319559
}
```

Raises BinanceRequestException, BinanceAPIException

get_order_book (***params*) → Dict[KT, VT]

Get the Order Book for the market

<https://binance-docs.github.io/apidocs/spot/en/#order-book>

Parameters

- **symbol** (*str*) – required
- **limit** (*int*) – Default 100; max 1000

Returns API response

```
{
  "lastUpdateId": 1027024,
  "bids": [
    [
      "4.00000000", # PRICE
      "431.00000000", # QTY
      [] # Can be ignored
    ]
  ],
  "asks": [
    [
      "4.00000200",
      "12.00000000",
      []
    ]
  ]
}
```

Raises BinanceRequestException, BinanceAPIException

get_orderbook_ticker (**params)

Latest price for a symbol or symbols.

<https://binance-docs.github.io/apidocs/spot/en/#symbol-order-book-ticker>

Parameters **symbol** (*str*) –

Returns API response

```
{
  "symbol": "LTCBTC",
  "bidPrice": "4.00000000",
  "bidQty": "431.00000000",
  "askPrice": "4.00002000",
  "askQty": "9.00000000"
}
```

OR

```
[
  {
    "symbol": "LTCBTC",
    "bidPrice": "4.00000000",
    "bidQty": "431.00000000",
    "askPrice": "4.00002000",
    "askQty": "9.00000000"
  },
  {
    "symbol": "ETHBTC",
    "bidPrice": "0.07946700",
    "bidQty": "9.00000000",
    "askPrice": "100000.00000000",
    "askQty": "1000.00000000"
  }
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_orderbook_tickers () → Dict[KT, VT]

Best price/qty on the order book for all symbols.

<https://binance-docs.github.io/apidocs/spot/en/#symbol-order-book-ticker>

Parameters **symbol** (*str*) – optional

Returns List of order book market entries

```
[
  {
    "symbol": "LTCBTC",
    "bidPrice": "4.00000000",
    "bidQty": "431.00000000",
    "askPrice": "4.00002000",
    "askQty": "9.00000000"
  },
  {
    "symbol": "ETHBTC",
    "bidPrice": "0.07946700",
    "bidQty": "9.00000000",
    "askPrice": "100000.00000000",
    "askQty": "1000.00000000"
  }
]
```

(continues on next page)

(continued from previous page)

```

        "askPrice": "100000.00000000",
        "askQty": "1000.00000000"
    }
]

```

Raises BinanceRequestException, BinanceAPIException

get_products () → Dict[KT, VT]

Return list of products currently listed on Binance

Use `get_exchange_info()` call instead

Returns list - List of product dictionaries

Raises BinanceRequestException, BinanceAPIException

get_recent_trades (**params) → Dict[KT, VT]

Get recent trades (up to last 500).

<https://binance-docs.github.io/apidocs/spot/en/#recent-trades-list>

Parameters

- **symbol** (*str*) – required
- **limit** (*int*) – Default 500; max 1000.

Returns API response

```

[
  {
    "id": 28457,
    "price": "4.00000100",
    "qty": "12.00000000",
    "time": 1499865549590,
    "isBuyerMaker": true,
    "isBestMatch": true
  }
]

```

Raises BinanceRequestException, BinanceAPIException

get_server_time () → Dict[KT, VT]

Test connectivity to the Rest API and get the current server time.

<https://binance-docs.github.io/apidocs/spot/en/#check-server-time>

Returns Current server time

```

{
  "serverTime": 1499827319559
}

```

Raises BinanceRequestException, BinanceAPIException

get_sub_account_assets (**params)

get_sub_account_futures_transfer_history (**params)

get_sub_account_list (**params)
get_sub_account_transfer_history (**params)
get_subaccount_deposit_address (**params)
get_subaccount_deposit_history (**params)
get_subaccount_futures_details (**params)
get_subaccount_futures_margin_status (**params)
get_subaccount_futures_positionrisk (**params)
get_subaccount_futures_summary (**params)
get_subaccount_margin_details (**params)
get_subaccount_margin_summary (**params)
get_subaccount_transfer_history (**params)
get_symbol_info (symbol) → Optional[Dict[KT, VT]]
 Return information about a symbol

Parameters **symbol** (str) – required e.g BNBBTC

Returns Dict if found, None if not

```

{
  "symbol": "ETHBTC",
  "status": "TRADING",
  "baseAsset": "ETH",
  "baseAssetPrecision": 8,
  "quoteAsset": "BTC",
  "quotePrecision": 8,
  "orderTypes": ["LIMIT", "MARKET"],
  "icebergAllowed": false,
  "filters": [
    {
      "filterType": "PRICE_FILTER",
      "minPrice": "0.00000100",
      "maxPrice": "100000.00000000",
      "tickSize": "0.00000100"
    }, {
      "filterType": "LOT_SIZE",
      "minQty": "0.00100000",
      "maxQty": "100000.00000000",
      "stepSize": "0.00100000"
    }, {
      "filterType": "MIN_NOTIONAL",
      "minNotional": "0.00100000"
    }
  ]
}

```

Raises BinanceRequestException, BinanceAPIException

get_symbol_ticker (**params)
 Latest price for a symbol or symbols.

<https://binance-docs.github.io/apidocs/spot/en/#symbol-price-ticker>

Parameters `symbol` (*str*) –

Returns API response

```
{
  "symbol": "LTCBTC",
  "price": "4.00000200"
}
```

OR

```
[
  {
    "symbol": "LTCBTC",
    "price": "4.00000200"
  },
  {
    "symbol": "ETHBTC",
    "price": "0.07946600"
  }
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_system_status ()

Get system status detail.

<https://binance-docs.github.io/apidocs/spot/en/#system-status-sapi-system>

Returns API response

```
{
  "status": 0,           # 0: normal system maintenance
  "msg": "normal"       # normal or System maintenance.
}
```

Raises `BinanceAPIException`

get_ticker (***params*)

24 hour price change statistics.

<https://binance-docs.github.io/apidocs/spot/en/#24hr-ticker-price-change-statistics>

Parameters `symbol` (*str*) –

Returns API response

```
{
  "priceChange": "-94.99999800",
  "priceChangePercent": "-95.960",
  "weightedAvgPrice": "0.29628482",
  "prevClosePrice": "0.10002000",
  "lastPrice": "4.00000200",
  "bidPrice": "4.00000000",
  "askPrice": "4.00000200",
  "openPrice": "99.00000000",
  "highPrice": "100.00000000",
  "lowPrice": "0.10000000",
}
```

(continues on next page)

(continued from previous page)

```

"volume": "8913.30000000",
"openTime": 1499783499040,
"closeTime": 1499869899040,
"fristId": 28385, # First tradeId
"lastId": 28460, # Last tradeId
"count": 76 # Trade count
}

```

OR

```

[
  {
    "priceChange": "-94.99999800",
    "priceChangePercent": "-95.960",
    "weightedAvgPrice": "0.29628482",
    "prevClosePrice": "0.10002000",
    "lastPrice": "4.00000200",
    "bidPrice": "4.00000000",
    "askPrice": "4.00000200",
    "openPrice": "99.00000000",
    "highPrice": "100.00000000",
    "lowPrice": "0.10000000",
    "volume": "8913.30000000",
    "openTime": 1499783499040,
    "closeTime": 1499869899040,
    "fristId": 28385, # First tradeId
    "lastId": 28460, # Last tradeId
    "count": 76 # Trade count
  }
]

```

Raises BinanceRequestException, BinanceAPIException**get_trade_fee** (**params)

Get trade fee.

https://binance-docs.github.io/apidocs/spot/en/#trade-fee-sapi-user_data**Parameters**

- **symbol** (*str*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```

[
  {
    "symbol": "ADAETH",
    "makerCommission": "0.001",
    "takerCommission": "0.001"
  },
  {
    "symbol": "BNBBTC",
    "makerCommission": "0.001",
    "takerCommission": "0.001"
  }
]

```

`get_universal_transfer_history(**params)`

`get_withdraw_history(**params)`

Fetch withdraw history.

https://binance-docs.github.io/apidocs/spot/en/#withdraw-history-supporting-network-user_data

Parameters

- `coin` (*str*) – optional
- `offset` (*int*) – optional - default:0
- `limit` (*int*) – optional
- `startTime` (*int*) – optional - Default: 90 days from current timestamp
- `endTime` (*int*) – optional - Default: present timestamp
- `recvWindow` (*int*) – the number of milliseconds the request is valid for

Returns API response

```
[
  {
    "address": "0x94df8b352de7f46f64b01d3666bf6e936e44ce60",
    "amount": "8.91000000",
    "applyTime": "2019-10-12 11:12:02",
    "coin": "USDT",
    "id": "b6ae22b3aa844210a7041aee7589627c",
    "withdrawOrderId": "WITHDRAWtest123", // will not be returned if there
↪ 's no withdrawOrderId for this withdraw.
    "network": "ETH",
    "transferType": 0, // 1 for internal transfer, 0 for external_
↪ transfer
    "status": 6,
    "txId":
↪ "0xb5ef8c13b968a406cc62a93a8bd80f9e9a906ef1b3fcf20a2e48573c17659268"
  },
  {
    "address": "1FzdVHtiBqMrWdjPyRPULCUceZPJ2WLCsB",
    "amount": "0.00150000",
    "applyTime": "2019-09-24 12:43:45",
    "coin": "BTC",
    "id": "156ec387f49b41df8724fa744fa82719",
    "network": "BTC",
    "status": 6,
    "txId":
↪ "60fd9007ebfddc753455f95fafa808c4302c836e4d1eebc5a132c36c1d8ac354"
  }
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

`get_withdraw_history_id(withdraw_id, **params)`

Fetch withdraw history.

https://binance-docs.github.io/apidocs/spot/en/#withdraw-history-supporting-network-user_data

Parameters

- `withdraw_id` (*str*) – required

- **asset** (*str*) – optional
- **startTime** (*long*) – optional
- **endTime** (*long*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "id": "7213fea8e94b4a5593d507237e5a555b",
  "withdrawOrderId": None,
  "amount": 0.99,
  "transactionFee": 0.01,
  "address": "0x6915f16f8791d0a1cc2bf47c13a6b2a92000504b",
  "asset": "ETH",
  "txId":
  ↪ "0xdf33b22bdb2b28b1f75ccd201a4a4m6e7g83jy5fc5d5a9d1340961598cfcb0a1",
  "applyTime": 1508198532000,
  "status": 4
}
```

Raises BinanceRequestException, BinanceAPIException

isolated_margin_stream_close (*symbol*, *listenKey*)

isolated_margin_stream_get_listen_key (*symbol*)

isolated_margin_stream_keepalive (*symbol*, *listenKey*)

make_subaccount_futures_transfer (***params*)

make_subaccount_margin_transfer (***params*)

make_subaccount_to_master_transfer (***params*)

make_subaccount_to_subaccount_transfer (***params*)

make_subaccount_universal_transfer (***params*)

make_universal_transfer (***params*)

User Universal Transfer

<https://binance-docs.github.io/apidocs/spot/en/#user-universal-transfer>

Parameters

- **type** (*str* (*ENUM*)) – required
- **asset** (*str*) – required
- **amount** (*str*) – required
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

```
transfer_status = client.make_universal_transfer(params)
```

Returns API response

```
{
  "tranId": 13526853623
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

`margin_stream_close` (*listenKey*)
`margin_stream_get_listen_key` ()
`margin_stream_keepalive` (*listenKey*)
`new_transfer_history` (***params*)
`options_account_info` (***params*)
`options_bill` (***params*)
`options_cancel_all_orders` (***params*)
`options_cancel_batch_order` (***params*)
`options_cancel_order` (***params*)
`options_exchange_info` ()
`options_funds_transfer` (***params*)
`options_historical_trades` (***params*)
`options_index_price` (***params*)
`options_info` ()
`options_klines` (***params*)
`options_mark_price` (***params*)
`options_order_book` (***params*)
`options_ping` ()
`options_place_batch_order` (***params*)
`options_place_order` (***params*)
`options_positions` (***params*)
`options_price` (***params*)
`options_query_order` (***params*)
`options_query_order_history` (***params*)
`options_query_pending_orders` (***params*)
`options_recent_trades` (***params*)
`options_time` ()
`options_user_trades` (***params*)
`order_limit` (*timeInForce*=`'GTC'`, ***params*)

Send in a new limit order

Any order with an `icebergQty` MUST have `timeInForce` set to `GTC`.

Parameters

- **symbol** (*str*) – required
- **side** (*str*) – required
- **quantity** (*decimal*) – required

- **price** (*str*) – required
- **timeInForce** (*str*) – default Good till cancelled
- **newClientId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **icebergQty** (*decimal*) – Used with LIMIT, STOP_LOSS_LIMIT, and TAKE_PROFIT_LIMIT to create an iceberg order.
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See order endpoint for full response options

Raises BinanceRequestException, BinanceAPIException, BinanceOrderException, BinanceOrderMinAmountException, BinanceOrderMinPriceException, BinanceOrderMinTotalException, BinanceOrderUnknownSymbolException, BinanceOrderInactiveSymbolException

order_limit_buy (*timeInForce='GTC', **params*)

Send in a new limit buy order

Any order with an icebergQty MUST have timeInForce set to GTC.

Parameters

- **symbol** (*str*) – required
- **quantity** (*decimal*) – required
- **price** (*str*) – required
- **timeInForce** (*str*) – default Good till cancelled
- **newClientId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **stopPrice** (*decimal*) – Used with stop orders
- **icebergQty** (*decimal*) – Used with iceberg orders
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See order endpoint for full response options

Raises BinanceRequestException, BinanceAPIException, BinanceOrderException, BinanceOrderMinAmountException, BinanceOrderMinPriceException, BinanceOrderMinTotalException, BinanceOrderUnknownSymbolException, BinanceOrderInactiveSymbolException

order_limit_sell (*timeInForce='GTC', **params*)

Send in a new limit sell order

Parameters

- **symbol** (*str*) – required
- **quantity** (*decimal*) – required
- **price** (*str*) – required

- **timeInForce** (*str*) – default Good till cancelled
- **newClientId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **stopPrice** (*decimal*) – Used with stop orders
- **icebergQty** (*decimal*) – Used with iceberg orders
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See order endpoint for full response options

Raises BinanceRequestException, BinanceAPIException, BinanceOrderException, BinanceOrderMinAmountException, BinanceOrderMinPriceException, BinanceOrderMinTotalException, BinanceOrderUnknownSymbolException, BinanceOrderInactiveSymbolException

order_market (***params*)

Send in a new market order

Parameters

- **symbol** (*str*) – required
- **side** (*str*) – required
- **quantity** (*decimal*) – required
- **quoteOrderQty** (*decimal*) – amount the user wants to spend (when buying) or receive (when selling) of the quote asset
- **newClientId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See order endpoint for full response options

Raises BinanceRequestException, BinanceAPIException, BinanceOrderException, BinanceOrderMinAmountException, BinanceOrderMinPriceException, BinanceOrderMinTotalException, BinanceOrderUnknownSymbolException, BinanceOrderInactiveSymbolException

order_market_buy (***params*)

Send in a new market buy order

Parameters

- **symbol** (*str*) – required
- **quantity** (*decimal*) – required
- **quoteOrderQty** (*decimal*) – the amount the user wants to spend of the quote asset
- **newClientId** (*str*) – A unique id for the order. Automatically generated if not sent.

- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See order endpoint for full response options

Raises BinanceRequestException, BinanceAPIException, BinanceOrderException, BinanceOrderMinAmountException, BinanceOrderMinPriceException, BinanceOrderMinTotalException, BinanceOrderUnknownSymbolException, BinanceOrderInactiveSymbolException

order_market_sell (***params*)

Send in a new market sell order

Parameters

- **symbol** (*str*) – required
- **quantity** (*decimal*) – required
- **quoteOrderQty** (*decimal*) – the amount the user wants to receive of the quote asset
- **newClientOrderId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See order endpoint for full response options

Raises BinanceRequestException, BinanceAPIException, BinanceOrderException, BinanceOrderMinAmountException, BinanceOrderMinPriceException, BinanceOrderMinTotalException, BinanceOrderUnknownSymbolException, BinanceOrderInactiveSymbolException

order_oco_buy (***params*)

Send in a new OCO buy order

Parameters

- **symbol** (*str*) – required
- **listClientOrderId** (*str*) – A unique id for the list order. Automatically generated if not sent.
- **quantity** (*decimal*) – required
- **limitClientOrderId** (*str*) – A unique id for the limit order. Automatically generated if not sent.
- **price** (*str*) – required
- **limitIcebergQty** (*decimal*) – Used to make the LIMIT_MAKER leg an iceberg order.
- **stopClientOrderId** (*str*) – A unique id for the stop order. Automatically generated if not sent.
- **stopPrice** (*str*) – required
- **stopLimitPrice** (*str*) – If provided, stopLimitTimeInForce is required.

- **stopIcebergQty** (*decimal*) – Used with STOP_LOSS_LIMIT leg to make an iceberg order.
- **stopLimitTimeInForce** (*str*) – Valid values are GTC/FOK/IOC.
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See OCO order endpoint for full response options

Raises BinanceRequestException, BinanceAPIException, BinanceOrderException, BinanceOrderMinAmountException, BinanceOrderMinPriceException, BinanceOrderMinTotalException, BinanceOrderUnknownSymbolException, BinanceOrderInactiveSymbolException

order_oco_sell (***params*)

Send in a new OCO sell order

Parameters

- **symbol** (*str*) – required
- **listClientOrderId** (*str*) – A unique id for the list order. Automatically generated if not sent.
- **quantity** (*decimal*) – required
- **limitClientOrderId** (*str*) – A unique id for the limit order. Automatically generated if not sent.
- **price** (*str*) – required
- **limitIcebergQty** (*decimal*) – Used to make the LIMIT_MAKER leg an iceberg order.
- **stopClientOrderId** (*str*) – A unique id for the stop order. Automatically generated if not sent.
- **stopPrice** (*str*) – required
- **stopLimitPrice** (*str*) – If provided, stopLimitTimeInForce is required.
- **stopIcebergQty** (*decimal*) – Used with STOP_LOSS_LIMIT leg to make an iceberg order.
- **stopLimitTimeInForce** (*str*) – Valid values are GTC/FOK/IOC.
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See OCO order endpoint for full response options

Raises BinanceRequestException, BinanceAPIException, BinanceOrderException, BinanceOrderMinAmountException, BinanceOrderMinPriceException, BinanceOrderMinTotalException, BinanceOrderUnknownSymbolException, BinanceOrderInactiveSymbolException

ping () → Dict[KT, VT]

Test connectivity to the Rest API.

<https://binance-docs.github.io/apidocs/spot/en/#test-connectivity>

Returns Empty array

```
{ }
```

Raises BinanceRequestException, BinanceAPIException

purchase_lending_product (**params)

query_subaccount_spot_summary (**params)

query_universal_transfer_history (**params)

Query User Universal Transfer History

<https://binance-docs.github.io/apidocs/spot/en/#query-user-universal-transfer-history>

Parameters

- **type** (*str* (ENUM)) – required
- **startTime** (*int*) – optional
- **endTime** (*int*) – optional
- **current** (*int*) – optional - Default 1
- **size** (*int*) – required - Default 10, Max 100
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

```
transfer_status = client.query_universal_transfer_history(params)
```

Returns API response

```
{
  "total":2,
  "rows":[
    {
      "asset":"USDT",
      "amount":"1",
      "type":"MAIN_UMFUTURE",
      "status": "CONFIRMED",
      "tranId": 11415955596,
      "timestamp":1544433328000
    },
    {
      "asset":"USDT",
      "amount":"2",
      "type":"MAIN_UMFUTURE",
      "status": "CONFIRMED",
      "tranId": 11366865406,
      "timestamp":1544433328000
    }
  ]
}
```

Raises BinanceRequestException, BinanceAPIException

redeem_lending_product (**params)

repay_margin_loan (**params)

stream_close (*listenKey*)

Close out a user data stream.

<https://binance-docs.github.io/apidocs/spot/en/#listen-key-spot>

Parameters *listenKey* (*str*) – required

Returns API response

```
{ }
```

Raises `BinanceRequestException`, `BinanceAPIException`

stream_get_listen_key ()

Start a new user data stream and return the listen key. If a stream already exists it should return the same key. If the stream becomes invalid a new key is returned.

Can be used to keep the user stream alive.

<https://binance-docs.github.io/apidocs/spot/en/#listen-key-spot>

Returns API response

```
{  
  "listenKey":  
  ↪ "pqia91ma19a5s61cv6a81va65sdf19v8a65a1a5s61cv6a81va65sdf19v8a65a1"  
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

stream_keepalive (*listenKey*)

PING a user data stream to prevent a time out.

<https://binance-docs.github.io/apidocs/spot/en/#listen-key-spot>

Parameters *listenKey* (*str*) – required

Returns API response

```
{ }
```

Raises `BinanceRequestException`, `BinanceAPIException`

toggle_bnb_burn_spot_margin (***params*)**transfer_dust** (***params*)

Convert dust assets to BNB.

https://binance-docs.github.io/apidocs/spot/en/#dust-transfer-user_data

Parameters

- **asset** (*str*) – The asset being converted. e.g: 'ONE'
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

```
result = client.transfer_dust(asset='ONE')
```

Returns API response


```
{
  "totalServiceCharge": "0.02102542",
  "totalTransferred": "1.05127099",
  "transferResult": [
    {
      "amount": "0.03000000",
      "fromAsset": "ETH",
      "operateTime": 1563368549307,
      "serviceChargeAmount": "0.00500000",
      "tranId": 2970932918,
      "transferredAmount": "0.25000000"
    }
  ]
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

transfer_history (***params*)

transfer_isolated_margin_to_spot (***params*)

transfer_margin_to_spot (***params*)

transfer_spot_to_isolated_margin (***params*)

transfer_spot_to_margin (***params*)

universal_transfer (***params*)

withdraw (***params*)

Submit a withdraw request.

<https://binance-docs.github.io/apidocs/spot/en/#withdraw-sapi>

Assumptions:

- You must have Withdraw permissions enabled on your API key
- You must have withdrawn to the address specified through the website and approved the transaction via email

Parameters

- **coin** (*str*) – required
- **withdrawOrderId** (*str*) – optional - client id for withdraw
- **network** (*str*) – optional
- **address** (*str*) – optional
- **amount** (*decimal*) – required
- **transactionFeeFlag** (*bool*) – required - When making internal transfer, true for returning the fee to the destination account; false for returning the fee back to the departure account. Default false.
- **name** (*str*) – optional - Description of the address, default asset value passed will be used
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "id": "7213fea8e94b4a5593d507237e5a555b"
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

```
class binance.client.BaseClient (api_key: Optional[str] = None, api_secret: Optional[str] =
    None, requests_params: Dict[str, str] = None, tld: str = 'com',
    testnet: bool = False)
```

Bases: `object`

`AGG_BEST_MATCH = 'M'`

`AGG_BUYER_MAKES = 'm'`

`AGG_FIRST_TRADE_ID = 'f'`

`AGG_ID = 'a'`

`AGG_LAST_TRADE_ID = 'l'`

`AGG_PRICE = 'p'`

`AGG_QUANTITY = 'q'`

`AGG_TIME = 'T'`

`API_TESTNET_URL = 'https://testnet.binance.vision/api'`

`API_URL = 'https://api.binance.{}/api'`

`COIN_FUTURE_TO_SPOT = 'CMFUTURE_MAIN'`

`FIAT_TO_MINING = 'C2C_MINING'`

`FIAT_TO_SPOT = 'C2C_MAIN'`

`FIAT_TO_USDT_FUTURE = 'C2C_UMFUTURE'`

`FUTURES_API_VERSION = 'v1'`

`FUTURES_API_VERSION2 = 'v2'`

`FUTURES_COIN_DATA_TESTNET_URL = 'https://testnet.binancefuture.com/futures/data'`

`FUTURES_COIN_DATA_URL = 'https://dapi.binance.{}/futures/data'`

`FUTURES_COIN_TESTNET_URL = 'https://testnet.binancefuture.com/dapi'`

`FUTURES_COIN_URL = 'https://dapi.binance.{}/dapi'`

`FUTURES_DATA_TESTNET_URL = 'https://testnet.binancefuture.com/futures/data'`

`FUTURES_DATA_URL = 'https://fapi.binance.{}/futures/data'`

`FUTURES_TESTNET_URL = 'https://testnet.binancefuture.com/fapi'`

`FUTURES_URL = 'https://fapi.binance.{}/fapi'`

`FUTURE_ORDER_TYPE_LIMIT = 'LIMIT'`

`FUTURE_ORDER_TYPE_LIMIT_MAKER = 'LIMIT_MAKER'`

`FUTURE_ORDER_TYPE_MARKET = 'MARKET'`

`FUTURE_ORDER_TYPE_STOP = 'STOP'`

`FUTURE_ORDER_TYPE_STOP_MARKET = 'STOP_MARKET'`

```
FUTURE_ORDER_TYPE_TAKE_PROFIT = 'TAKE_PROFIT'  
FUTURE_ORDER_TYPE_TAKE_PROFIT_MARKET = 'TAKE_PROFIT_MARKET'  
KLINE_INTERVAL_12HOUR = '12h'  
KLINE_INTERVAL_15MINUTE = '15m'  
KLINE_INTERVAL_1DAY = '1d'  
KLINE_INTERVAL_1HOUR = '1h'  
KLINE_INTERVAL_1MINUTE = '1m'  
KLINE_INTERVAL_1MONTH = '1M'  
KLINE_INTERVAL_1WEEK = '1w'  
KLINE_INTERVAL_2HOUR = '2h'  
KLINE_INTERVAL_30MINUTE = '30m'  
KLINE_INTERVAL_3DAY = '3d'  
KLINE_INTERVAL_3MINUTE = '3m'  
KLINE_INTERVAL_4HOUR = '4h'  
KLINE_INTERVAL_5MINUTE = '5m'  
KLINE_INTERVAL_6HOUR = '6h'  
KLINE_INTERVAL_8HOUR = '8h'  
MARGIN_API_URL = 'https://api.binance.{}/sapi'  
MARGIN_API_VERSION = 'v1'  
MARGIN_CROSS_TO_SPOT = 'MARGIN_MAIN'  
MARGIN_CROSS_TO_USDT_FUTURE = 'MARGIN_UMFUTURE'  
MINING_TO_FIAT = 'MINING_C2C'  
MINING_TO_SPOT = 'MINING_MAIN'  
MINING_TO_USDT_FUTURE = 'MINING_UMFUTURE'  
OPTIONS_API_VERSION = 'v1'  
OPTIONS_TESTNET_URL = 'https://testnet.binanceops.{}/vapi'  
OPTIONS_URL = 'https://vapi.binance.{}/vapi'  
ORDER_RESP_TYPE_ACK = 'ACK'  
ORDER_RESP_TYPE_FULL = 'FULL'  
ORDER_RESP_TYPE_RESULT = 'RESULT'  
ORDER_STATUS_CANCELED = 'CANCELED'  
ORDER_STATUS_EXPIRED = 'EXPIRED'  
ORDER_STATUS_FILLED = 'FILLED'  
ORDER_STATUS_NEW = 'NEW'  
ORDER_STATUS_PARTIALLY_FILLED = 'PARTIALLY_FILLED'  
ORDER_STATUS_PENDING_CANCEL = 'PENDING_CANCEL'
```

```
ORDER_STATUS_REJECTED = 'REJECTED'  
ORDER_TYPE_LIMIT = 'LIMIT'  
ORDER_TYPE_LIMIT_MAKER = 'LIMIT_MAKER'  
ORDER_TYPE_MARKET = 'MARKET'  
ORDER_TYPE_STOP_LOSS = 'STOP_LOSS'  
ORDER_TYPE_STOP_LOSS_LIMIT = 'STOP_LOSS_LIMIT'  
ORDER_TYPE_TAKE_PROFIT = 'TAKE_PROFIT'  
ORDER_TYPE_TAKE_PROFIT_LIMIT = 'TAKE_PROFIT_LIMIT'  
PRIVATE_API_VERSION = 'v3'  
PUBLIC_API_VERSION = 'v1'  
REQUEST_TIMEOUT = 10  
SIDE_BUY = 'BUY'  
SIDE_SELL = 'SELL'  
SPOT_TO_COIN_FUTURE = 'MAIN_CMFUTURE'  
SPOT_TO_FIAT = 'MAIN_C2C'  
SPOT_TO_MARGIN_CROSS = 'MAIN_MARGIN'  
SPOT_TO_MINING = 'MAIN_MINING'  
SPOT_TO_USDT_FUTURE = 'MAIN_UMFUTURE'  
SYMBOL_TYPE_SPOT = 'SPOT'  
TIME_IN_FORCE_FOK = 'FOK'  
TIME_IN_FORCE_GTC = 'GTC'  
TIME_IN_FORCE_IOC = 'IOC'  
USDT_FUTURE_TO_FIAT = 'UMFUTURE_C2C'  
USDT_FUTURE_TO_MARGIN_CROSS = 'UMFUTURE_MARGIN'  
USDT_FUTURE_TO_SPOT = 'UMFUTURE_MAIN'  
WEBSITE_URL = 'https://www.binance.{'
```

```
__init__(api_key: Optional[str] = None, api_secret: Optional[str] = None, requests_params:  
         Dict[str, str] = None, tld: str = 'com', testnet: bool = False)  
Binance API Client constructor
```

Parameters

- **api_key** (*str.*) – Api Key
- **api_secret** (*str.*) – Api Secret
- **requests_params** (*dict.*) – optional - Dictionary of requests params to use for all calls
- **testnet** (*bool*) – Use testnet environment - only available for vanilla options at the moment

```
class binance.client.Client (api_key: Optional[str] = None, api_secret: Optional[str] = None,  
requests_params: Dict[str, str] = None, tld: str = 'com', testnet:  
bool = False)
```

Bases: `binance.client.BaseClient`

```
__init__ (api_key: Optional[str] = None, api_secret: Optional[str] = None, requests_params:  
Dict[str, str] = None, tld: str = 'com', testnet: bool = False)
```

Binance API Client constructor

Parameters

- **api_key** (*str.*) – Api Key
- **api_secret** (*str.*) – Api Secret
- **requests_params** (*dict.*) – optional - Dictionary of requests params to use for all calls
- **testnet** (*bool*) – Use testnet environment - only available for vanilla options at the moment

```
aggregate_trade_iter (symbol: str, start_str=None, last_id=None)
```

Iterate over aggregate trade data from (start_time or last_id) to the end of the history so far.

If start_time is specified, start with the first trade after start_time. Meant to initialise a local cache of trade data.

If last_id is specified, start with the trade after it. This is meant for updating a pre-existing local trade data cache.

Only allows start_str or last_id—not both. Not guaranteed to work right if you’re running more than one of these simultaneously. You will probably hit your rate limit.

See dateparser docs for valid start and end string formats <http://dateparser.readthedocs.io/en/latest/>

If using offset strings for dates add “UTC” to date string e.g. “now UTC”, “11 hours ago UTC”

Parameters

- **symbol** (*str*) – Symbol string e.g. ETHBTC
- **start_str** – Start date string in UTC format or timestamp in milliseconds. The iterator will

return the first trade occurring later than this time. :type start_str: strlint :param last_id: aggregate trade ID of the last known aggregate trade. Not a regular trade ID. See <https://binance-docs.github.io/apidocs/spot/en/#compressed-aggregate-trades-list>

Returns an iterator of JSON objects, one per trade. The format of each object is identical to `Client.aggregate_trades()`.

```
cancel_margin_oco_order (**params)
```

Cancel an entire Order List for a margin account.

<https://binance-docs.github.io/apidocs/spot/en/#margin-account-cancel-oco-trade>

Parameters

- **symbol** (*str*) – required
- **isIsolated** – for isolated margin or not, “TRUE”, “FALSE” default “FALSE”
- **orderId** (*int*) – Either orderId or listClientOrderId must be provided

- **listClientOrderId** (*str*) – Either orderListId or listClientOrderId must be provided
- **newClientOrderId** (*str*) – Used to uniquely identify this cancel. Automatically generated by default.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "orderListId": 0,
  "contingencyType": "OCO",
  "listStatusType": "ALL_DONE",
  "listOrderStatus": "ALL_DONE",
  "listClientOrderId": "C3wyj4WVEktd7u9aVBRXcN",
  "transactionTime": 1574040868128,
  "symbol": "LTCBTC",
  "isIsolated": false,          // if isolated margin
  "orders": [
    {
      "symbol": "LTCBTC",
      "orderId": 2,
      "clientOrderId": "pO9ufTiFGg3nw2fOdgeOXa"
    },
    {
      "symbol": "LTCBTC",
      "orderId": 3,
      "clientOrderId": "TXOvglzXuaubXAaENparCB"
    }
  ],
  "orderReports": [
    {
      "symbol": "LTCBTC",
      "origClientOrderId": "pO9ufTiFGg3nw2fOdgeOXa",
      "orderId": 2,
      "orderListId": 0,
      "clientOrderId": "unfWT8ig8i0uj6lPuYLez6",
      "price": "1.00000000",
      "origQty": "10.00000000",
      "executedQty": "0.00000000",
      "cumulativeQuoteQty": "0.00000000",
      "status": "CANCELED",
      "timeInForce": "GTC",
      "type": "STOP_LOSS_LIMIT",
      "side": "SELL",
      "stopPrice": "1.00000000"
    },
    {
      "symbol": "LTCBTC",
      "origClientOrderId": "TXOvglzXuaubXAaENparCB",
      "orderId": 3,
      "orderListId": 0,
      "clientOrderId": "unfWT8ig8i0uj6lPuYLez6",
      "price": "3.00000000",
      "origQty": "10.00000000",
      "executedQty": "0.00000000",
      "cumulativeQuoteQty": "0.00000000",
      "status": "CANCELED",

```

(continues on next page)

(continued from previous page)

```

        "timeInForce": "GTC",
        "type": "LIMIT_MAKER",
        "side": "SELL"
    }
]
}

```

cancel_margin_order (**params)

Cancel an active order for margin account.

Either orderId or origClientId must be sent.

<https://binance-docs.github.io/apidocs/spot/en/#margin-account-cancel-order-trade>

Parameters

- **symbol** (*str*) – required
- **isIsolated** (*str*) – set to ‘TRUE’ for isolated margin (default ‘FALSE’)
- **orderId** (*str*) –
- **origClientId** (*str*) –
- **newClientId** (*str*) – Used to uniquely identify this cancel. Automatically generated by default.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns

API response

```

{ "symbol": "LTCBTC", "orderId": 28, "origClientId": "myOrder1", "clientOrderId": "cancelMyOrder1", "transactTime": 1507725176595, "price": "1.00000000", "origQty": "10.00000000", "executedQty": "8.00000000", "cumulativeQuoteQty": "8.00000000", "status": "CANCELED", "timeInForce": "GTC", "type": "LIMIT", "side": "SELL"
}

```

Raises BinanceRequestException, BinanceAPIException

cancel_order (**params)

Cancel an active order. Either orderId or origClientId must be sent.

<https://binance-docs.github.io/apidocs/spot/en/#cancel-order-trade>

Parameters

- **symbol** (*str*) – required
- **orderId** (*int*) – The unique order id
- **origClientId** (*str*) – optional
- **newClientId** (*str*) – Used to uniquely identify this cancel. Automatically generated by default.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "symbol": "LTCBTC",
  "origClientOrderId": "myOrder1",
  "orderId": 1,
  "clientOrderId": "cancelMyOrder1"
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

change_fixed_activity_to_daily_position (**params)

Change Fixed/Activity Position to Daily Position

https://binance-docs.github.io/apidocs/spot/en/#change-fixed-activity-position-to-daily-position-user_data

close_connection ()

create_isolated_margin_account (**params)

Create isolated margin account for symbol

<https://binance-docs.github.io/apidocs/spot/en/#create-isolated-margin-account-margin>

Parameters

- **base** (*str*) – Base asset of symbol
- **quote** (*str*) – Quote asset of symbol

```
pair_details = client.create_isolated_margin_account(base='USDT', quote='BTC')
```

Returns API response

```
{
  "success": true,
  "symbol": "BTCUSDT"
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

create_margin_loan (**params)

Apply for a loan in cross-margin or isolated-margin account.

<https://binance-docs.github.io/apidocs/spot/en/#margin-account-borrow-margin>

Parameters

- **asset** (*str*) – name of the asset
- **amount** (*str*) – amount to transfer
- **isIsolated** (*str*) – set to 'TRUE' for isolated margin (default 'FALSE')
- **symbol** (*str*) – Isolated margin symbol (default blank for cross-margin)
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

```
transaction = client.margin_create_loan(asset='BTC', amount='1.1')
transaction = client.margin_create_loan(asset='BTC', amount='1.1',
                                       isIsolated='TRUE', symbol='ETHBTC')
```


Returns API response

```
{
  "tranId": 100000001
}
```

Raises BinanceRequestException, BinanceAPIException

create_margin_oco_order (**params)

Post a new OCO trade for margin account.

<https://binance-docs.github.io/apidocs/spot/en/#margin-account-new-oco-trade>

Parameters

- **symbol** (*str*) – required
- **isIsolated** – for isolated margin or not, “TRUE”, “FALSE” default “FALSE”
- **listClientId** (*str*) – A unique id for the list order. Automatically generated if not sent.
- **side** (*str*) – required
- **quantity** (*decimal*) – required
- **limitClientId** (*str*) – A unique id for the limit order. Automatically generated if not sent.
- **price** (*str*) – required
- **limitIcebergQty** (*decimal*) – Used to make the LIMIT_MAKER leg an iceberg order.
- **stopClientId** (*str*) – A unique Id for the stop loss/stop loss limit leg. Automatically generated if not sent.
- **stopPrice** (*str*) – required
- **stopLimitPrice** (*str*) – If provided, stopLimitTimeInForce is required.
- **stopIcebergQty** (*decimal*) – Used with STOP_LOSS_LIMIT leg to make an iceberg order.
- **stopLimitTimeInForce** (*str*) – Valid values are GTC/FOK/IOC.
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **sideEffectType** (*str*) – NO_SIDE_EFFECT, MARGIN_BUY, AUTO_REPAY; default NO_SIDE_EFFECT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "orderListId": 0,
  "contingencyType": "OCO",
  "listStatusType": "EXEC_STARTED",
  "listOrderStatus": "EXECUTING",
  "listClientId": "JYVpp3F0f5CAG15DhtrqLp",
  "transactionTime": 1563417480525,
```

(continues on next page)

(continued from previous page)

```

    "symbol": "LTCBTC",
    "marginBuyBorrowAmount": "5",           // will not return if no margin trade_
↪happens
    "marginBuyBorrowAsset": "BTC",         // will not return if no margin trade_
↪happens
    "isIsolated": false,                  // if isolated margin
    "orders": [
        {
            "symbol": "LTCBTC",
            "orderId": 2,
            "clientOrderId": "Kk7sqHb9J6mJWtMDVW7Vos"
        },
        {
            "symbol": "LTCBTC",
            "orderId": 3,
            "clientOrderId": "xTXKaGYd4bluPVp78IVRv1"
        }
    ],
    "orderReports": [
        {
            "symbol": "LTCBTC",
            "orderId": 2,
            "orderListId": 0,
            "clientOrderId": "Kk7sqHb9J6mJWtMDVW7Vos",
            "transactTime": 1563417480525,
            "price": "0.000000",
            "origQty": "0.624363",
            "executedQty": "0.000000",
            "cumulativeQuoteQty": "0.000000",
            "status": "NEW",
            "timeInForce": "GTC",
            "type": "STOP_LOSS",
            "side": "BUY",
            "stopPrice": "0.960664"
        },
        {
            "symbol": "LTCBTC",
            "orderId": 3,
            "orderListId": 0,
            "clientOrderId": "xTXKaGYd4bluPVp78IVRv1",
            "transactTime": 1563417480525,
            "price": "0.036435",
            "origQty": "0.624363",
            "executedQty": "0.000000",
            "cumulativeQuoteQty": "0.000000",
            "status": "NEW",
            "timeInForce": "GTC",
            "type": "LIMIT_MAKER",
            "side": "BUY"
        }
    ]
}

```

Raises `BinanceRequestException`, `BinanceAPIException`, `BinanceOrderException`, `BinanceOrderMinAmountException`, `BinanceOrderMinPriceException`, `BinanceOrderMinTotalException`, `BinanceOrderUnknownSymbolException`, `BinanceOrderInactiveSymbolException`

create_margin_order (**params)

Post a new order for margin account.

<https://binance-docs.github.io/apidocs/spot/en/#margin-account-new-order-trade>

Parameters

- **symbol** (*str*) – required
- **isIsolated** (*str*) – set to ‘TRUE’ for isolated margin (default ‘FALSE’)
- **side** (*str*) – required
- **type** (*str*) – required
- **quantity** (*decimal*) – required
- **price** (*str*) – required
- **stopPrice** (*str*) – Used with STOP_LOSS, STOP_LOSS_LIMIT, TAKE_PROFIT, and TAKE_PROFIT_LIMIT orders.
- **timeInForce** (*str*) – required if limit order GTC,IOC,FOK
- **newClientId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **icebergQty** (*str*) – Used with LIMIT, STOP_LOSS_LIMIT, and TAKE_PROFIT_LIMIT to create an iceberg order.
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; MARKET and LIMIT order types default to FULL, all other orders default to ACK.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

Response ACK:

```
{
  "symbol": "BTCUSDT",
  "orderId": 28,
  "clientOrderId": "6gCrw2kRUAf9CvJDGP16IP",
  "transactTime": 1507725176595
}
```

Response RESULT:

```
{
  "symbol": "BTCUSDT",
  "orderId": 28,
  "clientOrderId": "6gCrw2kRUAf9CvJDGP16IP",
  "transactTime": 1507725176595,
  "price": "1.00000000",
  "origQty": "10.00000000",
  "executedQty": "10.00000000",
  "cumulativeQuoteQty": "10.00000000",
  "status": "FILLED",
  "timeInForce": "GTC",
  "type": "MARKET",
  "side": "SELL"
}
```

Response FULL:

```

{
  "symbol": "BTCUSDT",
  "orderId": 28,
  "clientOrderId": "6gCrw2kRUAf9CvJDGP16IP",
  "transactTime": 1507725176595,
  "price": "1.00000000",
  "origQty": "10.00000000",
  "executedQty": "10.00000000",
  "cumulativeQuoteQty": "10.00000000",
  "status": "FILLED",
  "timeInForce": "GTC",
  "type": "MARKET",
  "side": "SELL",
  "fills": [
    {
      "price": "4000.00000000",
      "qty": "1.00000000",
      "commission": "4.00000000",
      "commissionAsset": "USDT"
    },
    {
      "price": "3999.00000000",
      "qty": "5.00000000",
      "commission": "19.99500000",
      "commissionAsset": "USDT"
    },
    {
      "price": "3998.00000000",
      "qty": "2.00000000",
      "commission": "7.99600000",
      "commissionAsset": "USDT"
    },
    {
      "price": "3997.00000000",
      "qty": "1.00000000",
      "commission": "3.99700000",
      "commissionAsset": "USDT"
    },
    {
      "price": "3995.00000000",
      "qty": "1.00000000",
      "commission": "3.99500000",
      "commissionAsset": "USDT"
    }
  ]
}

```

Raises `BinanceRequestException`, `BinanceAPIException`, `BinanceOrderException`, `BinanceOrderMinAmountException`, `BinanceOrderMinPriceException`, `BinanceOrderMinTotalException`, `BinanceOrderUnknownSymbolException`, `BinanceOrderInactiveSymbolException`

create_oco_order (**params)

Send in a new OCO order

<https://binance-docs.github.io/apidocs/spot/en/#new-oco-trade>

Parameters

- **symbol** (*str*) – required
- **listClientId** (*str*) – A unique id for the list order. Automatically generated if not sent.
- **side** (*str*) – required
- **quantity** (*decimal*) – required
- **limitClientId** (*str*) – A unique id for the limit order. Automatically generated if not sent.
- **price** (*str*) – required
- **limitIcebergQty** (*decimal*) – Used to make the LIMIT_MAKER leg an iceberg order.
- **stopClientId** (*str*) – A unique id for the stop order. Automatically generated if not sent.
- **stopPrice** (*str*) – required
- **stopLimitPrice** (*str*) – If provided, stopLimitTimeInForce is required.
- **stopIcebergQty** (*decimal*) – Used with STOP_LOSS_LIMIT leg to make an iceberg order.
- **stopLimitTimeInForce** (*str*) – Valid values are GTC/FOK/IOC.
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

Response ACK:

```
{
}
```

Response RESULT:

```
{
}
```

Response FULL:

```
{
}
```

Raises BinanceRequestException, BinanceAPIException, BinanceOrderException, BinanceOrderMinAmountException, BinanceOrderMinPriceException, BinanceOrderMinTotalException, BinanceOrderUnknownSymbolException, BinanceOrderInactiveSymbolException

create_order (***params*)

Send in a new order

Any order with an icebergQty MUST have timeInForce set to GTC.

<https://binance-docs.github.io/apidocs/spot/en/#new-order-trade>

Parameters

- **symbol** (*str*) – required
- **side** (*str*) – required
- **type** (*str*) – required
- **timeInForce** (*str*) – required if limit order
- **quantity** (*decimal*) – required
- **quoteOrderQty** (*decimal*) – amount the user wants to spend (when buying) or receive (when selling) of the quote asset, applicable to MARKET orders
- **price** (*str*) – required
- **newClientOrderId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **icebergQty** (*decimal*) – Used with LIMIT, STOP_LOSS_LIMIT, and TAKE_PROFIT_LIMIT to create an iceberg order.
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

Response ACK:

```
{
  "symbol": "LTCBTC",
  "orderId": 1,
  "clientOrderId": "myOrder1" # Will be newClientOrderId
  "transactTime": 1499827319559
}
```

Response RESULT:

```
{
  "symbol": "BTCUSDT",
  "orderId": 28,
  "clientOrderId": "6gCrw2kRUAf9CvJDGP16IP",
  "transactTime": 1507725176595,
  "price": "0.00000000",
  "origQty": "10.00000000",
  "executedQty": "10.00000000",
  "status": "FILLED",
  "timeInForce": "GTC",
  "type": "MARKET",
  "side": "SELL"
}
```

Response FULL:

```
{
  "symbol": "BTCUSDT",
  "orderId": 28,
  "clientOrderId": "6gCrw2kRUAf9CvJDGP16IP",
  "transactTime": 1507725176595,
  "price": "0.00000000",
  "origQty": "10.00000000",
```

(continues on next page)

(continued from previous page)

```

"executedQty": "10.00000000",
"status": "FILLED",
"timeInForce": "GTC",
"type": "MARKET",
"side": "SELL",
"fills": [
  {
    "price": "4000.00000000",
    "qty": "1.00000000",
    "commission": "4.00000000",
    "commissionAsset": "USDT"
  },
  {
    "price": "3999.00000000",
    "qty": "5.00000000",
    "commission": "19.99500000",
    "commissionAsset": "USDT"
  },
  {
    "price": "3998.00000000",
    "qty": "2.00000000",
    "commission": "7.99600000",
    "commissionAsset": "USDT"
  },
  {
    "price": "3997.00000000",
    "qty": "1.00000000",
    "commission": "3.99700000",
    "commissionAsset": "USDT"
  },
  {
    "price": "3995.00000000",
    "qty": "1.00000000",
    "commission": "3.99500000",
    "commissionAsset": "USDT"
  }
]
}

```

Raises `BinanceRequestException`, `BinanceAPIException`, `BinanceOrderException`, `BinanceOrderMinAmountException`, `BinanceOrderMinPriceException`, `BinanceOrderMinTotalException`, `BinanceOrderUnknownSymbolException`, `BinanceOrderInactiveSymbolException`

create_sub_account_futures_transfer (**params)

Execute sub-account Futures transfer

<https://github.com/binance-exchange/binance-official-api-docs/blob/9dbe0e961b80557bb19708a707c7fad08842b28e/wapi-api.md#sub-account-transferfor-master-account>

Parameters

- **fromEmail** (*str*) – required - Sender email
- **toEmail** (*str*) – required - Recipient email
- **futuresType** (*int*) – required
- **asset** (*str*) – required

- **amount** (*decimal*) – required
- **recvWindow** (*int*) – optional

Returns API response

```
{
    "success":true,
    "txnId":"2934662589"
}
```

Raises BinanceRequestException, BinanceAPIException

create_test_order (***params*)

Test new order creation and signature/recvWindow long. Creates and validates a new order but does not send it into the matching engine.

<https://binance-docs.github.io/apidocs/spot/en/#test-new-order-trade>

Parameters

- **symbol** (*str*) – required
- **side** (*str*) – required
- **type** (*str*) – required
- **timeInForce** (*str*) – required if limit order
- **quantity** (*decimal*) – required
- **price** (*str*) – required
- **newClientOrderId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **icebergQty** (*decimal*) – Used with iceberg orders
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – The number of milliseconds the request is valid for

Returns API response

```
{ }
```

Raises BinanceRequestException, BinanceAPIException, BinanceOrderException, BinanceOrderMinAmountException, BinanceOrderMinPriceException, BinanceOrderMinTotalException, BinanceOrderUnknownSymbolException, BinanceOrderInactiveSymbolException

disable_fast_withdraw_switch (***params*)

Disable Fast Withdraw Switch

https://binance-docs.github.io/apidocs/spot/en/#disable-fast-withdraw-switch-user_data

Parameters **recvWindow** (*int*) – optional

Returns API response

Raises BinanceRequestException, BinanceAPIException

disable_isolated_margin_account (**params)

Disable isolated margin account for a specific symbol. Each trading pair can only be deactivated once every 24 hours.

<https://binance-docs.github.io/apidocs/spot/en/#disable-isolated-margin-account-trade>

Parameters **symbol** –

Returns API response

```
{
  "success": true,
  "symbol": "BTCUSDT"
}
```

enable_fast_withdraw_switch (**params)

Enable Fast Withdraw Switch

https://binance-docs.github.io/apidocs/spot/en/#enable-fast-withdraw-switch-user_data

Parameters **recvWindow** (*int*) – optional

Returns API response

Raises BinanceRequestException, BinanceAPIException

enable_isolated_margin_account (**params)

Enable isolated margin account for a specific symbol.

<https://binance-docs.github.io/apidocs/spot/en/#enable-isolated-margin-account-trade>

Parameters **symbol** –

Returns API response

```
{
  "success": true,
  "symbol": "BTCUSDT"
}
```

enable_subaccount_futures (**params)

Enable Futures for Sub-account (For Master Account)

<https://binance-docs.github.io/apidocs/spot/en/#enable-futures-for-sub-account-for-master-account>

Parameters

- **email** (*str*) – required - Sub account email
- **recvWindow** (*int*) – optional

Returns API response

```
{
  "email": "123@test.com",
  "isFuturesEnabled": true // true or false
}
```

Raises BinanceRequestException, BinanceAPIException

enable_subaccount_margin (**params)

Enable Margin for Sub-account (For Master Account)

<https://binance-docs.github.io/apidocs/spot/en/#enable-margin-for-sub-account-for-master-account>

Parameters

- **email** (*str*) – required - Sub account email
- **recvWindow** (*int*) – optional

Returns API response

```
{
    "email": "123@test.com",
    "isMarginEnabled": true
}
```

Raises BinanceRequestException, BinanceAPIException

futures_account (**params)

Get current account information.

https://binance-docs.github.io/apidocs/futures/en/#account-information-user_data

futures_account_balance (**params)

Get futures account balance

https://binance-docs.github.io/apidocs/futures/en/#future-account-balance-user_data

futures_account_trades (**params)

Get trades for the authenticated account and symbol.

https://binance-docs.github.io/apidocs/futures/en/#account-trade-list-user_data

futures_account_transfer (**params)

Execute transfer between spot account and futures account.

<https://binance-docs.github.io/apidocs/futures/en/#new-future-account-transfer>

futures_adl_quantile_estimate (**params)

Get Position ADL Quantile Estimate

https://binance-docs.github.io/apidocs/futures/en/#position-adl-quantile-estimation-user_data

futures_aggregate_trades (**params)

Get compressed, aggregate trades. Trades that fill at the time, from the same order, with the same price will have the quantity aggregated.

https://binance-docs.github.io/apidocs/futures/en/#compressed-aggregate-trades-list-market_data

futures_cancel_all_open_orders (**params)

Cancel all open futures orders

<https://binance-docs.github.io/apidocs/futures/en/#cancel-all-open-orders-trade>

futures_cancel_order (**params)

Cancel an active futures order.

<https://binance-docs.github.io/apidocs/futures/en/#cancel-order-trade>

- futures_cancel_orders** (**params)
Cancel multiple futures orders
<https://binance-docs.github.io/apidocs/futures/en/#cancel-multiple-orders-trade>
- futures_change_leverage** (**params)
Change user's initial leverage of specific symbol market
<https://binance-docs.github.io/apidocs/futures/en/#change-initial-leverage-trade>
- futures_change_margin_type** (**params)
Change the margin type for a symbol
<https://binance-docs.github.io/apidocs/futures/en/#change-margin-type-trade>
- futures_change_multi_assets_mode** (*multiAssetsMargin: bool*)
Change user's Multi-Assets mode (Multi-Assets Mode or Single-Asset Mode) on Every symbol
<https://binance-docs.github.io/apidocs/futures/en/#change-multi-assets-mode-trade>
- futures_change_position_margin** (**params)
Change the position margin for a symbol
<https://binance-docs.github.io/apidocs/futures/en/#modify-isolated-position-margin-trade>
- futures_change_position_mode** (**params)
Change position mode for authenticated account
<https://binance-docs.github.io/apidocs/futures/en/#change-position-mode-trade>
- futures_coin_account** (**params)
Get current account information.
https://binance-docs.github.io/apidocs/delivery/en/#account-information-user_data
- futures_coin_account_balance** (**params)
Get futures account balance
https://binance-docs.github.io/apidocs/delivery/en/#futures-account-balance-user_data
- futures_coin_account_trades** (**params)
Get trades for the authenticated account and symbol.
https://binance-docs.github.io/apidocs/delivery/en/#account-trade-list-user_data
- futures_coin_aggregate_trades** (**params)
Get compressed, aggregate trades. Trades that fill at the time, from the same order, with the same price will have the quantity aggregated.
<https://binance-docs.github.io/apidocs/delivery/en/#compressed-aggregate-trades-list>
- futures_coin_cancel_all_open_orders** (**params)
Cancel all open futures orders
<https://binance-docs.github.io/apidocs/delivery/en/#cancel-all-open-orders-trade>
- futures_coin_cancel_order** (**params)
Cancel an active futures order.
<https://binance-docs.github.io/apidocs/delivery/en/#cancel-order-trade>
- futures_coin_cancel_orders** (**params)
Cancel multiple futures orders
<https://binance-docs.github.io/apidocs/delivery/en/#cancel-multiple-orders-trade>

futures_coin_change_leverage (**params)
Change user's initial leverage of specific symbol market
<https://binance-docs.github.io/apidocs/delivery/en/#change-initial-leverage-trade>

futures_coin_change_margin_type (**params)
Change the margin type for a symbol
<https://binance-docs.github.io/apidocs/delivery/en/#change-margin-type-trade>

futures_coin_change_position_margin (**params)
Change the position margin for a symbol
<https://binance-docs.github.io/apidocs/delivery/en/#modify-isolated-position-margin-trade>

futures_coin_change_position_mode (**params)
Change user's position mode (Hedge Mode or One-way Mode) on EVERY symbol
<https://binance-docs.github.io/apidocs/delivery/en/#change-position-mode-trade>

futures_coin_continuous_klines (**params)
Kline/candlestick bars for a specific contract type. Klines are uniquely identified by their open time.
<https://binance-docs.github.io/apidocs/delivery/en/#continuous-contract-kline-candlestick-data>

futures_coin_create_order (**params)
Send in a new order.
<https://binance-docs.github.io/apidocs/delivery/en/#new-order-trade>

futures_coin_exchange_info ()
Current exchange trading rules and symbol information
<https://binance-docs.github.io/apidocs/delivery/en/#exchange-information>

futures_coin_funding_rate (**params)
Get funding rate history
<https://binance-docs.github.io/apidocs/delivery/en/#get-funding-rate-history-of-perpetual-futures>

futures_coin_get_all_orders (**params)
Get all futures account orders; active, canceled, or filled.
https://binance-docs.github.io/apidocs/delivery/en/#all-orders-user_data

futures_coin_get_open_orders (**params)
Get all open orders on a symbol.
https://binance-docs.github.io/apidocs/delivery/en/#current-all-open-orders-user_data

futures_coin_get_order (**params)
Check an order's status.
https://binance-docs.github.io/apidocs/delivery/en/#query-order-user_data

futures_coin_get_position_mode (**params)
Get user's position mode (Hedge Mode or One-way Mode) on EVERY symbol
https://binance-docs.github.io/apidocs/delivery/en/#get-current-position-mode-user_data

futures_coin_historical_trades (**params)
Get older market historical trades.
https://binance-docs.github.io/apidocs/delivery/en/#old-trades-lookup-market_data

- futures_coin_income_history** (**params)
Get income history for authenticated account
https://binance-docs.github.io/apidocs/delivery/en/#get-income-history-user_data
- futures_coin_index_price_klines** (**params)
Kline/candlestick bars for the index price of a pair..
<https://binance-docs.github.io/apidocs/delivery/en/#index-price-kline-candlestick-data>
- futures_coin_klines** (**params)
Kline/candlestick bars for a symbol. Klines are uniquely identified by their open time.
<https://binance-docs.github.io/apidocs/delivery/en/#kline-candlestick-data>
- futures_coin_leverage_bracket** (**params)
Notional and Leverage Brackets
https://binance-docs.github.io/apidocs/delivery/en/#notional-bracket-for-pair-user_data
- futures_coin_liquidation_orders** (**params)
Get all liquidation orders
https://binance-docs.github.io/apidocs/delivery/en/#user-39-s-force-orders-user_data
- futures_coin_mark_price** (**params)
Get Mark Price and Funding Rate
<https://binance-docs.github.io/apidocs/delivery/en/#index-price-and-mark-price>
- futures_coin_mark_price_klines** (**params)
Kline/candlestick bars for the index price of a pair..
<https://binance-docs.github.io/apidocs/delivery/en/#mark-price-kline-candlestick-data>
- futures_coin_open_interest** (**params)
Get present open interest of a specific symbol.
<https://binance-docs.github.io/apidocs/delivery/en/#open-interest>
- futures_coin_open_interest_hist** (**params)
Get open interest statistics of a specific symbol.
<https://binance-docs.github.io/apidocs/delivery/en/#open-interest-statistics-market-data>
- futures_coin_order_book** (**params)
Get the Order Book for the market
<https://binance-docs.github.io/apidocs/delivery/en/#order-book>
- futures_coin_orderbook_ticker** (**params)
Best price/qty on the order book for a symbol or symbols.
<https://binance-docs.github.io/apidocs/delivery/en/#symbol-order-book-ticker>
- futures_coin_ping** ()
Test connectivity to the Rest API
<https://binance-docs.github.io/apidocs/delivery/en/#test-connectivity>
- futures_coin_place_batch_order** (**params)
Send in new orders.
<https://binance-docs.github.io/apidocs/delivery/en/#place-multiple-orders-trade>
To avoid modifying the existing signature generation and parameter order logic, the url encoding is done on the special query param, batchOrders, in the early stage.

futures_coin_position_information (**params)
Get position information
https://binance-docs.github.io/apidocs/delivery/en/#position-information-user_data

futures_coin_position_margin_history (**params)
Get position margin change history
<https://binance-docs.github.io/apidocs/delivery/en/#get-position-margin-change-history-trade>

futures_coin_recent_trades (**params)
Get recent trades (up to last 500).
<https://binance-docs.github.io/apidocs/delivery/en/#recent-trades-list>

futures_coin_stream_close (listenKey)

futures_coin_stream_get_listen_key ()

futures_coin_stream_keepalive (listenKey)

futures_coin_symbol_ticker (**params)
Latest price for a symbol or symbols.
<https://binance-docs.github.io/apidocs/delivery/en/#symbol-price-ticker>

futures_coin_ticker (**params)
24 hour rolling window price change statistics.
<https://binance-docs.github.io/apidocs/delivery/en/#24hr-ticker-price-change-statistics>

futures_coin_time ()
Test connectivity to the Rest API and get the current server time.
<https://binance-docs.github.io/apidocs/delivery/en/#check-server-time>

futures_continuous_klines (**params)
Kline/candlestick bars for a specific contract type. Klines are uniquely identified by their open time.
<https://binance-docs.github.io/apidocs/futures/en/#continuous-contract-kline-candlestick-data>

futures_create_order (**params)
Send in a new order.
<https://binance-docs.github.io/apidocs/futures/en/#new-order-trade>

futures_exchange_info ()
Current exchange trading rules and symbol information
https://binance-docs.github.io/apidocs/futures/en/#exchange-information-market_data

futures_funding_rate (**params)
Get funding rate history
https://binance-docs.github.io/apidocs/futures/en/#get-funding-rate-history-market_data

futures_get_all_orders (**params)
Get all futures account orders; active, canceled, or filled.
https://binance-docs.github.io/apidocs/futures/en/#all-orders-user_data

futures_get_multi_assets_mode ()
Get user's Multi-Assets mode (Multi-Assets Mode or Single-Asset Mode) on Every symbol
https://binance-docs.github.io/apidocs/futures/en/#get-current-multi-assets-mode-user_data

futures_get_open_orders (**params)

Get all open orders on a symbol.

https://binance-docs.github.io/apidocs/futures/en/#current-open-orders-user_data

futures_get_order (**params)

Check an order's status.

https://binance-docs.github.io/apidocs/futures/en/#query-order-user_data

futures_get_position_mode (**params)

Get position mode for authenticated account

https://binance-docs.github.io/apidocs/futures/en/#get-current-position-mode-user_data

futures_global_longshort_ratio (**params)

Get present global long to short ratio of a specific symbol.

<https://binance-docs.github.io/apidocs/futures/en/#long-short-ratio>

futures_historical_klines (symbol, interval, start_str, end_str=None, limit=500)

Get historical futures klines from Binance

Parameters

- **symbol** (str) – Name of symbol pair e.g BNBBTC
- **interval** (str) – Binance Kline interval
- **start_str** (str/int) – Start date string in UTC format or timestamp in milliseconds
- **end_str** (str/int) – optional - end date string in UTC format or timestamp in milliseconds (default will fetch everything up to now)
- **limit** (int) – Default 500; max 1000.

Returns list of OHLCV values

futures_historical_klines_generator (symbol, interval, start_str, end_str=None)

Get historical futures klines generator from Binance

Parameters

- **symbol** (str) – Name of symbol pair e.g BNBBTC
- **interval** (str) – Binance Kline interval
- **start_str** (str/int) – Start date string in UTC format or timestamp in milliseconds
- **end_str** (str/int) – optional - end date string in UTC format or timestamp in milliseconds (default will fetch everything up to now)

Returns generator of OHLCV values

futures_historical_trades (**params)

Get older market historical trades.

https://binance-docs.github.io/apidocs/futures/en/#old-trades-lookup-market_data

futures_income_history (**params)

Get income history for authenticated account

https://binance-docs.github.io/apidocs/futures/en/#get-income-history-user_data

futures_klines (**params)

Kline/candlestick bars for a symbol. Klines are uniquely identified by their open time.

https://binance-docs.github.io/apidocs/futures/en/#kline-candlestick-data-market_data

futures_leverage_bracket (***params*)
Notional and Leverage Brackets
https://binance-docs.github.io/apidocs/futures/en/#notional-and-leverage-brackets-market_data

futures_liquidation_orders (***params*)
Get all liquidation orders
https://binance-docs.github.io/apidocs/futures/en/#get-all-liquidation-orders-market_data

futures_mark_price (***params*)
Get Mark Price and Funding Rate
https://binance-docs.github.io/apidocs/futures/en/#mark-price-market_data

futures_open_interest (***params*)
Get present open interest of a specific symbol.
<https://binance-docs.github.io/apidocs/futures/en/#open-interest>

futures_open_interest_hist (***params*)
Get open interest statistics of a specific symbol.
<https://binance-docs.github.io/apidocs/futures/en/#open-interest-statistics>

futures_order_book (***params*)
Get the Order Book for the market
https://binance-docs.github.io/apidocs/futures/en/#order-book-market_data

futures_orderbook_ticker (***params*)
Best price/qty on the order book for a symbol or symbols.
https://binance-docs.github.io/apidocs/futures/en/#symbol-order-book-ticker-market_data

futures_ping ()
Test connectivity to the Rest API
<https://binance-docs.github.io/apidocs/futures/en/#test-connectivity>

futures_place_batch_order (***params*)
Send in new orders.
<https://binance-docs.github.io/apidocs/futures/en/#place-multiple-orders-trade>
To avoid modifying the existing signature generation and parameter order logic, the url encoding is done on the special query param, batchOrders, in the early stage.

futures_position_information (***params*)
Get position information
https://binance-docs.github.io/apidocs/futures/en/#position-information-user_data

futures_position_margin_history (***params*)
Get position margin change history
<https://binance-docs.github.io/apidocs/futures/en/#get-postion-margin-change-history-trade>

futures_recent_trades (***params*)
Get recent trades (up to last 500).
https://binance-docs.github.io/apidocs/futures/en/#recent-trades-list-market_data

futures_stream_close (*listenKey*)

futures_stream_get_listen_key ()

futures_stream_keepalive (*listenKey*)

futures_symbol_ticker (***params*)

Latest price for a symbol or symbols.

https://binance-docs.github.io/apidocs/futures/en/#symbol-price-ticker-market_data

futures_ticker (***params*)

24 hour rolling window price change statistics.

https://binance-docs.github.io/apidocs/futures/en/#24hr-ticker-price-change-statistics-market_data

futures_time ()

Test connectivity to the Rest API and get the current server time.

<https://binance-docs.github.io/apidocs/futures/en/#check-server-time>

futures_top_longshort_account_ratio (***params*)

Get present long to short ratio for top accounts of a specific symbol.

https://binance-docs.github.io/apidocs/futures/en/#top-trader-long-short-ratio-accounts-market_data

futures_top_longshort_position_ratio (***params*)

Get present long to short ratio for top positions of a specific symbol.

<https://binance-docs.github.io/apidocs/futures/en/#top-trader-long-short-ratio-positions>

get_account (***params*)

Get current account information.

https://binance-docs.github.io/apidocs/spot/en/#account-information-user_data

Parameters `recvWindow` (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "makerCommission": 15,
  "takerCommission": 15,
  "buyerCommission": 0,
  "sellerCommission": 0,
  "canTrade": true,
  "canWithdraw": true,
  "canDeposit": true,
  "balances": [
    {
      "asset": "BTC",
      "free": "4723846.89208129",
      "locked": "0.00000000"
    },
    {
      "asset": "LTC",
      "free": "4763368.68006011",
      "locked": "0.00000000"
    }
  ]
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_account_api_permissions (***params*)

Fetch api key permissions.

https://binance-docs.github.io/apidocs/spot/en/#get-api-key-permission-user_data

Parameters `recvWindow` (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "ipRestrict": false,
  "createTime": 1623840271000,
  "enableWithdrawals": false, // This option allows you to withdraw via
  ↳ API. You must apply the IP Access Restriction filter in order to enable
  ↳ withdrawals
  "enableInternalTransfer": true, // This option authorizes this key to
  ↳ transfer funds between your master account and your sub account instantly
  "permitsUniversalTransfer": true, // Authorizes this key to be used for a
  ↳ dedicated universal transfer API to transfer multiple supported currencies.
  ↳ Each business's own transfer API rights are not affected by this
  ↳ authorization
  "enableVanillaOptions": false, // Authorizes this key to Vanilla options
  ↳ trading
  "enableReading": true,
  "enableFutures": false, // API Key created before your futures account
  ↳ opened does not support futures API service
  "enableMargin": false, // This option can be adjusted after the Cross
  ↳ Margin account transfer is completed
  "enableSpotAndMarginTrading": false, // Spot and margin trading
  "tradingAuthorityExpirationTime": 1628985600000 // Expiration time for
  ↳ spot and margin trading permission
}
```

`get_account_api_trading_status(**params)`

Fetch account api trading status detail.

https://binance-docs.github.io/apidocs/spot/en/#account-api-trading-status-sapi-user_data

Parameters `recvWindow` (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "data": { // API trading status detail
    "isLocked": false, // API trading function is locked or not
    "plannedRecoverTime": 0, // If API trading function is locked, this
  ↳ is the planned recover time
    "triggerCondition": {
      "GCR": 150, // Number of GTC orders
      "IFER": 150, // Number of FOK/IOC orders
      "UFR": 300 // Number of orders
    },
    "indicators": { // The indicators updated every 30 seconds
      "BTCUSDT": [ // The symbol
        {
          "i": "UFR", // Unfilled Ratio (UFR)
          "c": 20, // Count of all orders
          "v": 0.05, // Current UFR value
          "t": 0.995 // Trigger UFR value
        },
        {
          "i": "IFER", // IOC/FOK Expiration Ratio (IFER)
          "c": 20, // Count of FOK/IOC orders
        }
      ]
    }
  }
}
```

(continues on next page)

(continued from previous page)

```

        "v": 0.99, // Current IFER value
        "t": 0.99 // Trigger IFER value
    },
    {
        "i": "GCR", // GTC Cancellation Ratio (GCR)
        "c": 20, // Count of GTC orders
        "v": 0.99, // Current GCR value
        "t": 0.99 // Trigger GCR value
    }
],
"ETHUSDT": [
    {
        "i": "UFR",
        "c": 20,
        "v": 0.05,
        "t": 0.995
    },
    {
        "i": "IFER",
        "c": 20,
        "v": 0.99,
        "t": 0.99
    },
    {
        "i": "GCR",
        "c": 20,
        "v": 0.99,
        "t": 0.99
    }
]
},
"updateTime": 1547630471725
}

```

get_account_snapshot (**params)

Get daily account snapshot of specific type.

https://binance-docs.github.io/apidocs/spot/en/#daily-account-snapshot-user_data**Parameters**

- **type** (*string*) – required. Valid values are SPOT/MARGIN/FUTURES.
- **startTime** (*int*) – optional
- **endTime** (*int*) – optional
- **limit** (*int*) – optional
- **recvWindow** (*int*) – optional

Returns API response

```

{
  "code": 200, // 200 for success; others are error codes
  "msg": "", // error message
  "snapshotVos": [
    {

```

(continues on next page)

(continued from previous page)

```

    "data":{
      "balances":[
        {
          "asset":"BTC",
          "free":"0.09905021",
          "locked":"0.00000000"
        },
        {
          "asset":"USDT",
          "free":"1.89109409",
          "locked":"0.00000000"
        }
      ],
      "totalAssetOfBtc":"0.09942700"
    },
    "type":"spot",
    "updateTime":1576281599000
  }
]
}

```

OR

```

{
  "code":200, // 200 for success; others are error codes
  "msg":""," // error message
  "snapshotVos":[
    {
      "data":{
        "marginLevel":"2748.02909813",
        "totalAssetOfBtc":"0.00274803",
        "totalLiabilityOfBtc":"0.00000100",
        "totalNetAssetOfBtc":"0.00274750",
        "userAssets":[
          {
            "asset":"XRP",
            "borrowed":"0.00000000",
            "free":"1.00000000",
            "interest":"0.00000000",
            "locked":"0.00000000",
            "netAsset":"1.00000000"
          }
        ]
      },
      "type":"margin",
      "updateTime":1576281599000
    }
  ]
}

```

OR

```

{
  "code":200, // 200 for success; others are error codes
  "msg":""," // error message
  "snapshotVos":[
    {

```

(continues on next page)

(continued from previous page)

```

    "data":{
      "assets":[
        {
          "asset":"USDT",
          "marginBalance":"118.99782335",
          "walletBalance":"120.23811389"
        }
      ],
      "position":[
        {
          "entryPrice":"7130.41000000",
          "markPrice":"7257.66239673",
          "positionAmt":"0.01000000",
          "symbol":"BTCUSDT",
          "unRealizedProfit":"1.24029054"
        }
      ]
    },
    "type":"futures",
    "updateTime":1576281599000
  }
]
}

```

Raises `BinanceRequestException`, `BinanceAPIException`

get_account_status (**params)

Get account status detail.

https://binance-docs.github.io/apidocs/spot/en/#account-status-sapi-user_data

Parameters `recvWindow` (*int*) – the number of milliseconds the request is valid for

Returns API response

```

{
  "data": "Normal"
}

```

get_aggregate_trades (**params) → Dict[KT, VT]

Get compressed, aggregate trades. Trades that fill at the time, from the same order, with the same price will have the quantity aggregated.

<https://binance-docs.github.io/apidocs/spot/en/#compressed-aggregate-trades-list>

Parameters

- **symbol** (*str*) – required
- **fromId** (*str*) – ID to get aggregate trades from INCLUSIVE.
- **startTime** (*int*) – Timestamp in ms to get aggregate trades from INCLUSIVE.
- **endTime** (*int*) – Timestamp in ms to get aggregate trades until INCLUSIVE.
- **limit** (*int*) – Default 500; max 1000.

Returns API response

```
[
  {
    "a": 26129,          # Aggregate tradeId
    "p": "0.01633102", # Price
    "q": "4.70443515", # Quantity
    "f": 27781,        # First tradeId
    "l": 27781,        # Last tradeId
    "T": 1498793709153, # Timestamp
    "m": true,         # Was the buyer the maker?
    "M": true          # Was the trade the best price match?
  }
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_all_coins_info (***params*)

Get information of coins (available for deposit and withdraw) for user.

https://binance-docs.github.io/apidocs/spot/en/#all-coins-39-information-user_data

Parameters `recvWindow` (*int*) – optional

Returns API response

```
{
  "coin": "BTC",
  "depositAllEnable": true,
  "withdrawAllEnable": true,
  "name": "Bitcoin",
  "free": "0",
  "locked": "0",
  "freeze": "0",
  "withdrawing": "0",
  "ipoing": "0",
  "ipoable": "0",
  "storage": "0",
  "isLegalMoney": false,
  "trading": true,
  "networkList": [
    {
      "network": "BNB",
      "coin": "BTC",
      "withdrawIntegerMultiple": "0.00000001",
      "isDefault": false,
      "depositEnable": true,
      "withdrawEnable": true,
      "depositDesc": "",
      "withdrawDesc": "",
      "specialTips": "Both a MEMO and an Address are required to_
↪successfully deposit your BEP2-BTCB tokens to Binance.",
      "name": "BEP2",
      "resetAddressStatus": false,
      "addressRegex": "^(bnb1)[0-9a-z]{38}$",
      "memoRegex": "^[0-9A-Za-z-_{1,120}$",
      "withdrawFee": "0.0000026",
      "withdrawMin": "0.0000052",
      "withdrawMax": "0",
      "minConfirm": 1,

```

(continues on next page)

(continued from previous page)

```

        "unlockConfirm": 0
    },
    {
        "network": "BTC",
        "coin": "BTC",
        "withdrawIntegerMultiple": "0.00000001",
        "isDefault": true,
        "depositEnable": true,
        "withdrawEnable": true,
        "depositDesc": "",
        "withdrawDesc": "",
        "specialTips": "",
        "name": "BTC",
        "resetAddressStatus": false,
        "addressRegex": "^[13][a-km-zA-HJ-NP-Z1-9]{25,34}$|^ (bc1) [0-9A-Za-
↵z]{39,59}$",
        "memoRegex": "",
        "withdrawFee": "0.0005",
        "withdrawMin": "0.001",
        "withdrawMax": "0",
        "minConfirm": 1,
        "unlockConfirm": 2
    }
]
}

```

Raises `BinanceRequestException`, `BinanceAPIException`

get_all_isolated_margin_symbols (**params)

Query isolated margin symbol info for all pairs

https://binance-docs.github.io/apidocs/spot/en/#get-all-isolated-margin-symbol-user_data

```
pair_details = client.get_all_isolated_margin_symbols()
```

Returns API response

```

[
  {
    "base": "BNB",
    "isBuyAllowed": true,
    "isMarginTrade": true,
    "isSellAllowed": true,
    "quote": "BTC",
    "symbol": "BNBBTC"
  },
  {
    "base": "TRX",
    "isBuyAllowed": true,
    "isMarginTrade": true,
    "isSellAllowed": true,
    "quote": "BTC",
    "symbol": "TRXBTC"
  }
]

```

Raises BinanceRequestException, BinanceAPIException

get_all_margin_orders (**params)

Query all margin accounts orders

If orderId is set, it will get orders >= that orderId. Otherwise most recent orders are returned.

For some historical orders cumulativeQuoteQty will be < 0, meaning the data is not available at this time.

https://binance-docs.github.io/apidocs/spot/en/#query-margin-account-39-s-all-order-user_data

Parameters

- **symbol** (*str*) – required
- **isIsolated** (*str*) – set to ‘TRUE’ for isolated margin (default ‘FALSE’)
- **orderId** (*str*) – optional
- **startTime** (*str*) – optional
- **endTime** (*str*) – optional
- **limit** (*int*) – Default 500; max 1000
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns

API response

```
[
  { "id": 43123876, "price": "0.00395740", "qty": "4.06000000", "quoteQty":
    "0.01606704", "symbol": "BNBBTC", "time": 1556089977693
  }, {
    "id": 43123877, "price": "0.00395740", "qty": "0.77000000", "quoteQty":
    "0.00304719", "symbol": "BNBBTC", "time": 1556089977693
  }, {
    "id": 43253549, "price": "0.00428930", "qty": "23.30000000", "quoteQty":
    "0.09994069", "symbol": "BNBBTC", "time": 1556163963504
  }
]
```

Raises BinanceRequestException, BinanceAPIException

get_all_orders (**params)

Get all account orders; active, canceled, or filled.

https://binance-docs.github.io/apidocs/spot/en/#all-orders-user_data

Parameters

- **symbol** (*str*) – required
- **orderId** (*int*) – The unique order id
- **startTime** (*int*) – optional
- **endTime** (*int*) – optional
- **limit** (*int*) – Default 500; max 1000.

- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
[
  {
    "symbol": "LTCBTC",
    "orderId": 1,
    "clientOrderId": "myOrder1",
    "price": "0.1",
    "origQty": "1.0",
    "executedQty": "0.0",
    "status": "NEW",
    "timeInForce": "GTC",
    "type": "LIMIT",
    "side": "BUY",
    "stopPrice": "0.0",
    "icebergQty": "0.0",
    "time": 1499827319559
  }
]
```

Raises BinanceRequestException, BinanceAPIException

get_all_tickers () → List[Dict[str, str]]

Latest price for all symbols.

<https://binance-docs.github.io/apidocs/spot/en/#symbol-price-ticker>

Returns List of market tickers

```
[
  {
    "symbol": "LTCBTC",
    "price": "4.00000200"
  },
  {
    "symbol": "ETHBTC",
    "price": "0.07946600"
  }
]
```

Raises BinanceRequestException, BinanceAPIException

get_asset_balance (*asset*, ***params*)

Get current asset balance.

Parameters

- **asset** (*str*) – required
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns dictionary or None if not found

```
{
  "asset": "BTC",
  "free": "4723846.89208129",
```

(continues on next page)

(continued from previous page)

```

    "locked": "0.00000000"
}

```

Raises `BinanceRequestException`, `BinanceAPIException`

get_asset_details (**params)

Fetch details on assets.

https://binance-docs.github.io/apidocs/spot/en/#asset-detail-sapi-user_data

Parameters

- **asset** (*str*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```

{
    "CTR": {
        "minWithdrawAmount": "70.00000000", //min withdraw amount
        "depositStatus": false, //deposit status (false if ALL of networks
↪ ' are false)
        "withdrawFee": 35, // withdraw fee
        "withdrawStatus": true, //withdraw status (false if ALL of_
↪ networks' are false)
        "depositTip": "Delisted, Deposit Suspended" //reason
    },
    "SKY": {
        "minWithdrawAmount": "0.02000000",
        "depositStatus": true,
        "withdrawFee": 0.01,
        "withdrawStatus": true
    }
}

```

get_asset_dividend_history (**params)

Query asset dividend record.

https://binance-docs.github.io/apidocs/spot/en/#asset-dividend-record-user_data

Parameters

- **asset** (*str*) – optional
- **startTime** (*long*) – optional
- **endTime** (*long*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

```
result = client.get_asset_dividend_history()
```

Returns API response

```

{
    "rows": [
        {

```

(continues on next page)

(continued from previous page)

```

        "amount": "10.00000000",
        "asset": "BHFT",
        "divTime": 1563189166000,
        "enInfo": "BHFT distribution",
        "tranId": 2968885920
    },
    {
        "amount": "10.00000000",
        "asset": "BHFT",
        "divTime": 1563189165000,
        "enInfo": "BHFT distribution",
        "tranId": 2968885920
    }
],
"total": 2
}

```

Raises `BinanceRequestException`, `BinanceAPIException`

get_avg_price (**params)

Current average price for a symbol.

<https://binance-docs.github.io/apidocs/spot/en/#current-average-price>

Parameters `symbol` (*str*) –

Returns API response

```

{
    "mins": 5,
    "price": "9.35751834"
}

```

get_bnb_burn_spot_margin (**params)

Get BNB Burn Status

https://binance-docs.github.io/apidocs/spot/en/#get-bnb-burn-status-user_data

```
status = client.get_bnb_burn_spot_margin()
```

Returns API response

```

{
    "spotBNBBurn": true,
    "interestBNBBurn": false
}

```

Raises `BinanceRequestException`, `BinanceAPIException`

get_c2c_trade_history (**params)

Get C2C Trade History

https://binance-docs.github.io/apidocs/spot/en/#get-c2c-trade-history-user_data

Parameters

- **tradeType** (*str*) – required - BUY, SELL

- **startTimestamp** – optional
- **endTimestamp** (*int*) – optional
- **page** (*int*) – optional - default 1
- **rows** (*int*) – optional - default 100, max 100
- **recvWindow** (*int*) – optional

Returns

API response

```
{ "code": "000000", "message": "success", "data": [
  { "orderNumber": "20219644646554779648", "advNo":
    "11218246497340923904", "tradeType": "SELL", "asset": "BUSD", "fiat":
    "CNY", "fiatSymbol": "", "amount": "5000.00000000", // Quantity (in Crypto)
    "totalPrice": "33400.00000000", "unitPrice": "6.68", // Unit Price (in Fiat)
    "orderStatus": "COMPLETED", // PENDING, TRADING, BUYER_PAYED,
    DISTRIBUTING, COMPLETED, IN_APPEAL, CANCELLED, CAN-
    CANCELLED_BY_SYSTEM "createTime": 1619361369000, "commission":
    "0", // Transaction Fee (in Crypto) "counterPartNickName": "ab***", "advertise-
    mentRole": "TAKER"
  }
], "total": 1, "success": true
}
```

get_deposit_address (*coin*: *str*, *network*: *Optional[str]* = *None*, ***params*)

Fetch a deposit address for a symbol

https://binance-docs.github.io/apidocs/spot/en/#deposit-address-supporting-network-user_data

Parameters

- **coin** (*str*) – required
- **network** (*str*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "address": "1HPn8Rx2y6nNSfagQBKy27GB99Vbzg89wv",
  "coin": "BTC",
  "tag": "",
  "url": "https://btc.com/1HPn8Rx2y6nNSfagQBKy27GB99Vbzg89wv"
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_deposit_history (***params*)

Fetch deposit history.

https://binance-docs.github.io/apidocs/spot/en/#deposit-history-supporting-network-user_data

Parameters

- **coin** (*str*) – optional

- **startTime** (*long*) – optional
- **endTime** (*long*) – optional
- **offset** (*long*) – optional - default:0
- **limit** (*long*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
[
  {
    "amount": "0.00999800",
    "coin": "PAXG",
    "network": "ETH",
    "status": 1,
    "address": "0x788cabe9236ce061e5a892e1a59395a81fc8d62c",
    "addressTag": "",
    "txId":
    ↪ "0xaad4654a3234aa6118af9b4b335f5ae81c360b2394721c019b5d1e75328b09f3",
    "insertTime": 1599621997000,
    "transferType": 0,
    "confirmTimes": "12/12"
  },
  {
    "amount": "0.50000000",
    "coin": "IOTA",
    "network": "IOTA",
    "status": 1,
    "address":
    ↪ "SIZ9VLMHWATXKV99LH99CIGFJFUMLEHGWVZVNNZXRJJVWBPBYWPPBOSDORZ9EQSHCZAMPVAPGFYQAUUV9DROOXJL
    ↪",
    "addressTag": "",
    "txId":
    ↪ "ESBFVQUTPIWQNJSPXFNHNYHSQNTGKRVKPRABQWTAXCDWOAKDKYWPVVG9BGXNVNKTLEJGESAVXIKIZ9999
    ↪",
    "insertTime": 1599620082000,
    "transferType": 0,
    "confirmTimes": "1/1"
  }
]
```

Raises BinanceRequestException, BinanceAPIException

get_dust_log (***params*)

Get log of small amounts exchanged for BNB.

https://binance-docs.github.io/apidocs/spot/en/#dustlog-sapi-user_data

Parameters

- **startTime** (*int*) – optional
- **endTime** (*int*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```

{
  "total": 8, //Total counts of exchange
  "userAssetDribblets": [
    {
      "totalTransferredAmount": "0.00132256", // Total transferred BNB_
      ↪amount for this exchange.
      "totalServiceChargeAmount": "0.00002699", //Total service_
      ↪charge amount for this exchange.
      "transId": 45178372831,
      "userAssetDribbletDetails": [ //Details of this_
      ↪exchange.
        {
          "transId": 4359321,
          "serviceChargeAmount": "0.000009",
          "amount": "0.0009",
          "operateTime": 1615985535000,
          "transferredAmount": "0.000441",
          "fromAsset": "USDT"
        },
        {
          "transId": 4359321,
          "serviceChargeAmount": "0.00001799",
          "amount": "0.0009",
          "operateTime": "2018-05-03 17:07:04",
          "transferredAmount": "0.00088156",
          "fromAsset": "ETH"
        }
      ]
    },
    {
      "operateTime":1616203180000,
      "totalTransferredAmount": "0.00058795",
      "totalServiceChargeAmount": "0.000012",
      "transId": 4357015,
      "userAssetDribbletDetails": [
        {
          "transId": 4357015,
          "serviceChargeAmount": "0.00001"
          "amount": "0.001",
          "operateTime": 1616203180000,
          "transferredAmount": "0.00049",
          "fromAsset": "USDT"
        },
        {
          "transId": 4357015,
          "serviceChargeAmount": "0.000002"
          "amount": "0.0001",
          "operateTime": 1616203180000,
          "transferredAmount": "0.00009795",
          "fromAsset": "ETH"
        }
      ]
    }
  ]
}

```

get_exchange_info() → Dict[KT, VT]

Return rate limits and list of symbols

Returns list - List of product dictionaries

```
{
  "timezone": "UTC",
  "serverTime": 1508631584636,
  "rateLimits": [
    {
      "rateLimitType": "REQUESTS",
      "interval": "MINUTE",
      "limit": 1200
    },
    {
      "rateLimitType": "ORDERS",
      "interval": "SECOND",
      "limit": 10
    },
    {
      "rateLimitType": "ORDERS",
      "interval": "DAY",
      "limit": 100000
    }
  ],
  "exchangeFilters": [],
  "symbols": [
    {
      "symbol": "ETHBTC",
      "status": "TRADING",
      "baseAsset": "ETH",
      "baseAssetPrecision": 8,
      "quoteAsset": "BTC",
      "quotePrecision": 8,
      "orderTypes": ["LIMIT", "MARKET"],
      "icebergAllowed": false,
      "filters": [
        {
          "filterType": "PRICE_FILTER",
          "minPrice": "0.00000100",
          "maxPrice": "100000.00000000",
          "tickSize": "0.00000100"
        },
        {
          "filterType": "LOT_SIZE",
          "minQty": "0.00100000",
          "maxQty": "100000.00000000",
          "stepSize": "0.00100000"
        },
        {
          "filterType": "MIN_NOTIONAL",
          "minNotional": "0.00100000"
        }
      ]
    }
  ]
}
```

Raises BinanceRequestException, BinanceAPIException

get_fiat_deposit_withdraw_history (**params)
Get Fiat Deposit/Withdraw History

https://binance-docs.github.io/apidocs/spot/en/#get-fiat-deposit-withdraw-history-user_data

Parameters

- **transactionType** (*str*) – required - 0-deposit,1-withdraw
- **beginTime** (*int*) – optional
- **endTime** (*int*) – optional
- **page** (*int*) – optional - default 1
- **rows** (*int*) – optional - default 100, max 500
- **recvWindow** (*int*) – optional

get_fiat_payments_history (**params)

Get Fiat Payments History

https://binance-docs.github.io/apidocs/spot/en/#get-fiat-payments-history-user_data

Parameters

- **transactionType** (*str*) – required - 0-buy,1-sell
- **beginTime** (*int*) – optional
- **endTime** (*int*) – optional
- **page** (*int*) – optional - default 1
- **rows** (*int*) – optional - default 100, max 500
- **recvWindow** (*int*) – optional

get_fixed_activity_project_list (**params)

Get Fixed and Activity Project List

https://binance-docs.github.io/apidocs/spot/en/#get-fixed-and-activity-project-list-user_data

Parameters

- **asset** (*str*) – optional
- **type** (*str*) – required - “ACTIVITY”, “CUSTOMIZED_FIXED”
- **status** (*str*) – optional - “ALL”, “SUBSCRIBABLE”, “UNSUBSCRIBABLE”; default “ALL”
- **sortBy** (*str*) – optional - “START_TIME”, “LOT_SIZE”, “INTEREST_RATE”, “DURATION”; default “START_TIME”
- **current** (*int*) – optional - Currently querying page. Start from 1. Default:1
- **size** (*int*) – optional - Default:10, Max:100
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
[
  {
    "asset": "USDT",
    "displayPriority": 1,
    "duration": 90,
    "interestPerLot": "1.35810000",
    "interestRate": "0.05510000",
```

(continues on next page)

(continued from previous page)

```

    "lotSize": "100.00000000",
    "lotsLowLimit": 1,
    "lotsPurchased": 74155,
    "lotsUpLimit": 80000,
    "maxLotsPerUser": 2000,
    "needKyc": False,
    "projectId": "CUSDT90DAYSS001",
    "projectName": "USDT",
    "status": "PURCHASING",
    "type": "CUSTOMIZED_FIXED",
    "withAreaLimitation": False
  }
]

```

Raises `BinanceRequestException`, `BinanceAPIException`

get_historical_klines (*symbol*, *interval*, *start_str*, *end_str=None*, *limit=500*, *klines_type: binance.enums.HistoricalKlinesType = <HistoricalKlinesType.SPOT: 1>*)

Get Historical Klines from Binance

Parameters

- **symbol** (*str*) – Name of symbol pair e.g BNBBTC
- **interval** (*str*) – Binance Kline interval
- **start_str** (*str/int*) – Start date string in UTC format or timestamp in milliseconds
- **end_str** (*str/int*) – optional - end date string in UTC format or timestamp in milliseconds (default will fetch everything up to now)
- **limit** (*int*) – Default 500; max 1000.
- **klines_type** (*HistoricalKlinesType*) – Historical klines type: SPOT or FUTURES

Returns list of OHLCV values

get_historical_klines_generator (*symbol*, *interval*, *start_str*, *end_str=None*, *klines_type: binance.enums.HistoricalKlinesType = <HistoricalKlinesType.SPOT: 1>*)

Get Historical Klines generator from Binance

Parameters

- **symbol** (*str*) – Name of symbol pair e.g BNBBTC
- **interval** (*str*) – Binance Kline interval
- **start_str** (*str/int*) – Start date string in UTC format or timestamp in milliseconds
- **end_str** (*str/int*) – optional - end date string in UTC format or timestamp in milliseconds (default will fetch everything up to now)
- **klines_type** (*HistoricalKlinesType*) – Historical klines type: SPOT or FUTURES

Returns generator of OHLCV values

`get_historical_trades (**params)` → Dict[KT, VT]

Get older trades.

<https://binance-docs.github.io/apidocs/spot/en/#old-trade-lookup>

Parameters

- **symbol** (*str*) – required
- **limit** (*int*) – Default 500; max 1000.
- **fromId** (*str*) – TradeId to fetch from. Default gets most recent trades.

Returns API response

```
[
  {
    "id": 28457,
    "price": "4.00000100",
    "qty": "12.00000000",
    "time": 1499865549590,
    "isBuyerMaker": true,
    "isBestMatch": true
  }
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

`get_isolated_margin_account (**params)`

Query isolated margin account details

https://binance-docs.github.io/apidocs/spot/en/#query-isolated-margin-account-info-user_data

Parameters **symbols** – optional up to 5 margin pairs as a comma separated string

```
account_info = client.get_isolated_margin_account ()
account_info = client.get_isolated_margin_account (symbols="BTCUSDT,ETHUSDT")
```

Returns API response

```
If "symbols" is not sent:

{
  "assets": [
    {
      "baseAsset":
        {
          "asset": "BTC",
          "borrowEnabled": true,
          "borrowed": "0.00000000",
          "free": "0.00000000",
          "interest": "0.00000000",
          "locked": "0.00000000",
          "netAsset": "0.00000000",
          "netAssetOfBtc": "0.00000000",
          "repayEnabled": true,
          "totalAsset": "0.00000000"
        },
      "quoteAsset":
```

(continues on next page)

(continued from previous page)

```

        {
            "asset": "USDT",
            "borrowEnabled": true,
            "borrowed": "0.00000000",
            "free": "0.00000000",
            "interest": "0.00000000",
            "locked": "0.00000000",
            "netAsset": "0.00000000",
            "netAssetOfBtc": "0.00000000",
            "repayEnabled": true,
            "totalAsset": "0.00000000"
        },
        "symbol": "BTCUSDT"
        "isolatedCreated": true,
        "marginLevel": "0.00000000",
        "marginLevelStatus": "EXCESSIVE", // "EXCESSIVE", "NORMAL",
        ↪ "MARGIN_CALL", "PRE_LIQUIDATION", "FORCE_LIQUIDATION"
        "marginRatio": "0.00000000",
        "indexPrice": "10000.00000000"
        "liquidatePrice": "1000.00000000",
        "liquidateRate": "1.00000000"
        "tradeEnabled": true
    }
],
"totalAssetOfBtc": "0.00000000",
"totalLiabilityOfBtc": "0.00000000",
"totalNetAssetOfBtc": "0.00000000"
}

```

If "symbols" is sent:

```

{
  "assets": [
    {
      "baseAsset":
        {
          "asset": "BTC",
          "borrowEnabled": true,
          "borrowed": "0.00000000",
          "free": "0.00000000",
          "interest": "0.00000000",
          "locked": "0.00000000",
          "netAsset": "0.00000000",
          "netAssetOfBtc": "0.00000000",
          "repayEnabled": true,
          "totalAsset": "0.00000000"
        },
      "quoteAsset":
        {
          "asset": "USDT",
          "borrowEnabled": true,
          "borrowed": "0.00000000",
          "free": "0.00000000",
          "interest": "0.00000000",
          "locked": "0.00000000",
          "netAsset": "0.00000000",
          "netAssetOfBtc": "0.00000000",

```

(continues on next page)

(continued from previous page)

```

        "repayEnabled": true,
        "totalAsset": "0.00000000"
    },
    "symbol": "BTCUSDT"
    "isolatedCreated": true,
    "marginLevel": "0.00000000",
    "marginLevelStatus": "EXCESSIVE", // "EXCESSIVE", "NORMAL",
    ↪ "MARGIN_CALL", "PRE_LIQUIDATION", "FORCE_LIQUIDATION"
    "marginRatio": "0.00000000",
    "indexPrice": "10000.00000000"
    "liquidatePrice": "1000.00000000",
    "liquidateRate": "1.00000000"
    "tradeEnabled": true
    }
    ]
}

```

get_isolated_margin_symbol (**params)

Query isolated margin symbol info

https://binance-docs.github.io/apidocs/spot/en/#query-isolated-margin-symbol-user_data**Parameters** **symbol** (*str*) – name of the symbol pair

```
pair_details = client.get_isolated_margin_symbol(symbol='BTCUSDT')
```

Returns API response

```

{
  "symbol": "BTCUSDT",
  "base": "BTC",
  "quote": "USDT",
  "isMarginTrade": true,
  "isBuyAllowed": true,
  "isSellAllowed": true
}

```

Raises `BinanceRequestException`, `BinanceAPIException`**get_klines** (**params) → Dict[KT, VT]

Kline/candlestick bars for a symbol. Klines are uniquely identified by their open time.

<https://binance-docs.github.io/apidocs/spot/en/#kline-candlestick-data>**Parameters**

- **symbol** (*str*) – required
- **interval** (*str*) –
-
- **limit** (*int*) –
- Default 500; max 1000.
- **startTime** (*int*) –
- **endTime** (*int*) –

Returns API response

```
[
  [
    1499040000000,      # Open time
    "0.01634790",      # Open
    "0.80000000",      # High
    "0.01575800",      # Low
    "0.01577100",      # Close
    "148976.11427815", # Volume
    1499644799999,      # Close time
    "2434.19055334",   # Quote asset volume
    308,                # Number of trades
    "1756.87402397",   # Taker buy base asset volume
    "28.46694368",     # Taker buy quote asset volume
    "17928899.62484339" # Can be ignored
  ]
]
```

Raises BinanceRequestException, BinanceAPIException**get_lending_account** (**params)

Get Lending Account Details

https://binance-docs.github.io/apidocs/spot/en/#lending-account-user_data**get_lending_daily_quota_left** (**params)

Get Left Daily Purchase Quota of Flexible Product.

https://binance-docs.github.io/apidocs/spot/en/#get-left-daily-purchase-quota-of-flexible-product-user_data**get_lending_daily_redemption_quota** (**params)

Get Left Daily Redemption Quota of Flexible Product

https://binance-docs.github.io/apidocs/spot/en/#get-left-daily-redemption-quota-of-flexible-product-user_data**get_lending_interest_history** (**params)

Get Lending Interest History

https://binance-docs.github.io/apidocs/spot/en/#get-interest-history-user_data-2**get_lending_position** (**params)

Get Flexible Product Position

https://binance-docs.github.io/apidocs/spot/en/#get-flexible-product-position-user_data**get_lending_product_list** (**params)

Get Lending Product List

https://binance-docs.github.io/apidocs/spot/en/#get-flexible-product-list-user_data**get_lending_purchase_history** (**params)

Get Lending Purchase History

https://binance-docs.github.io/apidocs/spot/en/#get-purchase-record-user_data**get_lending_redemption_history** (**params)

Get Lending Redemption History

https://binance-docs.github.io/apidocs/spot/en/#get-redemption-record-user_data

get_margin_account (**params)

Query cross-margin account details

https://binance-docs.github.io/apidocs/spot/en/#query-cross-margin-account-details-user_data

Returns API response

```
{
  "borrowEnabled": true,
  "marginLevel": "11.64405625",
  "totalAssetOfBtc": "6.82728457",
  "totalLiabilityOfBtc": "0.58633215",
  "totalNetAssetOfBtc": "6.24095242",
  "tradeEnabled": true,
  "transferEnabled": true,
  "userAssets": [
    {
      "asset": "BTC",
      "borrowed": "0.00000000",
      "free": "0.00499500",
      "interest": "0.00000000",
      "locked": "0.00000000",
      "netAsset": "0.00499500"
    },
    {
      "asset": "BNB",
      "borrowed": "201.66666672",
      "free": "2346.50000000",
      "interest": "0.00000000",
      "locked": "0.00000000",
      "netAsset": "2144.83333328"
    },
    {
      "asset": "ETH",
      "borrowed": "0.00000000",
      "free": "0.00000000",
      "interest": "0.00000000",
      "locked": "0.00000000",
      "netAsset": "0.00000000"
    },
    {
      "asset": "USDT",
      "borrowed": "0.00000000",
      "free": "0.00000000",
      "interest": "0.00000000",
      "locked": "0.00000000",
      "netAsset": "0.00000000"
    }
  ]
}
```

Raises BinanceRequestException, BinanceAPIException

get_margin_all_assets (**params)

Get All Margin Assets (MARKET_DATA)

https://binance-docs.github.io/apidocs/spot/en/#get-all-margin-assets-market_data

```
margin_assets = client.get_margin_all_assets()
```

Returns API response

```
[
  {
    "assetFullName": "USD coin",
    "assetName": "USDC",
    "isBorrowable": true,
    "isMortgageable": true,
    "userMinBorrow": "0.00000000",
    "userMinRepay": "0.00000000"
  },
  {
    "assetFullName": "BNB-coin",
    "assetName": "BNB",
    "isBorrowable": true,
    "isMortgageable": true,
    "userMinBorrow": "1.00000000",
    "userMinRepay": "0.00000000"
  }
]
```

Raises BinanceRequestException, BinanceAPIException

`get_margin_all_pairs` (***params*)

Get All Cross Margin Pairs (MARKET_DATA)

https://binance-docs.github.io/apidocs/spot/en/#get-all-cross-margin-pairs-market_data

```
margin_pairs = client.get_margin_all_pairs()
```

Returns API response

```
[
  {
    "base": "BNB",
    "id": 351637150141315861,
    "isBuyAllowed": true,
    "isMarginTrade": true,
    "isSellAllowed": true,
    "quote": "BTC",
    "symbol": "BNBBTC"
  },
  {
    "base": "TRX",
    "id": 351637923235429141,
    "isBuyAllowed": true,
    "isMarginTrade": true,
    "isSellAllowed": true,
    "quote": "BTC",
    "symbol": "TRXBTC"
  }
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_margin_asset (**params)

Query cross-margin asset

https://binance-docs.github.io/apidocs/spot/en/#query-margin-asset-market_data

Parameters `asset` (*str*) – name of the asset

```
asset_details = client.get_margin_asset(asset='BNB')
```

Returns API response

```
{
  "assetFullName": "Binance Coin",
  "assetName": "BNB",
  "isBorrowable": false,
  "isMortgageable": true,
  "userMinBorrow": "0.00000000",
  "userMinRepay": "0.00000000"
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_margin_force_liquidation_rec (**params)

Get Force Liquidation Record (USER_DATA)

https://binance-docs.github.io/apidocs/spot/en/#get-force-liquidation-record-user_data

Parameters

- **startTime** (*str*) –
- **endTime** (*str*) –
- **isolatedSymbol** (*str*) – isolated symbol (if querying isolated margin)
- **current** (*str*) – Currently querying page. Start from 1. Default:1
- **size** (*int*) – Default:10 Max:100
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns

API response

```
{
  "rows": [
    {
      "avgPrice": "0.00388359",
      "executedQty": "31.39000000",
      "orderId": 180015097,
      "price": "0.00388110",
      "qty": "31.39000000",
      "side": "SELL",
      "symbol": "BNBBTC",
      "timeInForce": "GTC",
      "isIsolated": true,
      "updatedTime": 1558941374745
    }
  ],
  "total": 1
}
```


get_margin_interest_history (**params)

Get Interest History (USER_DATA)

https://binance-docs.github.io/apidocs/spot/en/#get-interest-history-user_data

Parameters

- **asset** (*str*) –
- **isolatedSymbol** (*str*) – isolated symbol (if querying isolated margin)
- **startTime** (*str*) –
- **endTime** (*str*) –
- **current** (*str*) – Currently querying page. Start from 1. Default:1
- **size** (*int*) – Default:10 Max:100
- **archived** (*bool*) – Default: false. Set to true for archived data from 6 months ago
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns

API response

```
{
  "rows":[
    { "isolatedSymbol": "BNBUSDT", // isolated symbol, will not be returned
      for crossed margin "asset": "BNB", "interest": "0.02414667", "interestAc-
      curredTime": 1566813600000, "interestRate": "0.01600000", "principal":
      "36.22000000", "type": "ON_BORROW"
    }
  ], "total": 1
}
```

get_margin_loan_details (**params)

Query loan record

txId or startTime must be sent. txId takes precedence.

https://binance-docs.github.io/apidocs/spot/en/#query-loan-record-user_data

Parameters

- **asset** (*str*) – required
- **isolatedSymbol** (*str*) – isolated symbol (if querying isolated margin)
- **txId** (*str*) – the tranId in of the created loan
- **startTime** (*str*) – earliest timestamp to filter transactions
- **endTime** (*str*) – Used to uniquely identify this cancel. Automatically generated by default.
- **current** (*str*) – Currently querying page. Start from 1. Default:1
- **size** (*int*) – Default:10 Max:100
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns

API response

```
{
  "rows": [
    { "asset": "BNB", "principal": "0.84624403", "timestamp": 1555056425000,
      //one of PENDING (pending to execution), CONFIRMED (successfully loaned),
      FAILED (execution failed, nothing happened to your account); "status": "CONFIRMED"
    }
  ], "total": 1
}
```

Raises BinanceRequestException, BinanceAPIException**get_margin_oco_order** (**params)

Retrieves a specific OCO based on provided optional parameters

https://binance-docs.github.io/apidocs/spot/en/#query-margin-account-39-s-oco-user_data**Parameters**

- **isIsolated** – for isolated margin or not, “TRUE”, “FALSE” default “FALSE”
- **symbol** (*str*) – mandatory for isolated margin, not supported for cross margin
- **orderListId** (*int*) – Either orderListId or listClientOrderId must be provided
- **listClientOrderId** (*str*) – Either orderListId or listClientOrderId must be provided
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns

API response

```
{ "orderListId": 27, "contingencyType": "OCO", "listStatusType":
  "EXEC_STARTED", "listOrderStatus": "EXECUTING", "listClientOrderId":
  "h2USkA5YQpaXHPirkd96xE", "transactionTime": 1565245656253, "symbol":
  "LTCBTC", "isIsolated": false, // if isolated margin "orders": [
    { "symbol": "LTCBTC", "orderId": 4, "clientOrderId":
      "qD1gy3kc3Gx0rihm9Y3xwS"
    }, {
      "symbol": "LTCBTC", "orderId": 5, "clientOrderId":
      "ARzZ9I00CPM8i3NhmU9Ega"
    }
  ]
}
```

get_margin_order (**params)

Query margin accounts order

Either orderId or origClientOrderId must be sent.

For some historical orders `cummulativeQuoteQty` will be < 0 , meaning the data is not available at this time.

https://binance-docs.github.io/apidocs/spot/en/#query-margin-account-39-s-order-user_data

Parameters

- **symbol** (*str*) – required
- **isIsolated** (*str*) – set to ‘TRUE’ for isolated margin (default ‘FALSE’)
- **orderId** (*str*) –
- **origClientId** (*str*) –
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns

API response

```
{ "clientId": "ZwfQzuDIGpceVhKW5DvCmO", "cummulativeQuoteQty":
  "0.00000000", "executedQty": "0.00000000", "icebergQty": "0.00000000",
  "isWorking": true, "orderId": 213205622, "origQty": "0.30000000", "price":
  "0.00493630", "side": "SELL", "status": "NEW", "stopPrice": "0.00000000",
  "symbol": "BNBBTC", "time": 1562133008725, "timeInForce": "GTC", "type":
  "LIMIT", "updateTime": 1562133008725
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_margin_price_index (***params*)

Query margin priceIndex

https://binance-docs.github.io/apidocs/spot/en/#query-margin-priceindex-market_data

Parameters **symbol** (*str*) – name of the symbol pair

```
price_index_details = client.get_margin_price_index(symbol='BTCUSDT')
```

Returns API response

```
{
  "calcTime": 1562046418000,
  "price": "0.00333930",
  "symbol": "BNBBTC"
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_margin_repay_details (***params*)

Query repay record

`txId` or `startTime` must be sent. `txId` takes precedence.

https://binance-docs.github.io/apidocs/spot/en/#query-repay-record-user_data

Parameters

- **asset** (*str*) – required
- **isolatedSymbol** (*str*) – isolated symbol (if querying isolated margin)

- **txId** (*str*) – the tranId in of the created loan
- **startTime** (*str*) –
- **endTime** (*str*) – Used to uniquely identify this cancel. Automatically generated by default.
- **current** (*str*) – Currently querying page. Start from 1. Default:1
- **size** (*int*) – Default:10 Max:100
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns

API response

```
{
  "rows": [
    { //Total amount repaid "amount": "14.00000000", "asset": "BNB", //Interest re-
      paid "interest": "0.01866667", //Principal repaid "principal": "13.98133333",
      //one of PENDING (pending to execution), CONFIRMED (successfully loaned),
      FAILED (execution failed, nothing happened to your account); "status": "CON-
      FIRMED", "timestamp": 1563438204000, "txId": 2970933056
    }
  ], "total": 1
}
```

Raises BinanceRequestException, BinanceAPIException**get_margin_symbol** (***params*)

Query cross-margin symbol info

https://binance-docs.github.io/apidocs/spot/en/#query-cross-margin-pair-market_data**Parameters** **symbol** (*str*) – name of the symbol pair

```
pair_details = client.get_margin_symbol(symbol='BTCUSDT')
```

Returns API response

```
{
  "id":323355778339572400,
  "symbol":"BTCUSDT",
  "base":"BTC",
  "quote":"USDT",
  "isMarginTrade":true,
  "isBuyAllowed":true,
  "isSellAllowed":true
}
```

Raises BinanceRequestException, BinanceAPIException**get_margin_trades** (***params*)

Query margin accounts trades

If fromId is set, it will get orders >= that fromId. Otherwise most recent orders are returned.

https://binance-docs.github.io/apidocs/spot/en/#query-margin-account-39-s-trade-list-user_data

Parameters

- **symbol** (*str*) – required
- **isIsolated** (*str*) – set to ‘TRUE’ for isolated margin (default ‘FALSE’)
- **fromId** (*str*) – optional
- **startTime** (*str*) – optional
- **endTime** (*str*) – optional
- **limit** (*int*) – Default 500; max 1000
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns

API response

```
[
  { "commission": "0.00006000", "commissionAsset": "BTC", "id": 34, "is-
    BestMatch": true, "isBuyer": false, "isMaker": false, "orderId": 39324,
    "price": "0.02000000", "qty": "3.00000000", "symbol": "BNBBTC", "time":
    1561973357171
  }, { "commission": "0.00002950", "commissionAsset": "BTC", "id": 32, "is-
    BestMatch": true, "isBuyer": false, "isMaker": true, "orderId": 39319,
    "price": "0.00590000", "qty": "5.00000000", "symbol": "BNBBTC", "time":
    1561964645345
  }
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_max_margin_loan (***params*)

Query max borrow amount for an asset

https://binance-docs.github.io/apidocs/spot/en/#query-max-borrow-user_data

Parameters

- **asset** (*str*) – required
- **isolatedSymbol** (*str*) – isolated symbol (if querying isolated margin)
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns

API response

```
{ "amount": "1.69248805"
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_max_margin_transfer (***params*)

Query max transfer-out amount

https://binance-docs.github.io/apidocs/spot/en/#query-max-transfer-out-amount-user_data

Parameters

- **asset** (*str*) – required
- **isolatedSymbol** (*str*) – isolated symbol (if querying isolated margin)
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns

API response

```
{ "amount": "3.59498107"
}
```

Raises BinanceRequestException, BinanceAPIException

get_my_trades (***params*)

Get trades for a specific symbol.

https://binance-docs.github.io/apidocs/spot/en/#account-trade-list-user_data

Parameters

- **symbol** (*str*) – required
- **startTime** (*int*) – optional
- **endTime** (*int*) – optional
- **limit** (*int*) – Default 500; max 1000.
- **fromId** (*int*) – TradeId to fetch from. Default gets most recent trades.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
[
  {
    "id": 28457,
    "price": "4.00000100",
    "qty": "12.00000000",
    "commission": "10.10000000",
    "commissionAsset": "BNB",
    "time": 1499865549590,
    "isBuyer": true,
    "isMaker": false,
    "isBestMatch": true
  }
]
```

Raises BinanceRequestException, BinanceAPIException

get_open_margin_oco_orders (***params*)

Retrieves open OCO trades

https://binance-docs.github.io/apidocs/spot/en/#query-margin-account-39-s-open-oco-user_data

Parameters

- **isIsolated** – for isolated margin or not, “TRUE”, “FALSE” default “FALSE”
- **symbol** (*str*) – mandatory for isolated margin, not supported for cross margin
- **fromId** (*int*) – If supplied, neither startTime or endTime can be provided

- **startTime** (*int*) – optional
- **endTime** (*int*) – optional
- **limit** (*int*) – optional Default Value: 500; Max Value: 1000
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns

API response

```
[
  {
    "orderListId": 29, "contingencyType": "OCO", "listStatusType":
    "EXEC_STARTED", "listOrderStatus": "EXECUTING", "listClientOrderId":
    "amEEAXryFzFwYF1FeRpUoZ", "transactionTime": 1565245913483, "symbol":
    "LTCBTC", "isIsolated": true, // if isolated margin "orders": [
      { "symbol": "LTCBTC", "orderId": 4, "clientOrderId":
        "oD7aesZqjEGlZrbtRpy5zB"
      }, {
        "symbol": "LTCBTC", "orderId": 5, "clientOrderId":
        "Jr1h6xirOxgeJOUuYQS7V3"
      }
    ]
  }, {
    "orderListId": 28, "contingencyType": "OCO", "listStatusType":
    "EXEC_STARTED", "listOrderStatus": "EXECUTING", "list-
    ClientOrderId": "hG7hFNxJV6cZy3Ze4AUT4d", "transactionTime":
    1565245913407, "symbol": "LTCBTC", "orders": [
      { "symbol": "LTCBTC", "orderId": 2, "clientOrderId":
        "j6lFOfbmFMRjTYA7rRJOLP"
      }, {
        "symbol": "LTCBTC", "orderId": 3, "clientOrderId":
        "z0KCjOdditiLS5ekAFtK81"
      }
    ]
  }
]
```

get_open_margin_orders (**params)

Query margin accounts open orders

If the symbol is not sent, orders for all symbols will be returned in an array (cross-margin only).

If querying isolated margin orders, both the `isIsolated='TRUE'` and `symbol=symbol_name` must be set.

When all symbols are returned, the number of requests counted against the rate limiter is equal to the number of symbols currently trading on the exchange.

https://binance-docs.github.io/apidocs/spot/en/#query-margin-account-39-s-open-order-user_data

Parameters

- **symbol** (*str*) – optional
- **isIsolated** (*str*) – set to ‘TRUE’ for isolated margin (default ‘FALSE’)
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns

API response

```
[
  {
    "clientOrderId": "qhcZw71gAkCCTv0t0k8LUK", "cumulativeQuoteQty":
    "0.00000000", "executedQty": "0.00000000", "icebergQty": "0.00000000",
    "isWorking": true, "orderId": 211842552, "origQty": "0.30000000",
    "price": "0.00475010", "side": "SELL", "status": "NEW", "stopPrice":
    "0.00000000", "symbol": "BNBBTC", "time": 1562040170089, "timeIn-
    Force": "GTC", "type": "LIMIT", "updateTime": 1562040170089
  }
]
```

Raises BinanceRequestException, BinanceAPIException**get_open_orders** (***params*)

Get all open orders on a symbol.

https://binance-docs.github.io/apidocs/spot/en/#current-open-orders-user_data**Parameters**

- **symbol** (*str*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
[
  {
    "symbol": "LTCBTC",
    "orderId": 1,
    "clientOrderId": "myOrder1",
    "price": "0.1",
    "origQty": "1.0",
    "executedQty": "0.0",
    "status": "NEW",
    "timeInForce": "GTC",
    "type": "LIMIT",
    "side": "BUY",
    "stopPrice": "0.0",
    "icebergQty": "0.0",
    "time": 1499827319559
  }
]
```

Raises BinanceRequestException, BinanceAPIException**get_order** (***params*)

Check an order’s status. Either orderId or origClientId must be sent.

https://binance-docs.github.io/apidocs/spot/en/#query-order-user_data**Parameters**

- **symbol** (*str*) – required
- **orderId** (*int*) – The unique order id
- **origClientId** (*str*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "symbol": "LTCBTC",
  "orderId": 1,
  "clientOrderId": "myOrder1",
  "price": "0.1",
  "origQty": "1.0",
  "executedQty": "0.0",
  "status": "NEW",
  "timeInForce": "GTC",
  "type": "LIMIT",
  "side": "BUY",
  "stopPrice": "0.0",
  "icebergQty": "0.0",
  "time": 1499827319559
}
```

Raises BinanceRequestException, BinanceAPIException

get_order_book (***params*) → Dict[KT, VT]

Get the Order Book for the market

<https://binance-docs.github.io/apidocs/spot/en/#order-book>

Parameters

- **symbol** (*str*) – required
- **limit** (*int*) – Default 100; max 1000

Returns API response

```
{
  "lastUpdateId": 1027024,
  "bids": [
    [
      "4.00000000",      # PRICE
      "431.00000000",  # QTY
      []                # Can be ignored
    ]
  ],
  "asks": [
    [
      "4.00000200",
      "12.00000000",
      []
    ]
  ]
}
```

Raises BinanceRequestException, BinanceAPIException

get_orderbook_ticker (**params)

Latest price for a symbol or symbols.

<https://binance-docs.github.io/apidocs/spot/en/#symbol-order-book-ticker>

Parameters **symbol** (*str*) –

Returns API response

```
{
  "symbol": "LTCBTC",
  "bidPrice": "4.00000000",
  "bidQty": "431.00000000",
  "askPrice": "4.00000200",
  "askQty": "9.00000000"
}
```

OR

```
[
  {
    "symbol": "LTCBTC",
    "bidPrice": "4.00000000",
    "bidQty": "431.00000000",
    "askPrice": "4.00000200",
    "askQty": "9.00000000"
  },
  {
    "symbol": "ETHBTC",
    "bidPrice": "0.07946700",
    "bidQty": "9.00000000",
    "askPrice": "100000.00000000",
    "askQty": "1000.00000000"
  }
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_orderbook_tickers () → Dict[KT, VT]

Best price/qty on the order book for all symbols.

<https://binance-docs.github.io/apidocs/spot/en/#symbol-order-book-ticker>

Parameters **symbol** (*str*) – optional

Returns List of order book market entries

```
[
  {
    "symbol": "LTCBTC",
    "bidPrice": "4.00000000",
    "bidQty": "431.00000000",
    "askPrice": "4.00000200",
    "askQty": "9.00000000"
  },
  {
    "symbol": "ETHBTC",
    "bidPrice": "0.07946700",
    "bidQty": "9.00000000",
    "askPrice": "100000.00000000",
    "askQty": "1000.00000000"
  }
]
```

(continues on next page)

(continued from previous page)

```

    "askPrice": "100000.00000000",
    "askQty": "1000.00000000"
  }
]

```

Raises BinanceRequestException, BinanceAPIException

get_products () → Dict[KT, VT]

Return list of products currently listed on Binance

Use `get_exchange_info()` call instead

Returns list - List of product dictionaries

Raises BinanceRequestException, BinanceAPIException

get_recent_trades (**params) → Dict[KT, VT]

Get recent trades (up to last 500).

<https://binance-docs.github.io/apidocs/spot/en/#recent-trades-list>

Parameters

- **symbol** (*str*) – required
- **limit** (*int*) – Default 500; max 1000.

Returns API response

```

[
  {
    "id": 28457,
    "price": "4.00000100",
    "qty": "12.00000000",
    "time": 1499865549590,
    "isBuyerMaker": true,
    "isBestMatch": true
  }
]

```

Raises BinanceRequestException, BinanceAPIException

get_server_time () → Dict[KT, VT]

Test connectivity to the Rest API and get the current server time.

<https://binance-docs.github.io/apidocs/spot/en/#check-server-time>

Returns Current server time

```

{
  "serverTime": 1499827319559
}

```

Raises BinanceRequestException, BinanceAPIException

get_sub_account_assets (**params)

Fetch sub-account assets

<https://binance-docs.github.io/apidocs/spot/en/#query-sub-account-assets-sapi-for-master-account>

Parameters

- **email** (*str*) – required
- **recvWindow** (*int*) – optional

Returns API response

```
{
  "balances": [
    {
      "asset": "ADA",
      "free": 10000,
      "locked": 0
    },
    {
      "asset": "BNB",
      "free": 10003,
      "locked": 0
    },
    {
      "asset": "BTC",
      "free": 11467.6399,
      "locked": 0
    },
    {
      "asset": "ETH",
      "free": 10004.995,
      "locked": 0
    },
    {
      "asset": "USDT",
      "free": 11652.14213,
      "locked": 0
    }
  ]
}
```

Raises `BinanceRequestException`, `BinanceAPIException`**get_sub_account_futures_transfer_history** (***params*)

Query Sub-account Futures Transfer History.

<https://binance-docs.github.io/apidocs/spot/en/#query-sub-account-futures-asset-transfer-history-for-master-account>**Parameters**

- **email** (*str*) – required
- **futuresType** (*int*) – required
- **startTime** (*int*) – optional
- **endTime** (*int*) – optional
- **page** (*int*) – optional
- **limit** (*int*) – optional
- **recvWindow** (*int*) – optional

Returns API response

```
{
  "success":true,
  "futuresType": 2,
  "transfers":[
    {
      "from":"aaa@test.com",
      "to":"bbb@test.com",
      "asset":"BTC",
      "qty":"1",
      "time":1544433328000
    },
    {
      "from":"bbb@test.com",
      "to":"ccc@test.com",
      "asset":"ETH",
      "qty":"2",
      "time":1544433328000
    }
  ]
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_sub_account_list (***params*)

Query Sub-account List.

<https://binance-docs.github.io/apidocs/spot/en/#query-sub-account-list-sapi-for-master-account>

Parameters

- **email** (*str*) – optional - Sub-account email
- **isFreeze** (*str*) – optional
- **page** (*int*) – optional - Default value: 1
- **limit** (*int*) – optional - Default value: 1, Max value: 200
- **recvWindow** (*int*) – optional

Returns API response

```
{
  "subAccounts": [
    {
      "email": "testsub@gmail.com",
      "isFreeze": false,
      "createTime": 1544433328000
    },
    {
      "email": "virtual@oxebmvfonoemail.com",
      "isFreeze": false,
      "createTime": 1544433328000
    }
  ]
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_sub_account_transfer_history (**params)

Query Sub-account Transfer History.

<https://binance-docs.github.io/apidocs/spot/en/#query-sub-account-spot-asset-transfer-history-sapi-for-master-account>

Parameters

- **fromEmail** (*str*) – optional
- **toEmail** (*str*) – optional
- **startTime** (*int*) – optional
- **endTime** (*int*) – optional
- **page** (*int*) – optional - Default value: 1
- **limit** (*int*) – optional - Default value: 500
- **recvWindow** (*int*) – optional

Returns API response

```
[
  {
    "from": "aaa@test.com",
    "to": "bbb@test.com",
    "asset": "BTC",
    "qty": "10",
    "status": "SUCCESS",
    "tranId": 6489943656,
    "time": 1544433328000
  },
  {
    "from": "bbb@test.com",
    "to": "ccc@test.com",
    "asset": "ETH",
    "qty": "2",
    "status": "SUCCESS",
    "tranId": 6489938713,
    "time": 1544433328000
  }
]
```

Raises BinanceRequestException, BinanceAPIException

get_subaccount_deposit_address (**params)

Get Sub-account Deposit Address (For Master Account)

<https://binance-docs.github.io/apidocs/spot/en/#get-sub-account-deposit-address-for-master-account>

Parameters

- **email** (*str*) – required - Sub account email
- **coin** (*str*) – required
- **network** (*str*) – optional
- **recvWindow** (*int*) – optional

Returns API response

```
{
    "address": "TDunhSa7jkTNUKrusUTU1MUHtqXoBPKETV",
    "coin": "USDT",
    "tag": "",
    "url": "https://tronscan.org/#/address/TDunhSa7jkTNUKrusUTU1MUHtqXoBPKETV
↪"
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_subaccount_deposit_history (**params)

Get Sub-account Deposit History (For Master Account)

<https://binance-docs.github.io/apidocs/spot/en/#get-sub-account-deposit-address-for-master-account>

Parameters

- **email** (*str*) – required - Sub account email
- **coin** (*str*) – optional
- **status** (*int*) – optional - (0:pending,6: credited but cannot withdraw, 1:success)
- **startTime** (*int*) – optional
- **endTime** (*int*) – optional
- **limit** (*int*) – optional
- **offset** (*int*) – optional - default:0
- **recvWindow** (*int*) – optional

Returns API response

```
[
  {
    "amount": "0.00999800",
    "coin": "PAXG",
    "network": "ETH",
    "status": 1,
    "address": "0x788cabe9236ce061e5a892e1a59395a81fc8d62c",
    "addressTag": "",
    "txId":
↪ "0xaad4654a3234aa6118af9b4b335f5ae81c360b2394721c019b5d1e75328b09f3",
    "insertTime": 1599621997000,
    "transferType": 0,
    "confirmTimes": "12/12"
  },
  {
    "amount": "0.50000000",
    "coin": "IOTA",
    "network": "IOTA",
    "status": 1,
    "address":
↪ "SIZ9VLMHWATXKV99LH99CIGFJFUMLEHGWVZVNNZXRJJVWBPHYWPPBOSDORZ9EQSHCZAMPVAPGFYQAUUV9DROOXJL
↪",
    "addressTag": "",
    "txId":
↪ "ESBFVQUTPIWQNJSPXFNHNYHSQNTGKRVKPRABQWTAXCDWOAKDKYWPTVG9BGXNVNKTLEJGESAVXIKIZ9999
↪",

```

(continues on next page)

(continued from previous page)

```

        "insertTime":1599620082000,
        "transferType":0,
        "confirmTimes":"1/1"
    }
]

```

Raises `BinanceRequestException`, `BinanceAPIException`

get_subaccount_futures_details (**params)

Get Detail on Sub-account's Futures Account (For Master Account)

<https://binance-docs.github.io/apidocs/spot/en/#get-detail-on-sub-account-39-s-futures-account-for-master-account>

Parameters

- **email** (*str*) – required - Sub account email
- **recvWindow** (*int*) – optional

Returns API response

```

{
  "email": "abc@test.com",
  "asset": "USDT",
  "assets": [
    {
      "asset": "USDT",
      "initialMargin": "0.00000000",
      "maintenanceMargin": "0.00000000",
      "marginBalance": "0.88308000",
      "maxWithdrawAmount": "0.88308000",
      "openOrderInitialMargin": "0.00000000",
      "positionInitialMargin": "0.00000000",
      "unrealizedProfit": "0.00000000",
      "walletBalance": "0.88308000"
    }
  ],
  "canDeposit": true,
  "canTrade": true,
  "canWithdraw": true,
  "feeTier": 2,
  "maxWithdrawAmount": "0.88308000",
  "totalInitialMargin": "0.00000000",
  "totalMaintenanceMargin": "0.00000000",
  "totalMarginBalance": "0.88308000",
  "totalOpenOrderInitialMargin": "0.00000000",
  "totalPositionInitialMargin": "0.00000000",
  "totalUnrealizedProfit": "0.00000000",
  "totalWalletBalance": "0.88308000",
  "updateTime": 1576756674610
}

```

Raises `BinanceRequestException`, `BinanceAPIException`

get_subaccount_futures_margin_status (**params)

Get Sub-account's Status on Margin/Futures (For Master Account)

<https://binance-docs.github.io/apidocs/spot/en/#get-sub-account-39-s-status-on-margin-futures-for-master-account>

Parameters

- **email** (*str*) – optional - Sub account email
- **recvWindow** (*int*) – optional

Returns API response

```
[
  {
    "email": "123@test.com",           // user email
    "isSubUserEnabled": true,         // true or false
    "isUserActive": true,            // true or false
    "insertTime": 1570791523523      // sub account create time
    "isMarginEnabled": true,         // true or false for margin
    "isFutureEnabled": true         // true or false for futures.
    "mobile": 1570791523523         // user mobile number
  }
]
```

Raises BinanceRequestException, BinanceAPIException**get_subaccount_futures_positionrisk** (**params)

Get Futures Position-Risk of Sub-account (For Master Account)

<https://binance-docs.github.io/apidocs/spot/en/#get-futures-position-risk-of-sub-account-for-master-account>**Parameters**

- **email** (*str*) – required - Sub account email
- **recvWindow** (*int*) – optional

Returns API response

```
[
  {
    "entryPrice": "9975.12000",
    "leverage": "50",                // current initial leverage
    "maxNotional": "1000000",       // notional value limit of current_
    ↪initial leverage
    "liquidationPrice": "7963.54",
    "markPrice": "9973.50770517",
    "positionAmount": "0.010",
    "symbol": "BTCUSDT",
    "unrealizedProfit": "-0.01612295"
  }
]
```

Raises BinanceRequestException, BinanceAPIException**get_subaccount_futures_summary** (**params)

Get Summary of Sub-account's Futures Account (For Master Account)

<https://binance-docs.github.io/apidocs/spot/en/#get-summary-of-sub-account-39-s-futures-account-for-master-account>**Parameters** **recvWindow** (*int*) – optional**Returns** API response

```

{
  "totalInitialMargin": "9.83137400",
  "totalMaintenanceMargin": "0.41568700",
  "totalMarginBalance": "23.03235621",
  "totalOpenOrderInitialMargin": "9.00000000",
  "totalPositionInitialMargin": "0.83137400",
  "totalUnrealizedProfit": "0.03219710",
  "totalWalletBalance": "22.15879444",
  "asset": "USDT",
  "subAccountList": [
    {
      "email": "123@test.com",
      "totalInitialMargin": "9.00000000",
      "totalMaintenanceMargin": "0.00000000",
      "totalMarginBalance": "22.12659734",
      "totalOpenOrderInitialMargin": "9.00000000",
      "totalPositionInitialMargin": "0.00000000",
      "totalUnrealizedProfit": "0.00000000",
      "totalWalletBalance": "22.12659734",
      "asset": "USDT"
    },
    {
      "email": "345@test.com",
      "totalInitialMargin": "0.83137400",
      "totalMaintenanceMargin": "0.41568700",
      "totalMarginBalance": "0.90575887",
      "totalOpenOrderInitialMargin": "0.00000000",
      "totalPositionInitialMargin": "0.83137400",
      "totalUnrealizedProfit": "0.03219710",
      "totalWalletBalance": "0.87356177",
      "asset": "USDT"
    }
  ]
}

```

Raises `BinanceRequestException`, `BinanceAPIException`

get_subaccount_margin_details (**params)

Get Detail on Sub-account's Margin Account (For Master Account)

<https://binance-docs.github.io/apidocs/spot/en/#get-detail-on-sub-account-39-s-margin-account-for-master-account>

Parameters

- **email** (*str*) – required - Sub account email
- **recvWindow** (*int*) – optional

Returns API response

```

{
  "email": "123@test.com",
  "marginLevel": "11.64405625",
  "totalAssetOfBtc": "6.82728457",
  "totalLiabilityOfBtc": "0.58633215",
  "totalNetAssetOfBtc": "6.24095242",
  "marginTradeCoeffVo":
  {

```

(continues on next page)

(continued from previous page)

```

        "forceLiquidationBar": "1.10000000", // Liquidation margin_
↪ratio
        "marginCallBar": "1.50000000",      // Margin call margin_
↪ratio
        "normalBar": "2.00000000"          // Initial margin ratio
    },
    "marginUserAssetVoList": [
        {
            "asset": "BTC",
            "borrowed": "0.00000000",
            "free": "0.00499500",
            "interest": "0.00000000",
            "locked": "0.00000000",
            "netAsset": "0.00499500"
        },
        {
            "asset": "BNB",
            "borrowed": "201.66666672",
            "free": "2346.50000000",
            "interest": "0.00000000",
            "locked": "0.00000000",
            "netAsset": "2144.83333328"
        },
        {
            "asset": "ETH",
            "borrowed": "0.00000000",
            "free": "0.00000000",
            "interest": "0.00000000",
            "locked": "0.00000000",
            "netAsset": "0.00000000"
        },
        {
            "asset": "USDT",
            "borrowed": "0.00000000",
            "free": "0.00000000",
            "interest": "0.00000000",
            "locked": "0.00000000",
            "netAsset": "0.00000000"
        }
    ]
}

```

Raises `BinanceRequestException`, `BinanceAPIException`

get_subaccount_margin_summary (**params)

Get Summary of Sub-account's Margin Account (For Master Account)

<https://binance-docs.github.io/apidocs/spot/en/#get-summary-of-sub-account-39-s-margin-account-for-master-account>

Parameters `recvWindow` (*int*) – optional

Returns API response

```

{
  "totalAssetOfBtc": "4.33333333",
  "totalLiabilityOfBtc": "2.11111112",
  "totalNetAssetOfBtc": "2.22222221",

```

(continues on next page)

(continued from previous page)

```

"subAccountList": [
  {
    "email": "123@test.com",
    "totalAssetOfBtc": "2.11111111",
    "totalLiabilityOfBtc": "1.11111111",
    "totalNetAssetOfBtc": "1.00000000"
  },
  {
    "email": "345@test.com",
    "totalAssetOfBtc": "2.22222222",
    "totalLiabilityOfBtc": "1.00000001",
    "totalNetAssetOfBtc": "1.22222221"
  }
]
}

```

Raises `BinanceRequestException`, `BinanceAPIException`

get_subaccount_transfer_history (**params)

Sub-account Transfer History (For Sub-account)

<https://binance-docs.github.io/apidocs/spot/en/#transfer-to-master-for-sub-account>

Parameters

- **asset** (*str*) – required - The asset being transferred, e.g., USDT
- **type** (*int*) – optional - 1: transfer in, 2: transfer out
- **startTime** (*int*) – optional
- **endTime** (*int*) – optional
- **limit** (*int*) – optional - Default 500
- **recvWindow** (*int*) – optional

Returns API response

```

[
  {
    "counterParty": "master",
    "email": "master@test.com",
    "type": 1, // 1 for transfer in, 2 for transfer out
    "asset": "BTC",
    "qty": "1",
    "status": "SUCCESS",
    "tranId": 11798835829,
    "time": 1544433325000
  },
  {
    "counterParty": "subAccount",
    "email": "sub2@test.com",
    "type": 2,
    "asset": "ETH",
    "qty": "2",
    "status": "SUCCESS",
    "tranId": 11798829519,
    "time": 1544433326000
  }
]

```

(continues on next page)

(continued from previous page)

```
}
]
```

Raises BinanceRequestException, BinanceAPIException

get_symbol_info (*symbol*) → Optional[Dict[KT, VT]]

Return information about a symbol

Parameters **symbol** (*str*) – required e.g BNBBTC

Returns Dict if found, None if not

```
{
  "symbol": "ETHBTC",
  "status": "TRADING",
  "baseAsset": "ETH",
  "baseAssetPrecision": 8,
  "quoteAsset": "BTC",
  "quotePrecision": 8,
  "orderTypes": ["LIMIT", "MARKET"],
  "icebergAllowed": false,
  "filters": [
    {
      "filterType": "PRICE_FILTER",
      "minPrice": "0.00000100",
      "maxPrice": "100000.00000000",
      "tickSize": "0.00000100"
    }, {
      "filterType": "LOT_SIZE",
      "minQty": "0.00100000",
      "maxQty": "100000.00000000",
      "stepSize": "0.00100000"
    }, {
      "filterType": "MIN_NOTIONAL",
      "minNotional": "0.00100000"
    }
  ]
}
```

Raises BinanceRequestException, BinanceAPIException

get_symbol_ticker (***params*)

Latest price for a symbol or symbols.

<https://binance-docs.github.io/apidocs/spot/en/#symbol-price-ticker>

Parameters **symbol** (*str*) –

Returns API response

```
{
  "symbol": "LTCBTC",
  "price": "4.00000200"
}
```

OR

```
[
  {
    "symbol": "LTCBTC",
    "price": "4.00000200"
  },
  {
    "symbol": "ETHBTC",
    "price": "0.07946600"
  }
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_system_status ()

Get system status detail.

<https://binance-docs.github.io/apidocs/spot/en/#system-status-sapi-system>

Returns API response

```
{
  "status": 0,           # 0: normal system maintenance
  "msg": "normal"       # normal or System maintenance.
}
```

Raises `BinanceAPIException`

get_ticker (**params)

24 hour price change statistics.

<https://binance-docs.github.io/apidocs/spot/en/#24hr-ticker-price-change-statistics>

Parameters `symbol` (*str*) –

Returns API response

```
{
  "priceChange": "-94.99999800",
  "priceChangePercent": "-95.960",
  "weightedAvgPrice": "0.29628482",
  "prevClosePrice": "0.10002000",
  "lastPrice": "4.00000200",
  "bidPrice": "4.00000000",
  "askPrice": "4.00000200",
  "openPrice": "99.00000000",
  "highPrice": "100.00000000",
  "lowPrice": "0.10000000",
  "volume": "8913.30000000",
  "openTime": 1499783499040,
  "closeTime": 1499869899040,
  "fristId": 28385,      # First tradeId
  "lastId": 28460,     # Last tradeId
  "count": 76          # Trade count
}
```

OR

```
[
  {
    "priceChange": "-94.99999800",
    "priceChangePercent": "-95.960",
    "weightedAvgPrice": "0.29628482",
    "prevClosePrice": "0.10002000",
    "lastPrice": "4.00000200",
    "bidPrice": "4.00000000",
    "askPrice": "4.00000200",
    "openPrice": "99.00000000",
    "highPrice": "100.00000000",
    "lowPrice": "0.10000000",
    "volume": "8913.30000000",
    "openTime": 1499783499040,
    "closeTime": 1499869899040,
    "fristId": 28385,    # First tradeId
    "lastId": 28460,   # Last tradeId
    "count": 76        # Trade count
  }
]
```

Raises `BinanceRequestException`, `BinanceAPIException`

get_trade_fee (**params)

Get trade fee.

https://binance-docs.github.io/apidocs/spot/en/#trade-fee-sapi-user_data

Parameters

- **symbol** (*str*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
[
  {
    "symbol": "ADABNB",
    "makerCommission": "0.001",
    "takerCommission": "0.001"
  },
  {
    "symbol": "BNBBTC",
    "makerCommission": "0.001",
    "takerCommission": "0.001"
  }
]
```

get_universal_transfer_history (**params)

Universal Transfer (For Master Account)

<https://binance-docs.github.io/apidocs/spot/en/#query-universal-transfer-history>

Parameters

- **fromEmail** (*str*) – optional
- **toEmail** (*str*) – optional
- **startTime** (*int*) – optional

- **endTime** (*int*) – optional
- **page** (*int*) – optional
- **limit** (*int*) – optional
- **recvWindow** (*int*) – optional

Returns API response

```
[
  {
    "tranId":11945860693,
    "fromEmail":"master@test.com",
    "toEmail":"subaccount1@test.com",
    "asset":"BTC",
    "amount":"0.1",
    "fromAccountType":"SPOT",
    "toAccountType":"COIN_FUTURE",
    "status":"SUCCESS",
    "createTimeStamp":1544433325000
  },
  {
    "tranId":11945857955,
    "fromEmail":"master@test.com",
    "toEmail":"subaccount2@test.com",
    "asset":"ETH",
    "amount":"0.2",
    "fromAccountType":"SPOT",
    "toAccountType":"USDT_FUTURE",
    "status":"SUCCESS",
    "createTimeStamp":1544433326000
  }
]
```

Raises BinanceRequestException, BinanceAPIException

get_withdraw_history (***params*)

Fetch withdraw history.

https://binance-docs.github.io/apidocs/spot/en/#withdraw-history-supporting-network-user_data

Parameters

- **coin** (*str*) – optional
- **offset** (*int*) – optional - default:0
- **limit** (*int*) – optional
- **startTime** (*int*) – optional - Default: 90 days from current timestamp
- **endTime** (*int*) – optional - Default: present timestamp
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
[
  {
    "address": "0x94df8b352de7f46f64b01d3666bf6e936e44ce60",
    "amount": "8.91000000",
```

(continues on next page)

(continued from previous page)

```

        "applyTime": "2019-10-12 11:12:02",
        "coin": "USDT",
        "id": "b6ae22b3aa844210a7041aee7589627c",
        "withdrawOrderId": "WITHDRAWtest123", // will not be returned if
→there's no withdrawOrderId for this withdraw.
        "network": "ETH",
        "transferType": 0, // 1 for internal transfer, 0 for external
→transfer
        "status": 6,
        "txId":
→"0xb5ef8c13b968a406cc62a93a8bd80f9e9a906ef1b3fcf20a2e48573c17659268"
    },
    {
        "address": "1FZdVHtiBqMrWdjPyRPULCUceZPJ2WLCsB",
        "amount": "0.00150000",
        "applyTime": "2019-09-24 12:43:45",
        "coin": "BTC",
        "id": "156ec387f49b41df8724fa744fa82719",
        "network": "BTC",
        "status": 6,
        "txId":
→"60fd9007ebfddc753455f95fafa808c4302c836e4d1eebc5a132c36c1d8ac354"
    }
]

```

Raises `BinanceRequestException`, `BinanceAPIException`

get_withdraw_history_id (*withdraw_id*, ****params**)

Fetch withdraw history.

https://binance-docs.github.io/apidocs/spot/en/#withdraw-history-supporting-network-user_data

Parameters

- **withdraw_id** (*str*) – required
- **asset** (*str*) – optional
- **startTime** (*long*) – optional
- **endTime** (*long*) – optional
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```

{
    "id": "7213fea8e94b4a5593d507237e5a555b",
    "withdrawOrderId": None,
    "amount": 0.99,
    "transactionFee": 0.01,
    "address": "0x6915f16f8791d0a1cc2bf47c13a6b2a92000504b",
    "asset": "ETH",
    "txId":
→"0xdf33b22bdb2b28b1f75ccd201a4a4m6e7g83jy5fc5d5a9d1340961598cfcb0a1",
    "applyTime": 1508198532000,
    "status": 4
}

```

Raises BinanceRequestException, BinanceAPIException

isolated_margin_stream_close (*symbol*, *listenKey*)

Close out an isolated margin data stream.

<https://binance-docs.github.io/apidocs/spot/en/#listen-key-isolated-margin>

Parameters

- **symbol** (*str*) – required - symbol for the isolated margin account
- **listenKey** (*str*) – required

Returns API response

```
{}
```

Raises BinanceRequestException, BinanceAPIException

isolated_margin_stream_get_listen_key (*symbol*)

Start a new isolated margin data stream and return the listen key If a stream already exists it should return the same key. If the stream becomes invalid a new key is returned.

Can be used to keep the stream alive.

<https://binance-docs.github.io/apidocs/spot/en/#listen-key-isolated-margin>

Parameters **symbol** (*str*) – required - symbol for the isolated margin account

Returns API response

```
{
  "listenKey":
  → "T3ee22BIYuWqmvne0HNq2A2WsF1EtLhvWCtItw6ffhhdmjifQ2tRbuKkTHhr"
}
```

Raises BinanceRequestException, BinanceAPIException

isolated_margin_stream_keepalive (*symbol*, *listenKey*)

PING an isolated margin data stream to prevent a time out.

<https://binance-docs.github.io/apidocs/spot/en/#listen-key-isolated-margin>

Parameters

- **symbol** (*str*) – required - symbol for the isolated margin account
- **listenKey** (*str*) – required

Returns API response

```
{}
```

Raises BinanceRequestException, BinanceAPIException

make_subaccount_futures_transfer (***params*)

Futures Transfer for Sub-account (For Master Account)

<https://binance-docs.github.io/apidocs/spot/en/#futures-transfer-for-sub-account-for-master-account>

Parameters

- **email** (*str*) – required - Sub account email
- **asset** (*str*) – required - The asset being transferred, e.g., USDT
- **amount** (*float*) – required - The amount to be transferred
- **type** (*int*) – required - 1: transfer from subaccount’s spot account to its USDT-margined futures account 2: transfer from subaccount’s USDT-margined futures account to its spot account 3: transfer from subaccount’s spot account to its COIN-margined futures account 4: transfer from subaccount’s COIN-margined futures account to its spot account

Returns API response

```
{
  "txnId": "2966662589"
}
```

Raises BinanceRequestException, BinanceAPIException

make_subaccount_margin_transfer (**params)

Margin Transfer for Sub-account (For Master Account)

<https://binance-docs.github.io/apidocs/spot/en/#margin-transfer-for-sub-account-for-master-account>

Parameters

- **email** (*str*) – required - Sub account email
- **asset** (*str*) – required - The asset being transferred, e.g., USDT
- **amount** (*float*) – required - The amount to be transferred
- **type** (*int*) – required - 1: transfer from subaccount’s spot account to margin account 2: transfer from subaccount’s margin account to its spot account

Returns API response

```
{
  "txnId": "2966662589"
}
```

Raises BinanceRequestException, BinanceAPIException

make_subaccount_to_master_transfer (**params)

Transfer to Master (For Sub-account)

<https://binance-docs.github.io/apidocs/spot/en/#transfer-to-master-for-sub-account>

Parameters

- **asset** (*str*) – required - The asset being transferred, e.g., USDT
- **amount** (*float*) – required - The amount to be transferred
- **recvWindow** (*int*) – optional

Returns API response

```
{
  "txnId": "2966662589"
}
```

Raises BinanceRequestException, BinanceAPIException

make_subaccount_to_subaccount_transfer (**params)

Transfer to Sub-account of Same Master (For Sub-account)

<https://binance-docs.github.io/apidocs/spot/en/#transfer-to-sub-account-of-same-master-for-sub-account>

Parameters

- **toEmail** (*str*) – required - Sub account email
- **asset** (*str*) – required - The asset being transferred, e.g., USDT
- **amount** (*float*) – required - The amount to be transferred
- **recvWindow** (*int*) – optional

Returns API response

```
{
  "txnId": "2966662589"
}
```

Raises BinanceRequestException, BinanceAPIException

make_subaccount_universal_transfer (**params)

Universal Transfer (For Master Account)

<https://binance-docs.github.io/apidocs/spot/en/#universal-transfer-for-master-account>

Parameters

- **fromEmail** (*str*) – optional
- **toEmail** (*str*) – optional
- **fromAccountType** (*str*) – required - “SPOT”, “USDT_FUTURE”, “COIN_FUTURE”
- **toAccountType** (*str*) – required - “SPOT”, “USDT_FUTURE”, “COIN_FUTURE”
- **asset** (*str*) – required - The asset being transferred, e.g., USDT
- **amount** (*float*) – required
- **recvWindow** (*int*) – optional

Returns API response

```
{
  "tranId": 11945860693
}
```

Raises BinanceRequestException, BinanceAPIException

make_universal_transfer (**params)

User Universal Transfer

<https://binance-docs.github.io/apidocs/spot/en/#user-universal-transfer>

Parameters

- **type** (*str* (ENUM)) – required
- **asset** (*str*) – required

- **amount** (*str*) – required
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

```
transfer_status = client.make_universal_transfer(params)
```

Returns API response

```
{
  "tranId":13526853623
}
```

Raises BinanceRequestException, BinanceAPIException

margin_stream_close (*listenKey*)

Close out a cross-margin data stream.

<https://binance-docs.github.io/apidocs/spot/en/#listen-key-margin>

Parameters **listenKey** (*str*) – required

Returns API response

```
{}
```

Raises BinanceRequestException, BinanceAPIException

margin_stream_get_listen_key ()

Start a new cross-margin data stream and return the listen key If a stream already exists it should return the same key. If the stream becomes invalid a new key is returned.

Can be used to keep the stream alive.

<https://binance-docs.github.io/apidocs/spot/en/#listen-key-margin>

Returns API response

```
{
  "listenKey":
  →"pqia9lma19a5s61cv6a81va65sdf19v8a65a1a5s61cv6a81va65sdf19v8a65a1"
}
```

Raises BinanceRequestException, BinanceAPIException

margin_stream_keepalive (*listenKey*)

PING a cross-margin data stream to prevent a time out.

<https://binance-docs.github.io/apidocs/spot/en/#listen-key-margin>

Parameters **listenKey** (*str*) – required

Returns API response

```
{}
```

Raises BinanceRequestException, BinanceAPIException

new_transfer_history (**params)

Get future account transaction history list

<https://binance-docs.github.io/apidocs/delivery/en/#new-future-account-transfer>

options_account_info (**params)

Account asset info (USER_DATA)

https://binance-docs.github.io/apidocs/voptions/en/#account-asset-info-user_data

Parameters **recvWindow** (*int*) – optional

options_bill (**params)

Account funding flow (USER_DATA)

https://binance-docs.github.io/apidocs/voptions/en/#account-funding-flow-user_data

Parameters

- **currency** (*str*) – required - Asset type - USDT
- **recordId** (*int*) – optional - Return the recordId and subsequent data, the latest data is returned by default - 100000
- **startTime** (*int*) – optional - Start Time - 1593511200000
- **endTime** (*int*) – optional - End Time - 1593511200000
- **limit** (*int*) – optional - Number of result sets returned Default:100 Max:1000 - 100
- **recvWindow** (*int*) – optional

options_cancel_all_orders (**params)

Cancel all Option orders (TRADE)

<https://binance-docs.github.io/apidocs/voptions/en/#cancel-all-option-orders-trade>

Parameters

- **symbol** (*str*) – required - Option trading pair - BTC-200730-9000-C
- **recvWindow** (*int*) – optional

options_cancel_batch_order (**params)

Cancel Multiple Option orders (TRADE)

<https://binance-docs.github.io/apidocs/voptions/en/#cancel-multiple-option-orders-trade>

Parameters

- **symbol** (*str*) – required - Option trading pair - BTC-200730-9000-C
- **orderIds** – optional - Order ID - [4611875134427365377,4611875134427365378]
- **clientOrderIds** (*list*) – optional - User-defined order ID - ["my_id_1","my_id_2"]
- **recvWindow** (*int*) – optional

options_cancel_order (**params)

Cancel Option order (TRADE)

<https://binance-docs.github.io/apidocs/voptions/en/#cancel-option-order-trade>

Parameters

- **symbol** (*str*) – required - Option trading pair - BTC-200730-9000-C

- **orderId** (*str*) – optional - Order ID - 4611875134427365377
- **clientOrderId** (*str*) – optional - User-defined order ID - 10000
- **recvWindow** (*int*) – optional

options_exchange_info ()

Get current limit info and trading pair info

<https://binance-docs.github.io/apidocs/voptions/en/#get-current-limit-info-and-trading-pair-info>**options_funds_transfer** (**params)

Funds transfer (USER_DATA)

https://binance-docs.github.io/apidocs/voptions/en/#funds-transfer-user_data**Parameters**

- **currency** (*str*) – required - Asset type - USDT
- **type** (*str* (ENUM)) – required - IN: Transfer from spot account to option account OUT: Transfer from option account to spot account - IN
- **amount** (*float*) – required - Amount - 10000
- **recvWindow** (*int*) – optional

options_historical_trades (**params)

Query trade history

<https://binance-docs.github.io/apidocs/voptions/en/#query-trade-history>**Parameters**

- **symbol** (*str*) – required - Option trading pair - BTC-200730-9000-C
- **fromId** (*int*) – optional - The deal ID from which to return. The latest deal record is returned by default - 1592317127349
- **limit** (*int*) – optional - Number of records Default:100 Max:500 - 100

options_index_price (**params)

Get the spot index price

<https://binance-docs.github.io/apidocs/voptions/en/#get-the-spot-index-price>**Parameters underlying** (*str*) – required - Spot pairOption contract underlying asset-BTCUSDT**options_info** ()

Get current trading pair info

<https://binance-docs.github.io/apidocs/voptions/en/#get-current-trading-pair-info>**options_klines** (**params)

Candle data

<https://binance-docs.github.io/apidocs/voptions/en/#candle-data>**Parameters**

- **symbol** (*str*) – required - Option trading pair - BTC-200730-9000-C
- **interval** (*str*) – required - Time interval - 5m
- **startTime** (*int*) – optional - Start Time - 1592317127349
- **endTime** (*int*) – optional - End Time - 1592317127349

- **limit** (*int*) – optional - Number of records Default:500 Max:1500 - 500

options_mark_price (***params*)

Get the latest mark price

<https://binance-docs.github.io/apidocs/voptions/en/#get-the-latest-mark-price>

Parameters **symbol** (*str*) – optional - Option trading pair - BTC-200730-9000-C

options_order_book (***params*)

Depth information

<https://binance-docs.github.io/apidocs/voptions/en/#depth-information>

Parameters

- **symbol** (*str*) – required - Option trading pair - BTC-200730-9000-C
- **limit** (*int*) – optional - Default:100 Max:1000.Optional value:[10, 20, 50, 100, 500, 1000] - 100

options_ping ()

Test connectivity

<https://binance-docs.github.io/apidocs/voptions/en/#test-connectivity>

options_place_batch_order (***params*)

Place Multiple Option orders (TRADE)

<https://binance-docs.github.io/apidocs/voptions/en/#place-multiple-option-orders-trade>

Parameters

- **orders** (*list*) – required - order list. Max 5 orders - [{"symbol": "BTC-210115-35000-C", "price": "100", "quantity": "0.0001", "side": "BUY", "type": "LIMIT"}]
- **recvWindow** (*int*) – optional

options_place_order (***params*)

Option order (TRADE)

<https://binance-docs.github.io/apidocs/voptions/en/#option-order-trade>

Parameters

- **symbol** (*str*) – required - Option trading pair - BTC-200730-9000-C
- **side** (*str* (ENUM)) – required - Buy/sell direction: SELL, BUY - BUY
- **type** (*str* (ENUM)) – required - Order Type: LIMIT, MARKET - LIMIT
- **quantity** (*float*) – required - Order Quantity - 3
- **price** (*float*) – optional - Order Price - 1000
- **timeInForce** (*str* (ENUM)) – optional - Time in force method Default GTC - GTC
- **reduceOnly** (*bool*) – optional - Reduce Only (Default false) - false
- **postOnly** (*bool*) – optional - Post Only (Default false) - false
- **newOrderRespType** (*str* (ENUM)) – optional - “ACK”, “RESULT”, Default “ACK” - ACK
- **clientOrderId** (*str*) – optional - User-defined order ID cannot be repeated in pending orders - 10000

- **recvWindow** (*int*) – optional

options_positions (***params*)

Option holdings info (USER_DATA)

https://binance-docs.github.io/apidocs/voptions/en/#option-holdings-info-user_data

Parameters

- **symbol** (*str*) – optional - Option trading pair - BTC-200730-9000-C
- **recvWindow** (*int*) – optional

options_price (***params*)

Get the latest price

<https://binance-docs.github.io/apidocs/voptions/en/#get-the-latest-price>

Parameters **symbol** (*str*) – optional - Option trading pair - BTC-200730-9000-C

options_query_order (***params*)

Query Option order (TRADE)

<https://binance-docs.github.io/apidocs/voptions/en/#query-option-order-trade>

Parameters

- **symbol** (*str*) – required - Option trading pair - BTC-200730-9000-C
- **orderId** (*str*) – optional - Order ID - 4611875134427365377
- **clientOrderId** (*str*) – optional - User-defined order ID - 10000
- **recvWindow** (*int*) – optional

options_query_order_history (***params*)

Query Option order history (TRADE)

<https://binance-docs.github.io/apidocs/voptions/en/#query-option-order-history-trade>

Parameters

- **symbol** (*str*) – required - Option trading pair - BTC-200730-9000-C
- **orderId** (*str*) – optional - Returns the orderId and subsequent orders, the most recent order is returned by default - 100000
- **startTime** (*int*) – optional - Start Time - 1593511200000
- **endTime** (*int*) – optional - End Time - 1593511200000
- **limit** (*int*) – optional - Number of result sets returned Default:100 Max:1000 - 100
- **recvWindow** (*int*) – optional

options_query_pending_orders (***params*)

Query current pending Option orders (TRADE)

<https://binance-docs.github.io/apidocs/voptions/en/#query-current-pending-option-orders-trade>

Parameters

- **symbol** (*str*) – required - Option trading pair - BTC-200730-9000-C
- **orderId** (*str*) – optional - Returns the orderId and subsequent orders, the most recent order is returned by default - 100000
- **startTime** (*int*) – optional - Start Time - 1593511200000

- **endTime** (*int*) – optional - End Time - 1593511200000
- **limit** (*int*) – optional - Number of result sets returned Default:100 Max:1000 - 100
- **recvWindow** (*int*) – optional

options_recent_trades (**params)

Recently completed Option trades

<https://binance-docs.github.io/apidocs/voptions/en/#recently-completed-option-trades>

Parameters

- **symbol** (*str*) – required - Option trading pair - BTC-200730-9000-C
- **limit** (*int*) – optional - Number of records Default:100 Max:500 - 100

options_time ()

Get server time

<https://binance-docs.github.io/apidocs/voptions/en/#get-server-time>

options_user_trades (**params)

Option Trade List (USER_DATA)

https://binance-docs.github.io/apidocs/voptions/en/#option-trade-list-user_data

Parameters

- **symbol** (*str*) – required - Option trading pair - BTC-200730-9000-C
- **fromId** (*int*) – optional - Trade id to fetch from. Default gets most recent trades. - 4611875134427365376
- **startTime** (*int*) – optional - Start Time - 1593511200000
- **endTime** (*int*) – optional - End Time - 1593511200000
- **limit** (*int*) – optional - Number of result sets returned Default:100 Max:1000 - 100
- **recvWindow** (*int*) – optional

order_limit (timeInForce='GTC', **params)

Send in a new limit order

Any order with an icebergQty MUST have timeInForce set to GTC.

Parameters

- **symbol** (*str*) – required
- **side** (*str*) – required
- **quantity** (*decimal*) – required
- **price** (*str*) – required
- **timeInForce** (*str*) – default Good till cancelled
- **newClientOrderId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **icebergQty** (*decimal*) – Used with LIMIT, STOP_LOSS_LIMIT, and TAKE_PROFIT_LIMIT to create an iceberg order.

- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See order endpoint for full response options

Raises BinanceRequestException, BinanceAPIException, BinanceOrderException, BinanceOrderMinAmountException, BinanceOrderMinPriceException, BinanceOrderMinTotalException, BinanceOrderUnknownSymbolException, BinanceOrderInactiveSymbolException

order_limit_buy (*timeInForce='GTC', **params*)

Send in a new limit buy order

Any order with an icebergQty MUST have timeInForce set to GTC.

Parameters

- **symbol** (*str*) – required
- **quantity** (*decimal*) – required
- **price** (*str*) – required
- **timeInForce** (*str*) – default Good till cancelled
- **newClientOrderId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **stopPrice** (*decimal*) – Used with stop orders
- **icebergQty** (*decimal*) – Used with iceberg orders
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See order endpoint for full response options

Raises BinanceRequestException, BinanceAPIException, BinanceOrderException, BinanceOrderMinAmountException, BinanceOrderMinPriceException, BinanceOrderMinTotalException, BinanceOrderUnknownSymbolException, BinanceOrderInactiveSymbolException

order_limit_sell (*timeInForce='GTC', **params*)

Send in a new limit sell order

Parameters

- **symbol** (*str*) – required
- **quantity** (*decimal*) – required
- **price** (*str*) – required
- **timeInForce** (*str*) – default Good till cancelled
- **newClientOrderId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **stopPrice** (*decimal*) – Used with stop orders

- **icebergQty** (*decimal*) – Used with iceberg orders
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See order endpoint for full response options

Raises `BinanceRequestException`, `BinanceAPIException`, `BinanceOrderException`, `BinanceOrderMinAmountException`, `BinanceOrderMinPriceException`, `BinanceOrderMinTotalException`, `BinanceOrderUnknownSymbolException`, `BinanceOrderInactiveSymbolException`

order_market (***params*)

Send in a new market order

Parameters

- **symbol** (*str*) – required
- **side** (*str*) – required
- **quantity** (*decimal*) – required
- **quoteOrderQty** (*decimal*) – amount the user wants to spend (when buying) or receive (when selling) of the quote asset
- **newClientOrderId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See order endpoint for full response options

Raises `BinanceRequestException`, `BinanceAPIException`, `BinanceOrderException`, `BinanceOrderMinAmountException`, `BinanceOrderMinPriceException`, `BinanceOrderMinTotalException`, `BinanceOrderUnknownSymbolException`, `BinanceOrderInactiveSymbolException`

order_market_buy (***params*)

Send in a new market buy order

Parameters

- **symbol** (*str*) – required
- **quantity** (*decimal*) – required
- **quoteOrderQty** (*decimal*) – the amount the user wants to spend of the quote asset
- **newClientOrderId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See order endpoint for full response options

Raises `BinanceRequestException`, `BinanceAPIException`, `BinanceOrderException`, `BinanceOrderMinAmountException`, `BinanceOrderMinPriceException`, `BinanceOrderMinTotalException`, `BinanceOrderUnknownSymbolException`, `BinanceOrderInactiveSymbolException`

order_market_sell (**params)

Send in a new market sell order

Parameters

- **symbol** (*str*) – required
- **quantity** (*decimal*) – required
- **quoteOrderQty** (*decimal*) – the amount the user wants to receive of the quote asset
- **newClientOrderId** (*str*) – A unique id for the order. Automatically generated if not sent.
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See order endpoint for full response options

Raises `BinanceRequestException`, `BinanceAPIException`, `BinanceOrderException`, `BinanceOrderMinAmountException`, `BinanceOrderMinPriceException`, `BinanceOrderMinTotalException`, `BinanceOrderUnknownSymbolException`, `BinanceOrderInactiveSymbolException`

order_oco_buy (**params)

Send in a new OCO buy order

Parameters

- **symbol** (*str*) – required
- **listClientOrderId** (*str*) – A unique id for the list order. Automatically generated if not sent.
- **quantity** (*decimal*) – required
- **limitClientOrderId** (*str*) – A unique id for the limit order. Automatically generated if not sent.
- **price** (*str*) – required
- **limitIcebergQty** (*decimal*) – Used to make the LIMIT_MAKER leg an iceberg order.
- **stopClientOrderId** (*str*) – A unique id for the stop order. Automatically generated if not sent.
- **stopPrice** (*str*) – required
- **stopLimitPrice** (*str*) – If provided, `stopLimitTimeInForce` is required.

- **stopIcebergQty** (*decimal*) – Used with STOP_LOSS_LIMIT leg to make an iceberg order.
- **stopLimitTimeInForce** (*str*) – Valid values are GTC/FOK/IOC.
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See OCO order endpoint for full response options

Raises BinanceRequestException, BinanceAPIException, BinanceOrderException, BinanceOrderMinAmountException, BinanceOrderMinPriceException, BinanceOrderMinTotalException, BinanceOrderUnknownSymbolException, BinanceOrderInactiveSymbolException

order_oco_sell (***params*)

Send in a new OCO sell order

Parameters

- **symbol** (*str*) – required
- **listClientId** (*str*) – A unique id for the list order. Automatically generated if not sent.
- **quantity** (*decimal*) – required
- **limitClientId** (*str*) – A unique id for the limit order. Automatically generated if not sent.
- **price** (*str*) – required
- **limitIcebergQty** (*decimal*) – Used to make the LIMIT_MAKER leg an iceberg order.
- **stopClientId** (*str*) – A unique id for the stop order. Automatically generated if not sent.
- **stopPrice** (*str*) – required
- **stopLimitPrice** (*str*) – If provided, stopLimitTimeInForce is required.
- **stopIcebergQty** (*decimal*) – Used with STOP_LOSS_LIMIT leg to make an iceberg order.
- **stopLimitTimeInForce** (*str*) – Valid values are GTC/FOK/IOC.
- **newOrderRespType** (*str*) – Set the response JSON. ACK, RESULT, or FULL; default: RESULT.
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

See OCO order endpoint for full response options

Raises BinanceRequestException, BinanceAPIException, BinanceOrderException, BinanceOrderMinAmountException, BinanceOrderMinPriceException, BinanceOrderMinTotalException, BinanceOrderUnknownSymbolException, BinanceOrderInactiveSymbolException

ping () → Dict[KT, VT]

Test connectivity to the Rest API.

<https://binance-docs.github.io/apidocs/spot/en/#test-connectivity>

Returns Empty array

```
{}
```

Raises BinanceRequestException, BinanceAPIException

purchase_lending_product (**params)

Purchase Flexible Product

https://binance-docs.github.io/apidocs/spot/en/#purchase-flexible-product-user_data

query_subaccount_spot_summary (**params)

Query Sub-account Spot Assets Summary (For Master Account)

<https://binance-docs.github.io/apidocs/spot/en/#query-sub-account-spot-assets-summary-for-master-account>

Parameters

- **email** (*str*) – optional - Sub account email
- **page** (*int*) – optional - default 1
- **size** (*int*) – optional - default 10, max 20
- **recvWindow** (*int*) – optional

Returns API response

```
{
  "totalCount":2,
  "masterAccountTotalAsset": "0.23231201",
  "spotSubUserAssetBtcVoList":[
    {
      "email":"sub123@test.com",
      "totalAsset":"9999.00000000"
    },
    {
      "email":"test456@test.com",
      "totalAsset":"0.00000000"
    }
  ]
}
```

Raises BinanceRequestException, BinanceAPIException

query_universal_transfer_history (**params)

Query User Universal Transfer History

<https://binance-docs.github.io/apidocs/spot/en/#query-user-universal-transfer-history>

Parameters

- **type** (*str* (ENUM)) – required
- **startTime** (*int*) – optional
- **endTime** (*int*) – optional

- **current** (*int*) – optional - Default 1
- **size** (*int*) – required - Default 10, Max 100
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

```
transfer_status = client.query_universal_transfer_history(params)
```

Returns API response

```
{
  "total":2,
  "rows":[
    {
      "asset":"USDT",
      "amount":"1",
      "type":"MAIN_UMFUTURE"
      "status": "CONFIRMED",
      "tranId": 11415955596,
      "timestamp":1544433328000
    },
    {
      "asset":"USDT",
      "amount":"2",
      "type":"MAIN_UMFUTURE",
      "status": "CONFIRMED",
      "tranId": 11366865406,
      "timestamp":1544433328000
    }
  ]
}
```

Raises BinanceRequestException, BinanceAPIException

redeem_lending_product (**params)

Redeem Flexible Product

https://binance-docs.github.io/apidocs/spot/en/#redeem-flexible-product-user_data

repay_margin_loan (**params)

Repay loan in cross-margin or isolated-margin account.

If amount is more than the amount borrowed, the full loan will be repaid.

<https://binance-docs.github.io/apidocs/spot/en/#margin-account-repay-margin>

Parameters

- **asset** (*str*) – name of the asset
- **amount** (*str*) – amount to transfer
- **isIsolated** (*str*) – set to ‘TRUE’ for isolated margin (default ‘FALSE’)
- **symbol** (*str*) – Isolated margin symbol (default blank for cross-margin)
- **recvWindow** (*int*) – the number of milliseconds the request is valid for


```
transaction = client.margin_repay_loan(asset='BTC', amount='1.1')

transaction = client.margin_repay_loan(asset='BTC', amount='1.1',
                                       isIsolated='TRUE', symbol='ETHBTC')
```

Returns API response

```
{
  "tranId": 100000001
}
```

Raises BinanceRequestException, BinanceAPIException

stream_close (*listenKey*)

Close out a user data stream.

<https://binance-docs.github.io/apidocs/spot/en/#listen-key-spot>

Parameters **listenKey** (*str*) – required

Returns API response

```
{}
```

Raises BinanceRequestException, BinanceAPIException

stream_get_listen_key ()

Start a new user data stream and return the listen key If a stream already exists it should return the same key. If the stream becomes invalid a new key is returned.

Can be used to keep the user stream alive.

<https://binance-docs.github.io/apidocs/spot/en/#listen-key-spot>

Returns API response

```
{
  "listenKey":
  ↪"pqia9lma19a5s61cv6a81va65sdf19v8a65a1a5s61cv6a81va65sdf19v8a65a1"
}
```

Raises BinanceRequestException, BinanceAPIException

stream_keepalive (*listenKey*)

PING a user data stream to prevent a time out.

<https://binance-docs.github.io/apidocs/spot/en/#listen-key-spot>

Parameters **listenKey** (*str*) – required

Returns API response

```
{}
```

Raises BinanceRequestException, BinanceAPIException

toggle_bnb_burn_spot_margin (**params)

Toggle BNB Burn On Spot Trade And Margin Interest

https://binance-docs.github.io/apidocs/spot/en/#toggle-bnb-burn-on-spot-trade-and-margin-interest-user_data

Parameters

- **spotBNBBurn** (*bool*) – Determines whether to use BNB to pay for trading fees on SPOT
- **interestBNBBurn** (*bool*) – Determines whether to use BNB to pay for margin loan's interest

```
response = client.toggle_bnb_burn_spot_margin()
```

Returns API response

```
{
  "spotBNBBurn": true,
  "interestBNBBurn": false
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

transfer_dust (**params)

Convert dust assets to BNB.

https://binance-docs.github.io/apidocs/spot/en/#dust-transfer-user_data

Parameters

- **asset** (*str*) – The asset being converted. e.g: 'ONE'
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

```
result = client.transfer_dust(asset='ONE')
```

Returns API response

```
{
  "totalServiceCharge": "0.02102542",
  "totalTransferred": "1.05127099",
  "transferResult": [
    {
      "amount": "0.03000000",
      "fromAsset": "ETH",
      "operateTime": 1563368549307,
      "serviceChargeAmount": "0.00500000",
      "tranId": 2970932918,
      "transferredAmount": "0.25000000"
    }
  ]
}
```

Raises `BinanceRequestException`, `BinanceAPIException`

transfer_history (**params)

Get future account transaction history list

https://binance-docs.github.io/apidocs/futures/en/#get-future-account-transaction-history-list-user_data**transfer_isolated_margin_to_spot** (**params)

Execute transfer between isolated margin account and spot account.

<https://binance-docs.github.io/apidocs/spot/en/#isolated-margin-account-transfer-margin>**Parameters**

- **asset** (*str*) – name of the asset
- **symbol** (*str*) – pair symbol
- **amount** (*str*) – amount to transfer
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

```
transfer = client.transfer_isolated_margin_to_spot(asset='BTC',
                                                  symbol='ETHBTC', amount=
↪ '1.1')
```

Returns API response

```
{
  "tranId": 100000001
}
```

Raises BinanceRequestException, BinanceAPIException**transfer_margin_to_spot** (**params)

Execute transfer between cross-margin account and spot account.

<https://binance-docs.github.io/apidocs/spot/en/#cross-margin-account-transfer-margin>**Parameters**

- **asset** (*str*) – name of the asset
- **amount** (*str*) – amount to transfer
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

```
transfer = client.transfer_margin_to_spot(asset='BTC', amount='1.1')
```

Returns API response

```
{
  "tranId": 100000001
}
```

Raises BinanceRequestException, BinanceAPIException**transfer_spot_to_isolated_margin** (**params)

Execute transfer between spot account and isolated margin account.

<https://binance-docs.github.io/apidocs/spot/en/#isolated-margin-account-transfer-margin>

Parameters

- **asset** (*str*) – name of the asset
- **symbol** (*str*) – pair symbol
- **amount** (*str*) – amount to transfer
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

```
transfer = client.transfer_spot_to_isolated_margin(asset='BTC',  
                                                  symbol='ETHBTC', amount=  
↪ '1.1')
```

Returns API response

```
{  
  "tranId": 100000001  
}
```

Raises BinanceRequestException, BinanceAPIException**transfer_spot_to_margin** (**params)

Execute transfer between spot account and cross-margin account.

<https://binance-docs.github.io/apidocs/spot/en/#cross-margin-account-transfer-margin>

Parameters

- **asset** (*str*) – name of the asset
- **amount** (*str*) – amount to transfer
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

```
transfer = client.transfer_spot_to_margin(asset='BTC', amount='1.1')
```

Returns API response

```
{  
  "tranId": 100000001  
}
```

Raises BinanceRequestException, BinanceAPIException**universal_transfer** (**params)

Universal transfer api accross different binance account types

<https://binance-docs.github.io/apidocs/spot/en/#user-universal-transfer>

withdraw (**params)

Submit a withdraw request.

<https://binance-docs.github.io/apidocs/spot/en/#withdraw-sapi>

Assumptions:

- You must have Withdraw permissions enabled on your API key

- You must have withdrawn to the address specified through the website and approved the transaction via email

Parameters

- **coin** (*str*) – required
- **withdrawOrderId** (*str*) – optional - client id for withdraw
- **network** (*str*) – optional
- **address** (*str*) – optional
- **amount** (*decimal*) – required
- **transactionFeeFlag** (*bool*) – required - When making internal transfer, true for returning the fee to the destination account; false for returning the fee back to the departure account. Default false.
- **name** (*str*) – optional - Description of the address, default asset value passed will be used
- **recvWindow** (*int*) – the number of milliseconds the request is valid for

Returns API response

```
{
  "id": "7213fea8e94b4a5593d507237e5a555b"
}
```

Raises BinanceRequestException, BinanceAPIException

depthcache module

class binance.depthcache.**BaseDepthCacheManager** (*client*, *symbol*, *loop=None*, *refresh_interval=None*, *bm=None*, *limit=10*, *conv_type=<class 'float'>*)

Bases: object

DEFAULT_REFRESH = 1800

TIMEOUT = 60

__init__ (*client*, *symbol*, *loop=None*, *refresh_interval=None*, *bm=None*, *limit=10*, *conv_type=<class 'float'>*)

Create a DepthCacheManager instance

Parameters

- **client** (*binance.Client*) – Binance API client
- **loop** –
- **symbol** (*string*) – Symbol to create depth cache for
- **refresh_interval** (*int*) – Optional number of seconds between cache refresh, use 0 or None to disable
- **bm** (*BinanceSocketManager*) – Optional BinanceSocketManager
- **limit** (*int*) – Optional number of orders to get from orderbook

- **conv_type** (*function.*) – Optional type to represent price, and amount, default is float.

close ()

Close the open socket for this manager

Returns

get_depth_cache ()

Get the current depth cache

Returns DepthCache object

get_symbol ()

Get the symbol

Returns symbol

recv ()

class binance.depthcache.DepthCache (*symbol, conv_type=<class 'float'>*)

Bases: object

__init__ (*symbol, conv_type=<class 'float'>*)

Initialise the DepthCache

Parameters

- **symbol** (*string*) – Symbol to create depth cache for
- **conv_type** (*function.*) – Optional type to represent price, and amount, default is float.

add_ask (*ask*)

Add an ask to the cache

Parameters *ask* –

Returns

add_bid (*bid*)

Add a bid to the cache

Parameters *bid* –

Returns

get_asks ()

Get the current asks

Returns list of asks with price and quantity as *conv_type*.

```
[
  [
    0.0001955, # Price
    57.0'      # Quantity
  ],
  [
    0.00019699,
    778.0
  ],
  [
    0.000197,
    64.0
  ]
]
```

(continues on next page)

(continued from previous page)

```

    ],
    [
        0.00019709,
        1130.0
    ],
    [
        0.0001971,
        385.0
    ]
]

```

get_bids()

Get the current bids

Returns list of bids with price and quantity as conv_type

```

[
  [
    0.0001946, # Price
    45.0      # Quantity
  ],
  [
    0.00019459,
    2384.0
  ],
  [
    0.00019158,
    5219.0
  ],
  [
    0.00019157,
    1180.0
  ],
  [
    0.00019082,
    287.0
  ]
]

```

static sort_depth (vals, reverse=False, conv_type=<class 'float'>)

Sort bids or asks by price

```

class binance.depthcache.DepthCacheManager (client, symbol, loop=None, re-
fresh_interval=None, bm=None,
limit=500, conv_type=<class 'float'>,
ws_interval=None)

```

Bases: *binance.depthcache.BaseDepthCacheManager*

```

__init__(client, symbol, loop=None, refresh_interval=None, bm=None, limit=500,
conv_type=<class 'float'>, ws_interval=None)

```

Initialise the DepthCacheManager

Parameters

- **client** (*binance.Client*) – Binance API client
- **loop** – asyncio loop
- **symbol** (*string*) – Symbol to create depth cache for

- **refresh_interval** (*int*) – Optional number of seconds between cache refresh, use 0 or None to disable
- **limit** (*int*) – Optional number of orders to get from orderbook
- **conv_type** (*function.*) – Optional type to represent price, and amount, default is float.
- **ws_interval** (*int*) – Optional interval for updates on websocket, default None. If not set, updates happen every second. Must be 0, None (1s) or 100 (100ms).

```
class binance.depthcache.FuturesDepthCacheManager (client, symbol, loop=None, re-  
fresh_interval=None, bm=None,  
limit=10, conv_type=<class  
'float'>)
```

Bases: *binance.depthcache.BaseDepthCacheManager*

```
class binance.depthcache.OptionsDepthCacheManager (client, symbol, loop=None, re-  
fresh_interval=None, bm=None,  
limit=10, conv_type=<class  
'float'>)
```

Bases: *binance.depthcache.BaseDepthCacheManager*

```
class binance.depthcache.ThreadedDepthCacheManager (api_key: Optional[str] = None,  
api_secret: Optional[str] = None,  
requests_params: Dict[str, str] =  
None, tld: str = 'com', testnet:  
bool = False)
```

Bases: *binance.threaded_stream.ThreadedApiManager*

```
__init__ (api_key: Optional[str] = None, api_secret: Optional[str] = None, requests_params:  
Dict[str, str] = None, tld: str = 'com', testnet: bool = False)  
Initialize the BinanceSocketManager
```

```
start_depth_cache (callback: Callable, symbol: str, refresh_interval=None, bm=None, limit=10,  
conv_type=<class 'float'>, ws_interval=0) → str
```

```
start_futures_depth_socket (callback: Callable, symbol: str, refresh_interval=None,  
bm=None, limit=10, conv_type=<class 'float'>) → str
```

```
start_options_depth_socket (callback: Callable, symbol: str, refresh_interval=None,  
bm=None, limit=10, conv_type=<class 'float'>) → str
```

exceptions module

```
exception binance.exceptions.BinanceAPIException (response, status_code, text)  
Bases: Exception
```

```
__init__ (response, status_code, text)  
Initialize self. See help(type(self)) for accurate signature.
```

```
exception binance.exceptions.BinanceOrderException (code, message)  
Bases: Exception
```

```
__init__ (code, message)  
Initialize self. See help(type(self)) for accurate signature.
```

```
exception binance.exceptions.BinanceOrderInactiveSymbolException (value)  
Bases: binance.exceptions.BinanceOrderException
```

```
__init__ (value)  
Initialize self. See help(type(self)) for accurate signature.
```


exception `binance.exceptions.BinanceOrderMinAmountException` (*value*)
 Bases: `binance.exceptions.BinanceOrderException`

`__init__` (*value*)
 Initialize self. See help(type(self)) for accurate signature.

exception `binance.exceptions.BinanceOrderMinPriceException` (*value*)
 Bases: `binance.exceptions.BinanceOrderException`

`__init__` (*value*)
 Initialize self. See help(type(self)) for accurate signature.

exception `binance.exceptions.BinanceOrderMinTotalException` (*value*)
 Bases: `binance.exceptions.BinanceOrderException`

`__init__` (*value*)
 Initialize self. See help(type(self)) for accurate signature.

exception `binance.exceptions.BinanceOrderUnknownSymbolException` (*value*)
 Bases: `binance.exceptions.BinanceOrderException`

`__init__` (*value*)
 Initialize self. See help(type(self)) for accurate signature.

exception `binance.exceptions.BinanceRequestException` (*message*)
 Bases: `Exception`

`__init__` (*message*)
 Initialize self. See help(type(self)) for accurate signature.

exception `binance.exceptions.BinanceWebsocketUnableToConnect`
 Bases: `Exception`

exception `binance.exceptions.NotImplementedException` (*value*)
 Bases: `Exception`

`__init__` (*value*)
 Initialize self. See help(type(self)) for accurate signature.

helpers module

`binance.helpers.convert_ts_str` (*ts_str*)

`binance.helpers.date_to_milliseconds` (*date_str: str*) → int
 Convert UTC date to milliseconds

If using offset strings add “UTC” to date string e.g. “now UTC”, “11 hours ago UTC”

See dateparse docs for formats <http://dateparser.readthedocs.io/en/latest/>

Parameters `date_str` – date in readable format, i.e. “January 01, 2018”, “11 hours ago UTC”, “now UTC”

`binance.helpers.interval_to_milliseconds` (*interval: str*) → Optional[int]

Convert a Binance interval string to milliseconds

Parameters `interval` – Binance interval string, e.g.: 1m, 3m, 5m, 15m, 30m, 1h, 2h, 4h, 6h, 8h, 12h, 1d, 3d, 1w

Returns int value of interval in milliseconds None if interval prefix is not a decimal integer None if interval suffix is not one of m, h, d, w

`binance.helpers.round_step_size` (*quantity*: `Union[float, decimal.Decimal]`, *step_size*: `Union[float, decimal.Decimal]`) → float

Rounds a given quantity to a specific step size

Parameters

- **quantity** – required
- **step_size** – required

Returns decimal

websockets module

class `binance.streams.BinanceSocketManager` (*client*: `binance.client.AsyncClient`, *loop*=None, *user_timeout*=300)

Bases: object

`DSTREAM_TESTNET_URL` = 'wss://dstream.binancefuture.com/'

`DSTREAM_URL` = 'wss://dstream.binance.{}/'

`FSTREAM_TESTNET_URL` = 'wss://stream.binancefuture.com/'

`FSTREAM_URL` = 'wss://stream.binance.{}/'

`STREAM_TESTNET_URL` = 'wss://testnet.binance.vision/'

`STREAM_URL` = 'wss://stream.binance.{}:9443/'

`VSTREAM_TESTNET_URL` = 'wss://testnetws.binanceops.{}/'

`VSTREAM_URL` = 'wss://vstream.binance.{}/'

`WEBSOCKET_DEPTH_10` = '10'

`WEBSOCKET_DEPTH_20` = '20'

`WEBSOCKET_DEPTH_5` = '5'

`__init__` (*client*: `binance.client.AsyncClient`, *loop*=None, *user_timeout*=300)

Initialise the BinanceSocketManager

Parameters `client` (`binance.AsyncClient`) – Binance API client

`aggtrade_futures_socket` (*symbol*: `str`, *futures_type*: `binance.enums.FuturesType` = `<FuturesType.USD_M: 1>`)

Start a websocket for aggregate symbol trade data for the futures stream

Parameters

- **symbol** – required
- **futures_type** – use USD-M or COIN-M futures default USD-M

Returns connection key string if successful, False otherwise

Message Format

```
{
  "e": "aggTrade", // Event type
  "E": 123456789, // Event time
  "s": "BTCUSDT", // Symbol
  "a": 5933014, // Aggregate trade ID
  "p": "0.001", // Price
  "q": "100", // Quantity
}
```

(continues on next page)

(continued from previous page)

```

"f": 100,          // First trade ID
"l": 105,          // Last trade ID
"T": 123456785,   // Trade time
"m": true,        // Is the buyer the market maker?
}

```

aggttrade_socket (*symbol: str*)

Start a websocket for symbol trade data

<https://github.com/binance-exchange/binance-official-api-docs/blob/master/web-socket-streams.md#aggregate-trade-streams>

Parameters **symbol** (*str*) – required**Returns** connection key string if successful, False otherwise

Message Format

```

{
  "e": "aggTrade",          # event type
  "E": 1499405254326,      # event time
  "s": "ETHBTC",          # symbol
  "a": 70232,              # aggregated tradeid
  "p": "0.10281118",      # price
  "q": "8.15632997",      # quantity
  "f": 77489,              # first breakdown trade id
  "l": 77489,              # last breakdown trade id
  "T": 1499405254324,     # trade time
  "m": false,              # whether buyer is a maker
  "M": true                # can be ignored
}

```

all_mark_price_socket (*fast: bool = True, futures_type: binance.enums.FuturesType = <FuturesType.USD_M: 1>*)

Start a websocket for all futures mark price data By default all symbols are included in an array. <https://binance-docs.github.io/apidocs/futures/en/#mark-price-stream-for-all-market> :param fast: use faster or 1s default :param futures_type: use USD-M or COIN-M futures default USD-M :returns: connection key string if successful, False otherwise Message Format .. code-block:: python

```

[
  {
    "e": "markPriceUpdate", // Event type
    "E": 1562305380000, // Event time
    "s": "BTC-CUSDT", // Symbol
    "p": "11185.87786614", // Mark price
    "r": "0.00030000", // Funding rate
    "T": 1562306400000 // Next funding time
  }
]

```

all_ticker_futures_socket (*futures_type: binance.enums.FuturesType = <FuturesType.USD_M: 1>*)

Start a websocket for all ticker data By default all markets are included in an array. <https://binance-docs.github.io/apidocs/futures/en/#all-book-tickers-stream> :param futures_type: use USD-M or COIN-M futures default USD-M :returns: connection key string if successful, False otherwise Message Format .. code-block:: python

```

[
  {
    "u": 400900217, // order book updateId
    "s": "BNBUSDT", // symbol
    "b": "25.35190000", // best bid price
    "B": "31.21000000", // best bid qty
  }
]

```

```

        "a": "25.36520000", // best ask price "A": "40.66000000" // best ask qty
    }
]

```

book_ticker_socket ()

Start a websocket for the best bid or ask's price or quantity for all symbols.

<https://github.com/binance-exchange/binance-official-api-docs/blob/master/web-socket-streams.md#all-book-tickers-stream>

Returns connection key string if successful, False otherwise

Message Format

```

{
    // Same as <symbol>@bookTicker payload
}

```

coin_futures_socket ()

Start a websocket for coin futures data

<https://binance-docs.github.io/apidocs/delivery/en/#websocket-market-streams>

Returns connection key string if successful, False otherwise

Message Format - see Binance API docs for all types

depth_socket (symbol: str, depth: Optional[str] = None, interval: Optional[int] = None)

Start a websocket for symbol market depth returning either a diff or a partial book

<https://github.com/binance-exchange/binance-official-api-docs/blob/master/web-socket-streams.md#partial-book-depth-streams>

Parameters

- **symbol** (*str*) – required
- **depth** (*str*) – optional Number of depth entries to return, default None. If passed returns a partial book instead of a diff
- **interval** (*int*) – optional interval for updates, default None. If not set, updates happen every second. Must be 0, None (1s) or 100 (100ms)

Returns connection key string if successful, False otherwise

Partial Message Format

```

{
    "lastUpdateId": 160, # Last update ID
    "bids": [           # Bids to be updated
        [
            "0.0024", # price level to be updated
            "10",     # quantity
            []        # ignore
        ]
    ],
    "asks": [         # Asks to be updated
        [
            "0.0026", # price level to be updated
            "100",    # quantity
        ]
    ]
}

```

(continues on next page)

(continued from previous page)

```

        [] # ignore
    ]
}

```

Diff Message Format

```

{
  "e": "depthUpdate", # Event type
  "E": 123456789,     # Event time
  "s": "BNBBTC",     # Symbol
  "U": 157,           # First update ID in event
  "u": 160,           # Final update ID in event
  "b": [              # Bids to be updated
    [
      "0.0024",      # price level to be updated
      "10",           # quantity
      []              # ignore
    ]
  ],
  "a": [              # Asks to be updated
    [
      "0.0026",      # price level to be updated
      "100",          # quantity
      []              # ignore
    ]
  ]
}

```

futures_depth_socket (*symbol*: str, *depth*: str = '10', *futures_type*: binance.enums.FuturesType = <FuturesType.USD_M: 1>)

Subscribe to a depth data stream

<https://binance-docs.github.io/apidocs/futures/en/#partial-book-depth-streams>

Parameters

- **symbol** (*str*) – required
- **depth** (*str*) – optional Number of depth entries to return, default 10.

futures_multiplex_socket (*streams*: List[str], *futures_type*: binance.enums.FuturesType = <FuturesType.USD_M: 1>)

Start a multiplexed socket using a list of socket names. User stream sockets can not be included.

Symbols in socket name must be lowercase i.e `bnbbtc@aggTrade`, `neobtc@ticker`

Combined stream events are wrapped as follows: {"stream": "<streamName>","data":<rawPayload>}

<https://github.com/binance-exchange/binance-official-api-docs/blob/master/web-socket-streams.md>

Parameters

- **streams** – list of stream names in lower case
- **futures_type** – use USD-M or COIN-M futures default USD-M

Returns connection key string if successful, False otherwise

Message Format - see Binance API docs for all types

futures_socket ()

Start a websocket for futures data

<https://binance-docs.github.io/apidocs/futures/en/#websocket-market-streams>

Returns connection key string if successful, False otherwise

Message Format - see Binance API docs for all types

futures_user_socket ()

Start a websocket for coin futures user data

<https://binance-docs.github.io/apidocs/futures/en/#user-data-streams>

Returns connection key string if successful, False otherwise

Message Format - see Binanace API docs for all types

index_price_socket (*symbol: str, fast: bool = True*)

Start a websocket for a symbol's futures mark price <https://binance-docs.github.io/apidocs/delivery/en/#index-price-stream> :param symbol: required :param fast: use faster or 1s default :returns: connection key string if successful, False otherwise

Message Format .. code-block:: python

```
{
    "e": "indexPriceUpdate", // Event type "E": 1591261236000, // Event time
    "i": "BTCUSD", // Pair "p": "9636.57860000", // Index Price
}
```

individual_symbol_ticker_futures_socket (*symbol: str, futures_type: binance.enums.FuturesType = <FuturesType.USD_M: 1>*)

Start a futures websocket for a single symbol's ticker data <https://binance-docs.github.io/apidocs/futures/en/#individual-symbol-ticker-streams> :param symbol: required :type symbol: str :param futures_type: use USD-M or COIN-M futures default USD-M :returns: connection key string if successful, False otherwise .. code-block:: python

```
{ "e": "24hrTicker", // Event type "E": 123456789, // Event time "s": "BTCUSDT", //
  Symbol "p": "0.0015", // Price change
}
```

isolated_margin_socket (*symbol: str*)

Start a websocket for isolated margin data

<https://binance-docs.github.io/apidocs/spot/en/#listen-key-isolated-margin>

Parameters **symbol** (*str*) – required - symbol for the isolated margin account

Returns connection key string if successful, False otherwise

Message Format - see Binance API docs for all types

kline_futures_socket (*symbol: str, interval='1m', futures_type: binance.enums.FuturesType = <FuturesType.USD_M: 1>, contract_type: binance.enums.ContractType = <ContractType.PERPETUAL: 'perpetual'>*)

Start a websocket for symbol kline data for the perpeual futures stream

<https://binance-docs.github.io/apidocs/futures/en/#continuous-contract-kline-candlestick-streams>

Parameters

- **symbol** (*str*) – required
- **interval** (*str*) – Kline interval, default KLINE_INTERVAL_1MINUTE
- **futures_type** – use USD-M or COIN-M futures default USD-M
- **contract_type** – use PERPETUAL or CURRENT_QUARTER or NEXT_QUARTER default PERPETUAL

Returns connection key string if successful, False otherwise

Message Format

```
{
  "e": "continuous_kline",      // Event type
  "E": 1607443058651,          // Event time
  "ps": "BTCUSDT",            // Pair
  "ct": "PERPETUAL"           // Contract type
  "k": {
    "t": 1607443020000,         // Kline start time
    "T": 1607443079999,         // Kline close time
    "i": "1m",                 // Interval
    "f": 116467658886,         // First trade ID
    "L": 116468012423,         // Last trade ID
    "o": "18787.00",           // Open price
    "c": "18804.04",           // Close price
    "h": "18804.04",           // High price
    "l": "18786.54",           // Low price
    "v": "197.664",            // volume
    "n": 543,                  // Number of trades
    "x": false,                // Is this kline closed?
    "q": "3715253.19494",      // Quote asset volume
    "V": "184.769",            // Taker buy volume
    "Q": "3472925.84746",      //Taker buy quote asset volume
    "B": "0"                   // Ignore
  }
}
<pair>_<contractType>@continuousKline_<interval>
```

kline_socket (*symbol: str, interval='1m'*)

Start a websocket for symbol kline data

<https://github.com/binance-exchange/binance-official-api-docs/blob/master/web-socket-streams.md#klinecandlestick-streams>

Parameters

- **symbol** (*str*) – required
- **interval** (*str*) – Kline interval, default KLINE_INTERVAL_1MINUTE

Returns connection key string if successful, False otherwise

Message Format

```
{
  "e": "kline",                # event type
  "E": 1499404907056,          # event time
  "s": "ETHBTC",               # symbol
  "k": {
    "t": 1499404860000,         # start time of this bar
    "T": 1499404919999,         # end time of this bar
```

(continues on next page)

(continued from previous page)

```

"s": "ETHBTC", # symbol
"i": "1m", # interval
"f": 77462, # first trade id
"L": 77465, # last trade id
"o": "0.10278577", # open
"c": "0.10278645", # close
"h": "0.10278712", # high
"l": "0.10278518", # low
"v": "17.47929838", # volume
"n": 4, # number of
→trades
"x": false, # whether this bar is
→final
"q": "1.79662878", # quote volume
"V": "2.34879839", # volume of active buy
"Q": "0.24142166", # quote volume of active buy
"B": "13279784.01349473" # can be ignored
}

```

margin_socket ()

Start a websocket for cross-margin data

<https://binance-docs.github.io/apidocs/spot/en/#listen-key-margin>**Returns** connection key string if successful, False otherwise

Message Format - see Binance API docs for all types

miniticker_socket (update_time: int = 1000)

Start a miniticker websocket for all trades

This is not in the official Binance api docs, but this is what feeds the right column on a ticker page on Binance.

Parameters update_time (int) – time between callbacks in milliseconds, must be 1000 or greater**Returns** connection key string if successful, False otherwise

Message Format

```

[
  {
    'e': '24hrMiniTicker', # Event type
    'E': 1515906156273, # Event time
    's': 'QTUMETH', # Symbol
    'c': '0.03836900', # close
    'o': '0.03953500', # open
    'h': '0.04400000', # high
    'l': '0.03756000', # low
    'v': '147435.80000000', # volume
    'q': '5903.84338533' # quote volume
  }
]

```

multiplex_socket (streams: List[str])

Start a multiplexed socket using a list of socket names. User stream sockets can not be included.

Symbols in socket name must be lowercase i.e `bnbbtc@aggTrade`, `neobtc@ticker`

Combined stream events are wrapped as follows: {"stream": "<streamName>", "data": <rawPayload>}

<https://github.com/binance-exchange/binance-official-api-docs/blob/master/web-socket-streams.md>

Parameters **streams** (*list*) – list of stream names in lower case

Returns connection key string if successful, False otherwise

Message Format - see Binance API docs for all types

options_depth_socket (*symbol: str, depth: str = '10'*)

Subscribe to a depth data stream

<https://binance-docs.github.io/apidocs/voptions/en/#market-streams-payload-depth>

Parameters

- **symbol** (*str*) – required
- **depth** (*str*) – optional Number of depth entries to return, default 10.

options_kline_socket (*symbol: str, interval='1m'*)

Subscribe to a candlestick data stream

<https://binance-docs.github.io/apidocs/voptions/en/#market-streams-payload-candle>

Parameters

- **symbol** (*str*) – required
- **interval** (*str*) – Kline interval, default KLINE_INTERVAL_1MINUTE

options_multiplex_socket (*streams: List[str]*)

Start a multiplexed socket using a list of socket names. User stream sockets can not be included.

Symbols in socket name must be lowercase i.e `bnbtc@aggTrade`, `neobtc@ticker`

Combined stream events are wrapped as follows: {"stream": "<streamName>", "data": <rawPayload>}

<https://binance-docs.github.io/apidocs/voptions/en/#account-and-trading-interface>

Parameters **streams** (*list*) – list of stream names in lower case

Returns connection key string if successful, False otherwise

Message Format - see Binance API docs for all types

options_recent_trades_socket (*symbol: str*)

Subscribe to a latest completed trades stream

<https://binance-docs.github.io/apidocs/voptions/en/#market-streams-payload-latest-completed-trades>

Parameters **symbol** (*str*) – required

options_ticker_socket (*symbol: str*)

Subscribe to a 24 hour ticker info stream

<https://binance-docs.github.io/apidocs/voptions/en/#market-streams-payload-24-hour-ticker>

Parameters **symbol** (*str*) – required

symbol_book_ticker_socket (*symbol: str*)

Start a websocket for the best bid or ask's price or quantity for a specified symbol.

<https://github.com/binance-exchange/binance-official-api-docs/blob/master/web-socket-streams.md#individual-symbol-book-ticker-streams>

Parameters **symbol** (*str*) – required

Returns connection key string if successful, False otherwise

Message Format

```
{
  "u":400900217,      // order book updateId
  "s":"BNBUSDT",     // symbol
  "b":"25.35190000", // best bid price
  "B":"31.21000000", // best bid qty
  "a":"25.36520000", // best ask price
  "A":"40.66000000"  // best ask qty
}
```

symbol_mark_price_socket (*symbol*: str, *fast*: bool = True, *futures_type*: *binance.enums.FuturesType* = <*FuturesType*.USD_M: I>)

Start a websocket for a symbol's futures mark price <https://binance-docs.github.io/apidocs/futures/en/#mark-price-stream> :param symbol: required :param fast: use faster or 1s default :param futures_type: use USD-M or COIN-M futures default USD-M :returns: connection key string if successful, False otherwise

Message Format .. code-block:: python

```
{ "e": "markPriceUpdate", // Event type "E": 1562305380000, // Event time "s": "BTCUSD", // Symbol "p": "11185.87786614", // Mark price "r": "0.00030000", // Funding rate "T": 1562306400000 // Next funding time
}
```

symbol_miniticker_socket (*symbol*: str)

Start a websocket for a symbol's miniTicker data

<https://binance-docs.github.io/apidocs/spot/en/#individual-symbol-mini-ticker-stream>

Parameters **symbol** (*str*) – required

Returns connection key string if successful, False otherwise

Message Format

```
{
  "e": "24hrMiniTicker", // Event type
  "E": 123456789,        // Event time
  "s": "BNBBTC",        // Symbol
  "c": "0.0025",        // Close price
  "o": "0.0010",        // Open price
  "h": "0.0025",        // High price
  "l": "0.0010",        // Low price
  "v": "10000",         // Total traded base asset volume
  "q": "18"              // Total traded quote asset volume
}
```

symbol_ticker_futures_socket (*symbol*: str, *futures_type*: *binance.enums.FuturesType* = <*FuturesType*.USD_M: I>)

Start a websocket for a symbol's ticker data By default all markets are included in an array. <https://binance-docs.github.io/apidocs/futures/en/#individual-symbol-book-ticker-streams> :param symbol: required :param futures_type: use USD-M or COIN-M futures default USD-M :returns: connection key string if successful, False otherwise .. code-block:: python

```
[
  { "u":400900217, // order book updateId "s":"BNBUSDT", // symbol
    "b":"25.35190000", // best bid price "B":"31.21000000", // best bid qty
    "a":"25.36520000", // best ask price "A":"40.66000000" // best ask qty
  }
```

```
    }
  ]
}
```

symbol_ticker_socket (*symbol: str*)

Start a websocket for a symbol's ticker data

<https://github.com/binance-exchange/binance-official-api-docs/blob/master/web-socket-streams.md#individual-symbol-ticker-streams>

Parameters **symbol** (*str*) – required

Returns connection key string if successful, False otherwise

Message Format

```
{
  "e": "24hrTicker", # Event type
  "E": 123456789, # Event time
  "s": "BNBBTC", # Symbol
  "p": "0.0015", # Price change
  "P": "250.00", # Price change percent
  "w": "0.0018", # Weighted average price
  "x": "0.0009", # Previous day's close price
  "c": "0.0025", # Current day's close price
  "Q": "10", # Close trade's quantity
  "b": "0.0024", # Best bid price
  "B": "10", # Bid bid quantity
  "a": "0.0026", # Best ask price
  "A": "100", # Best ask quantity
  "o": "0.0010", # Open price
  "h": "0.0025", # High price
  "l": "0.0010", # Low price
  "v": "10000", # Total traded base asset volume
  "q": "18", # Total traded quote asset volume
  "O": 0, # Statistics open time
  "C": 86400000, # Statistics close time
  "F": 0, # First trade ID
  "L": 18150, # Last trade Id
  "n": 18151 # Total number of trades
}
```

ticker_socket ()

Start a websocket for all ticker data

By default all markets are included in an array.

<https://github.com/binance-exchange/binance-official-api-docs/blob/master/web-socket-streams.md#all-market-tickers-stream>

Parameters **coro** (*function*) – callback function to handle messages

Returns connection key string if successful, False otherwise

Message Format

```
[
  {
    'F': 278610,
    'o': '0.07393000',
    's': 'BCCBTC',
    'C': 1509622420916,
  }
]
```

(continues on next page)

(continued from previous page)

```

        'b': '0.07800800',
        'l': '0.07160300',
        'h': '0.08199900',
        'L': 287722,
        'P': '6.694',
        'Q': '0.10000000',
        'q': '1202.67106335',
        'p': '0.00494900',
        'O': 1509536020916,
        'a': '0.07887800',
        'n': 9113,
        'B': '1.00000000',
        'c': '0.07887900',
        'x': '0.07399600',
        'w': '0.07639068',
        'A': '2.41900000',
        'v': '15743.68900000'
    }
]

```

trade_socket (*symbol: str*)

Start a websocket for symbol trade data

<https://github.com/binance-exchange/binance-official-api-docs/blob/master/web-socket-streams.md#trade-streams>

Parameters **symbol** (*str*) – required**Returns** connection key string if successful, False otherwise

Message Format

```

{
    "e": "trade",      # Event type
    "E": 123456789,   # Event time
    "s": "BNBBTC",   # Symbol
    "t": 12345,       # Trade ID
    "p": "0.001",    # Price
    "q": "100",       # Quantity
    "b": 88,          # Buyer order Id
    "a": 50,          # Seller order Id
    "T": 123456785,   # Trade time
    "m": true,        # Is the buyer the market maker?
    "M": true         # Ignore.
}

```

user_socket ()

Start a websocket for user data

<https://github.com/binance-exchange/binance-official-api-docs/blob/master/user-data-stream.md> <https://binance-docs.github.io/apidocs/spot/en/#listen-key-spot>

Returns connection key string if successful, False otherwise

Message Format - see Binance API docs for all types

class binance.streams.BinanceSocketType

Bases: str, enum.Enum

An enumeration.

```

ACCOUNT = 'Account'
COIN_M_FUTURES = 'Coin_M_Futures'
OPTIONS = 'Vanilla_Options'
SPOT = 'Spot'
USD_M_FUTURES = 'USD_M_Futures'

class binance.streams.KeepAliveWebsocket (client: binance.client.AsyncClient, loop, url,
                                          keepalive_type, prefix='ws/', is_binary=False,
                                          exit_coro=None, user_timeout=None)
    Bases: binance.streams.ReconnectingWebsocket
    __init__ (client: binance.client.AsyncClient, loop, url, keepalive_type, prefix='ws/', is_binary=False,
              exit_coro=None, user_timeout=None)
        Initialize self. See help(type(self)) for accurate signature.

class binance.streams.ReconnectingWebsocket (loop, url: str, path: Optional[str] = None,
                                             prefix: str = 'ws/', is_binary: bool = False,
                                             exit_coro=None)
    Bases: object
    MAX_QUEUE_SIZE = 100
    MAX_RECONNECTS = 5
    MAX_RECONNECT_SECONDS = 60
    MIN_RECONNECT_WAIT = 0.1
    NO_MESSAGE_RECONNECT_TIMEOUT = 60
    TIMEOUT = 10
    __init__ (loop, url: str, path: Optional[str] = None, prefix: str = 'ws/', is_binary: bool = False,
              exit_coro=None)
        Initialize self. See help(type(self)) for accurate signature.
    before_reconnect ()
    connect ()
    recv ()

class binance.streams.ThreadedWebsocketManager (api_key: Optional[str] = None,
                                                api_secret: Optional[str] = None,
                                                requests_params: Dict[str, str] = None,
                                                tld: str = 'com', testnet: bool = False)
    Bases: binance.threaded_stream.ThreadedApiManager
    __init__ (api_key: Optional[str] = None, api_secret: Optional[str] = None, requests_params:
              Dict[str, str] = None, tld: str = 'com', testnet: bool = False)
        Initialise the BinanceSocketManager
    start_aggtrade_futures_socket (callback: Callable, symbol: str, futures_type: binance.enums.FuturesType = <FuturesType.USD_M: 1>)
        → str
    start_aggtrade_socket (callback: Callable, symbol: str) → str
    start_all_mark_price_socket (callback: Callable, fast: bool = True, futures_type: binance.enums.FuturesType = <FuturesType.USD_M: 1>)
        → str

```

start_all_ticker_futures_socket (*callback*: Callable, *futures_type*: *binance.enums.FuturesType* = <*FuturesType*.*USD_M: 1*>) → str

start_book_ticker_socket (*callback*: Callable) → str

start_coin_futures_socket (*callback*: Callable) → str

start_depth_socket (*callback*: Callable, *symbol*: str, *depth*: Optional[str] = None, *interval*: Optional[int] = None) → str

start_futures_multiplex_socket (*callback*: Callable, *streams*: List[str], *futures_type*: *binance.enums.FuturesType* = <*FuturesType*.*USD_M: 1*>) → str

start_futures_socket (*callback*: Callable) → str

start_index_price_socket (*callback*: Callable, *symbol*: str, *fast*: bool = True) → str

start_individual_symbol_ticker_futures_socket (*callback*: Callable, *symbol*: str, *futures_type*: *binance.enums.FuturesType* = <*FuturesType*.*USD_M: 1*>) → str

start_isolated_margin_socket (*callback*: Callable, *symbol*: str) → str

start_kline_futures_socket (*callback*: Callable, *symbol*: str, *interval*=*'1m'*, *futures_type*: *binance.enums.FuturesType* = <*FuturesType*.*USD_M: 1*>, *contract_type*: *binance.enums.ContractType* = <*ContractType*.*PERPETUAL: 'perpetual'*>) → str

start_kline_socket (*callback*: Callable, *symbol*: str, *interval*=*'1m'*) → str

start_margin_socket (*callback*: Callable) → str

start_miniticker_socket (*callback*: Callable, *update_time*: int = 1000) → str

start_multiplex_socket (*callback*: Callable, *streams*: List[str]) → str

start_options_depth_socket (*callback*: Callable, *symbol*: str, *depth*: str = *'10'*) → str

start_options_kline_socket (*callback*: Callable, *symbol*: str, *interval*=*'1m'*) → str

start_options_multiplex_socket (*callback*: Callable, *streams*: List[str]) → str

start_options_recent_trades_socket (*callback*: Callable, *symbol*: str) → str

start_options_ticker_socket (*callback*: Callable, *symbol*: str) → str

start_symbol_book_ticker_socket (*callback*: Callable, *symbol*: str) → str

start_symbol_mark_price_socket (*callback*: Callable, *symbol*: str, *fast*: bool = True, *futures_type*: *binance.enums.FuturesType* = <*FuturesType*.*USD_M: 1*>) → str

start_symbol_miniticker_socket (*callback*: Callable, *symbol*: str) → str

start_symbol_ticker_futures_socket (*callback*: Callable, *symbol*: str, *futures_type*: *binance.enums.FuturesType* = <*FuturesType*.*USD_M: 1*>) → str

start_symbol_ticker_socket (*callback*: Callable, *symbol*: str) → str

start_ticker_socket (*callback*: Callable) → str

start_trade_socket (*callback*: Callable, *symbol*: str) → str

start_user_socket (*callback*: Callable) → str

```
class binance.streams.WSListenerState
```

```
    Bases: enum.Enum
```

```
    An enumeration.
```

```
    EXITING = 'Exiting'
```

```
    INITIALISING = 'Initialising'
```

```
    RECONNECTING = 'Reconnecting'
```

```
    STREAMING = 'Streaming'
```

```
binance.streams.random() → x in the interval [0, 1).
```

6.2 Index

- [genindex](#)

b

`binance.client`, 56
`binance.depthcache`, 185
`binance.exceptions`, 188
`binance.helpers`, 189
`binance.streams`, 190

Symbols

__init__() (binance.client.AsyncClient method), 56
 __init__() (binance.client.BaseClient method), 96
 __init__() (binance.client.Client method), 97
 __init__() (binance.depthcache.BaseDepthCacheManager method), 185
 __init__() (binance.depthcache.DepthCache method), 186
 __init__() (binance.depthcache.DepthCacheManager method), 187
 __init__() (binance.depthcache.ThreadedDepthCacheManager method), 188
 __init__() (binance.exceptions.BinanceAPIException method), 188
 __init__() (binance.exceptions.BinanceOrderException method), 188
 __init__() (binance.exceptions.BinanceOrderInactiveSymbolException method), 188
 __init__() (binance.exceptions.BinanceOrderMinAmountException method), 189
 __init__() (binance.exceptions.BinanceOrderMinPriceException method), 189
 __init__() (binance.exceptions.BinanceOrderMinTotalException method), 189
 __init__() (binance.exceptions.BinanceOrderUnknownSymbolException method), 189
 __init__() (binance.exceptions.BinanceRequestException method), 189
 __init__() (binance.exceptions.NotImplementedException method), 189
 __init__() (binance.streams.BinanceSocketManager method), 190
 __init__() (binance.streams.KeepAliveWebsocket method), 201
 __init__() (binance.streams.ReconnectingWebsocket method), 201
 __init__() (binance.streams.ThreadedWebsocketManager method), 201

A

ACCOUNT (binance.streams.BinanceSocketType attribute), 200
 add_ask() (binance.depthcache.DepthCache method), 186
 add_bid() (binance.depthcache.DepthCache method), 186
 AGG_BEST_MATCH (binance.client.BaseClient attribute), 94
 AGG_BUYER_MAKES (binance.client.BaseClient attribute), 94
 AGG_FIRST_TRADE_ID (binance.client.BaseClient attribute), 94
 AGG_ID (binance.client.BaseClient attribute), 94
 AGG_LAST_TRADE_ID (binance.client.BaseClient attribute), 94
 AGG_QUANTITY (binance.client.BaseClient attribute), 94
 AGG_TIME (binance.client.BaseClient attribute), 94
 aggregate_trade_iter() (binance.client.AsyncClient method), 56
 aggregate_trade_iter() (binance.client.Client method), 97
 asyncio_futures_socket() (binance.streams.BinanceSocketManager method), 190
 aggtrade_socket() (binance.streams.BinanceSocketManager method), 191
 all_mark_price_socket() (binance.streams.BinanceSocketManager method), 191
 all_ticker_futures_socket() (binance.streams.BinanceSocketManager method), 191
 API_TESTNET_URL (binance.client.BaseClient attribute), 94
 API_URL (binance.client.BaseClient attribute), 94

AsyncClient (class in *binance.client*), 56

B

BaseClient (class in *binance.client*), 94

BaseDepthCacheManager (class in *binance.depthcache*), 185

before_reconnect () (*binance.streams.ReconnectingWebsocket* method), 201

binance.client (module), 56

binance.depthcache (module), 185

binance.exceptions (module), 188

binance.helpers (module), 189

binance.streams (module), 190

BinanceAPIException, 188

BinanceOrderException, 188

BinanceOrderInactiveSymbolException, 188

BinanceOrderMinAmountException, 188

BinanceOrderMinPriceException, 189

BinanceOrderMinTotalException, 189

BinanceOrderUnknownSymbolException, 189

BinanceRequestException, 189

BinanceSocketManager (class in *binance.streams*), 190

BinanceSocketType (class in *binance.streams*), 200

BinanceWebsocketUnableToConnect, 189

book_ticker_socket () (*binance.streams.BinanceSocketManager* method), 192

C

cancel_margin_oco_order () (*binance.client.AsyncClient* method), 56

cancel_margin_oco_order () (*binance.client.Client* method), 97

cancel_margin_order () (*binance.client.AsyncClient* method), 56

cancel_margin_order () (*binance.client.Client* method), 99

cancel_order () (*binance.client.AsyncClient* method), 56

cancel_order () (*binance.client.Client* method), 99

change_fixed_activity_to_daily_position () (*binance.client.AsyncClient* method), 57

change_fixed_activity_to_daily_position () (*binance.client.Client* method), 100

Client (class in *binance.client*), 96

close () (*binance.depthcache.BaseDepthCacheManager* method), 186

close_connection () (*binance.client.AsyncClient* method), 57

close_connection () (*binance.client.Client* method), 100

COIN_FUTURE_TO_SPOT (*binance.client.BaseClient* attribute), 94

coin_futures_socket () (*binance.streams.BinanceSocketManager* method), 192

COIN_M_FUTURES (*binance.streams.BinanceSocketType* attribute), 201

connect () (*binance.streams.ReconnectingWebsocket* method), 201

convert_ts_str () (in module *binance.helpers*), 189

create () (*binance.client.AsyncClient* class method), 57

create_isolated_margin_account () (*binance.client.AsyncClient* method), 57

create_isolated_margin_account () (*binance.client.Client* method), 100

create_margin_loan () (*binance.client.AsyncClient* method), 57

create_margin_loan () (*binance.client.Client* method), 100

create_margin_oco_order () (*binance.client.AsyncClient* method), 57

create_margin_oco_order () (*binance.client.Client* method), 101

create_margin_order () (*binance.client.AsyncClient* method), 57

create_margin_order () (*binance.client.Client* method), 102

create_oco_order () (*binance.client.AsyncClient* method), 57

create_oco_order () (*binance.client.Client* method), 104

create_order () (*binance.client.AsyncClient* method), 58

create_order () (*binance.client.Client* method), 105

create_sub_account_futures_transfer () (*binance.client.AsyncClient* method), 60

create_sub_account_futures_transfer () (*binance.client.Client* method), 107

create_test_order () (*binance.client.AsyncClient* method), 60

create_test_order () (*binance.client.Client* method), 108

D

date_to_milliseconds () (in module *binance.helpers*), 189

DEFAULT_REFRESH (*binance.depthcache.BaseDepthCacheManager* attribute), 185

depth_socket () (*binance.streams.BinanceSocketManager* method), 192

- DepthCache (class in *binance.depthcache*), 186
- DepthCacheManager (class in *binance.depthcache*), 187
- `disable_fast_withdraw_switch()` (*binance.client.AsyncClient* method), 61
- `disable_fast_withdraw_switch()` (*binance.client.Client* method), 108
- `disable_isolated_margin_account()` (*binance.client.AsyncClient* method), 61
- `disable_isolated_margin_account()` (*binance.client.Client* method), 108
- DSTREAM_TESTNET_URL (*binance.streams.BinanceSocketManager* attribute), 190
- DSTREAM_URL (*binance.streams.BinanceSocketManager* attribute), 190
- ## E
- `enable_fast_withdraw_switch()` (*binance.client.AsyncClient* method), 61
- `enable_fast_withdraw_switch()` (*binance.client.Client* method), 109
- `enable_isolated_margin_account()` (*binance.client.AsyncClient* method), 61
- `enable_isolated_margin_account()` (*binance.client.Client* method), 109
- `enable_subaccount_futures()` (*binance.client.AsyncClient* method), 61
- `enable_subaccount_futures()` (*binance.client.Client* method), 109
- `enable_subaccount_margin()` (*binance.client.AsyncClient* method), 61
- `enable_subaccount_margin()` (*binance.client.Client* method), 109
- EXITING (*binance.streams.WSListenerState* attribute), 203
- ## F
- FIAT_TO_MINING (*binance.client.BaseClient* attribute), 94
- FIAT_TO_SPOT (*binance.client.BaseClient* attribute), 94
- FIAT_TO_USDT_FUTURE (*binance.client.BaseClient* attribute), 94
- FSTREAM_TESTNET_URL (*binance.streams.BinanceSocketManager* attribute), 190
- FSTREAM_URL (*binance.streams.BinanceSocketManager* attribute), 190
- FUTURE_ORDER_TYPE_LIMIT (*binance.client.BaseClient* attribute), 94
- FUTURE_ORDER_TYPE_LIMIT_MAKER (*binance.client.BaseClient* attribute), 94
- FUTURE_ORDER_TYPE_MARKET (*binance.client.BaseClient* attribute), 94
- FUTURE_ORDER_TYPE_STOP (*binance.client.BaseClient* attribute), 94
- FUTURE_ORDER_TYPE_STOP_MARKET (*binance.client.BaseClient* attribute), 94
- FUTURE_ORDER_TYPE_TAKE_PROFIT (*binance.client.BaseClient* attribute), 94
- FUTURE_ORDER_TYPE_TAKE_PROFIT_MARKET (*binance.client.BaseClient* attribute), 95
- `futures_account()` (*binance.client.AsyncClient* method), 61
- `futures_account()` (*binance.client.Client* method), 110
- `futures_account_balance()` (*binance.client.AsyncClient* method), 61
- `futures_account_balance()` (*binance.client.Client* method), 110
- `futures_account_trades()` (*binance.client.AsyncClient* method), 61
- `futures_account_trades()` (*binance.client.Client* method), 110
- `futures_account_transfer()` (*binance.client.AsyncClient* method), 61
- `futures_account_transfer()` (*binance.client.Client* method), 110
- `futures_adl_quantile_estimate()` (*binance.client.AsyncClient* method), 61
- `futures_adl_quantile_estimate()` (*binance.client.Client* method), 110
- `futures_aggregate_trades()` (*binance.client.AsyncClient* method), 61
- `futures_aggregate_trades()` (*binance.client.Client* method), 110
- FUTURES_API_VERSION (*binance.client.BaseClient* attribute), 94
- FUTURES_API_VERSION2 (*binance.client.BaseClient* attribute), 94
- `futures_cancel_all_open_orders()` (*binance.client.AsyncClient* method), 61
- `futures_cancel_all_open_orders()` (*binance.client.Client* method), 110
- `futures_cancel_order()` (*binance.client.AsyncClient* method), 61
- `futures_cancel_order()` (*binance.client.Client* method), 110
- `futures_cancel_orders()` (*binance.client.AsyncClient* method), 61
- `futures_cancel_orders()` (*binance.client.Client* method), 110
- `futures_change_leverage()` (*binance.client.AsyncClient* method), 61
- `futures_change_leverage()` (*binance.client.Client* method), 111

<code>futures_change_margin_type()</code> (<i>binance.client.AsyncClient method</i>), 61	(bi- <code>futures_coin_change_position_margin()</code> (<i>binance.client.Client method</i>), 112
<code>futures_change_margin_type()</code> (<i>binance.client.Client method</i>), 111	(bi- <code>futures_coin_change_position_mode()</code> (<i>binance.client.AsyncClient method</i>), 61
<code>futures_change_multi_assets_mode()</code> (<i>binance.client.AsyncClient method</i>), 61	<code>futures_coin_change_position_mode()</code> (<i>binance.client.Client method</i>), 112
<code>futures_change_multi_assets_mode()</code> (<i>binance.client.Client method</i>), 111	<code>futures_coin_continuous_klines()</code> (<i>binance.client.AsyncClient method</i>), 61
<code>futures_change_position_margin()</code> (<i>binance.client.AsyncClient method</i>), 61	(bi- <code>futures_coin_continuous_klines()</code> (<i>binance.client.Client method</i>), 112
<code>futures_change_position_margin()</code> (<i>binance.client.Client method</i>), 111	(bi- <code>futures_coin_create_order()</code> (<i>binance.client.AsyncClient method</i>), 61
<code>futures_change_position_mode()</code> (<i>binance.client.AsyncClient method</i>), 61	(bi- <code>futures_coin_create_order()</code> (<i>binance.client.Client method</i>), 112
<code>futures_change_position_mode()</code> (<i>binance.client.Client method</i>), 111	(bi- <code>FUTURES_COIN_DATA_TESTNET_URL</code> (<i>binance.client.BaseClient attribute</i>), 94
<code>futures_coin_account()</code> (<i>binance.client.AsyncClient method</i>), 61	(bi- <code>FUTURES_COIN_DATA_URL</code> (<i>binance.client.BaseClient attribute</i>), 94
<code>futures_coin_account()</code> (<i>binance.client.Client method</i>), 111	<code>futures_coin_exchange_info()</code> (<i>binance.client.AsyncClient method</i>), 61
<code>futures_coin_account_balance()</code> (<i>binance.client.AsyncClient method</i>), 61	(bi- <code>futures_coin_exchange_info()</code> (<i>binance.client.Client method</i>), 112
<code>futures_coin_account_balance()</code> (<i>binance.client.Client method</i>), 111	(bi- <code>futures_coin_funding_rate()</code> (<i>binance.client.AsyncClient method</i>), 62
<code>futures_coin_account_trades()</code> (<i>binance.client.AsyncClient method</i>), 61	(bi- <code>futures_coin_funding_rate()</code> (<i>binance.client.Client method</i>), 112
<code>futures_coin_account_trades()</code> (<i>binance.client.Client method</i>), 111	(bi- <code>futures_coin_get_all_orders()</code> (<i>binance.client.AsyncClient method</i>), 62
<code>futures_coin_aggregate_trades()</code> (<i>binance.client.AsyncClient method</i>), 61	(bi- <code>futures_coin_get_all_orders()</code> (<i>binance.client.Client method</i>), 112
<code>futures_coin_aggregate_trades()</code> (<i>binance.client.Client method</i>), 111	(bi- <code>futures_coin_get_open_orders()</code> (<i>binance.client.AsyncClient method</i>), 62
<code>futures_coin_cancel_all_open_orders()</code> (<i>binance.client.AsyncClient method</i>), 61	<code>futures_coin_get_open_orders()</code> (<i>binance.client.Client method</i>), 112
<code>futures_coin_cancel_all_open_orders()</code> (<i>binance.client.Client method</i>), 111	<code>futures_coin_get_order()</code> (<i>binance.client.AsyncClient method</i>), 62
<code>futures_coin_cancel_order()</code> (<i>binance.client.AsyncClient method</i>), 61	(bi- <code>futures_coin_get_order()</code> (<i>binance.client.Client method</i>), 112
<code>futures_coin_cancel_order()</code> (<i>binance.client.Client method</i>), 111	(bi- <code>futures_coin_get_position_mode()</code> (<i>binance.client.AsyncClient method</i>), 62
<code>futures_coin_cancel_orders()</code> (<i>binance.client.AsyncClient method</i>), 61	(bi- <code>futures_coin_get_position_mode()</code> (<i>binance.client.Client method</i>), 112
<code>futures_coin_cancel_orders()</code> (<i>binance.client.Client method</i>), 111	(bi- <code>futures_coin_historical_trades()</code> (<i>binance.client.AsyncClient method</i>), 62
<code>futures_coin_change_leverage()</code> (<i>binance.client.AsyncClient method</i>), 61	(bi- <code>futures_coin_historical_trades()</code> (<i>binance.client.Client method</i>), 112
<code>futures_coin_change_leverage()</code> (<i>binance.client.Client method</i>), 111	(bi- <code>futures_coin_income_history()</code> (<i>binance.client.AsyncClient method</i>), 62
<code>futures_coin_change_margin_type()</code> (<i>binance.client.AsyncClient method</i>), 61	(bi- <code>futures_coin_income_history()</code> (<i>binance.client.Client method</i>), 112
<code>futures_coin_change_margin_type()</code> (<i>binance.client.Client method</i>), 112	(bi- <code>futures_coin_index_price_klines()</code> (<i>binance.client.AsyncClient method</i>), 62
<code>futures_coin_change_position_margin()</code> (<i>binance.client.AsyncClient method</i>), 61	<code>futures_coin_index_price_klines()</code> (<i>binance.client.Client method</i>), 113

futures_coin_klines() (binance.client.AsyncClient method), 62	(bi-	futures_coin_recent_trades() (binance.client.Client method), 114	(bi-
futures_coin_klines() (binance.client.Client method), 113		futures_coin_stream_close() (binance.client.AsyncClient method), 62	(bi-
futures_coin_leverage_bracket() (binance.client.AsyncClient method), 62	(bi-	futures_coin_stream_close() (binance.client.Client method), 114	(bi-
futures_coin_leverage_bracket() (binance.client.Client method), 113	(bi-	futures_coin_stream_get_listen_key() (binance.client.AsyncClient method), 62	
futures_coin_liquidation_orders() (binance.client.AsyncClient method), 62	(bi-	futures_coin_stream_get_listen_key() (binance.client.Client method), 114	
futures_coin_liquidation_orders() (binance.client.Client method), 113	(bi-	futures_coin_stream_keepalive() (binance.client.AsyncClient method), 62	(bi-
futures_coin_mark_price() (binance.client.AsyncClient method), 62	(bi-	futures_coin_stream_keepalive() (binance.client.Client method), 114	(bi-
futures_coin_mark_price() (binance.client.Client method), 113	(bi-	futures_coin_symbol_ticker() (binance.client.AsyncClient method), 62	(bi-
futures_coin_mark_price_klines() (binance.client.AsyncClient method), 62	(bi-	futures_coin_symbol_ticker() (binance.client.Client method), 114	(bi-
futures_coin_mark_price_klines() (binance.client.Client method), 113	(bi-	FUTURES_COIN_TESTNET_URL (binance.client.BaseClient attribute), 94	(bi-
futures_coin_open_interest() (binance.client.AsyncClient method), 62	(bi-	futures_coin_ticker() (binance.client.AsyncClient method), 62	(bi-
futures_coin_open_interest() (binance.client.Client method), 113	(bi-	futures_coin_ticker() (binance.client.Client method), 114	
futures_coin_open_interest_hist() (binance.client.AsyncClient method), 62	(bi-	futures_coin_time() (binance.client.AsyncClient method), 62	
futures_coin_open_interest_hist() (binance.client.Client method), 113	(bi-	futures_coin_time() (binance.client.Client method), 114	
futures_coin_order_book() (binance.client.AsyncClient method), 62	(bi-	FUTURES_COIN_URL (binance.client.BaseClient attribute), 94	
futures_coin_order_book() (binance.client.Client method), 113	(bi-	futures_continuous_klines() (binance.client.AsyncClient method), 62	(bi-
futures_coin_orderbook_ticker() (binance.client.AsyncClient method), 62	(bi-	futures_continuous_klines() (binance.client.Client method), 114	(bi-
futures_coin_orderbook_ticker() (binance.client.Client method), 113	(bi-	futures_create_order() (binance.client.AsyncClient method), 62	(bi-
futures_coin_ping() (binance.client.AsyncClient method), 62		futures_create_order() (binance.client.Client method), 114	
futures_coin_ping() (binance.client.Client method), 113		FUTURES_DATA_TESTNET_URL (binance.client.BaseClient attribute), 94	(bi-
futures_coin_place_batch_order() (binance.client.AsyncClient method), 62	(bi-	FUTURES_DATA_URL (binance.client.BaseClient attribute), 94	
futures_coin_place_batch_order() (binance.client.Client method), 113	(bi-	futures_depth_socket() (binance.streams.BinanceSocketManager method), 193	(bi-
futures_coin_position_information() (binance.client.AsyncClient method), 62	(bi-	futures_exchange_info() (binance.client.AsyncClient method), 62	(bi-
futures_coin_position_information() (binance.client.Client method), 113	(bi-	futures_exchange_info() (binance.client.Client method), 114	
futures_coin_position_margin_history() (binance.client.AsyncClient method), 62		futures_funding_rate() (binance.client.AsyncClient method), 62	(bi-
futures_coin_position_margin_history() (binance.client.Client method), 114		futures_funding_rate() (binance.client.Client method), 114	(bi-
futures_coin_recent_trades() (binance.client.AsyncClient method), 62	(bi-	futures_get_all_orders() (bin-	

binance.client.AsyncClient method), 62
 futures_get_all_orders() (*binance.client.Client method*), 114
 futures_get_multi_assets_mode() (*binance.client.AsyncClient method*), 62
 futures_get_multi_assets_mode() (*binance.client.Client method*), 114
 futures_get_open_orders() (*binance.client.AsyncClient method*), 62
 futures_get_open_orders() (*binance.client.Client method*), 114
 futures_get_order() (*binance.client.AsyncClient method*), 62
 futures_get_order() (*binance.client.Client method*), 115
 futures_get_position_mode() (*binance.client.AsyncClient method*), 63
 futures_get_position_mode() (*binance.client.Client method*), 115
 futures_global_longshort_ratio() (*binance.client.AsyncClient method*), 63
 futures_global_longshort_ratio() (*binance.client.Client method*), 115
 futures_historical_klines() (*binance.client.AsyncClient method*), 63
 futures_historical_klines() (*binance.client.Client method*), 115
 futures_historical_klines_generator() (*binance.client.AsyncClient method*), 63
 futures_historical_klines_generator() (*binance.client.Client method*), 115
 futures_historical_trades() (*binance.client.AsyncClient method*), 63
 futures_historical_trades() (*binance.client.Client method*), 115
 futures_income_history() (*binance.client.AsyncClient method*), 63
 futures_income_history() (*binance.client.Client method*), 115
 futures_klines() (*binance.client.AsyncClient method*), 63
 futures_klines() (*binance.client.Client method*), 115
 futures_leverage_bracket() (*binance.client.AsyncClient method*), 63
 futures_leverage_bracket() (*binance.client.Client method*), 115
 futures_liquidation_orders() (*binance.client.AsyncClient method*), 63
 futures_liquidation_orders() (*binance.client.Client method*), 116
 futures_mark_price() (*binance.client.AsyncClient method*), 63
 futures_mark_price() (*binance.client.Client method*), 116
 futures_multiplex_socket() (*binance.streams.BinanceSocketManager method*), 193
 futures_open_interest() (*binance.client.AsyncClient method*), 63
 futures_open_interest() (*binance.client.Client method*), 116
 futures_open_interest_hist() (*binance.client.AsyncClient method*), 63
 futures_open_interest_hist() (*binance.client.Client method*), 116
 futures_order_book() (*binance.client.AsyncClient method*), 63
 futures_order_book() (*binance.client.Client method*), 116
 futures_orderbook_ticker() (*binance.client.AsyncClient method*), 63
 futures_orderbook_ticker() (*binance.client.Client method*), 116
 futures_ping() (*binance.client.AsyncClient method*), 63
 futures_ping() (*binance.client.Client method*), 116
 futures_place_batch_order() (*binance.client.AsyncClient method*), 63
 futures_place_batch_order() (*binance.client.Client method*), 116
 futures_position_information() (*binance.client.AsyncClient method*), 63
 futures_position_information() (*binance.client.Client method*), 116
 futures_position_margin_history() (*binance.client.AsyncClient method*), 63
 futures_position_margin_history() (*binance.client.Client method*), 116
 futures_recent_trades() (*binance.client.AsyncClient method*), 63
 futures_recent_trades() (*binance.client.Client method*), 116
 futures_socket() (*binance.streams.BinanceSocketManager method*), 193
 futures_stream_close() (*binance.client.AsyncClient method*), 63
 futures_stream_close() (*binance.client.Client method*), 116
 futures_stream_get_listen_key() (*binance.client.AsyncClient method*), 63
 futures_stream_get_listen_key() (*binance.client.Client method*), 116
 futures_stream_keepalive() (*binance.client.AsyncClient method*), 63
 futures_stream_keepalive() (*binance.client.Client method*), 116

- futures_symbol_ticker() (*binance.client.AsyncClient method*), 63
- futures_symbol_ticker() (*binance.client.Client method*), 117
- FUTURES_TESTNET_URL (*binance.client.BaseClient attribute*), 94
- futures_ticker() (*binance.client.AsyncClient method*), 63
- futures_ticker() (*binance.client.Client method*), 117
- futures_time() (*binance.client.AsyncClient method*), 63
- futures_time() (*binance.client.Client method*), 117
- futures_top_longshort_account_ratio() (*binance.client.AsyncClient method*), 63
- futures_top_longshort_account_ratio() (*binance.client.Client method*), 117
- futures_top_longshort_position_ratio() (*binance.client.AsyncClient method*), 63
- futures_top_longshort_position_ratio() (*binance.client.Client method*), 117
- FUTURES_URL (*binance.client.BaseClient attribute*), 94
- futures_user_socket() (*binance.streams.BinanceSocketManager method*), 194
- FuturesDepthCacheManager (*class in binance.depthcache*), 188
- ## G
- get_account() (*binance.client.AsyncClient method*), 63
- get_account() (*binance.client.Client method*), 117
- get_account_api_permissions() (*binance.client.AsyncClient method*), 64
- get_account_api_permissions() (*binance.client.Client method*), 117
- get_account_api_trading_status() (*binance.client.AsyncClient method*), 64
- get_account_api_trading_status() (*binance.client.Client method*), 118
- get_account_snapshot() (*binance.client.AsyncClient method*), 65
- get_account_snapshot() (*binance.client.Client method*), 119
- get_account_status() (*binance.client.AsyncClient method*), 66
- get_account_status() (*binance.client.Client method*), 121
- get_aggregate_trades() (*binance.client.AsyncClient method*), 66
- get_aggregate_trades() (*binance.client.Client method*), 121
- get_all_coins_info() (*binance.client.AsyncClient method*), 66
- get_all_coins_info() (*binance.client.Client method*), 122
- get_all_isolated_margin_symbols() (*binance.client.AsyncClient method*), 66
- get_all_isolated_margin_symbols() (*binance.client.Client method*), 123
- get_all_margin_orders() (*binance.client.AsyncClient method*), 66
- get_all_margin_orders() (*binance.client.Client method*), 124
- get_all_orders() (*binance.client.AsyncClient method*), 66
- get_all_orders() (*binance.client.Client method*), 124
- get_all_tickers() (*binance.client.AsyncClient method*), 67
- get_all_tickers() (*binance.client.Client method*), 125
- get_asks() (*binance.depthcache.DepthCache method*), 186
- get_asset_balance() (*binance.client.AsyncClient method*), 67
- get_asset_balance() (*binance.client.Client method*), 125
- get_asset_details() (*binance.client.AsyncClient method*), 68
- get_asset_details() (*binance.client.Client method*), 126
- get_asset_dividend_history() (*binance.client.AsyncClient method*), 68
- get_asset_dividend_history() (*binance.client.Client method*), 126
- get_avg_price() (*binance.client.AsyncClient method*), 69
- get_avg_price() (*binance.client.Client method*), 127
- get_bids() (*binance.depthcache.DepthCache method*), 187
- get_bnb_burn_spot_margin() (*binance.client.AsyncClient method*), 69
- get_bnb_burn_spot_margin() (*binance.client.Client method*), 127
- get_c2c_trade_history() (*binance.client.AsyncClient method*), 69
- get_c2c_trade_history() (*binance.client.Client method*), 127
- get_deposit_address() (*binance.client.AsyncClient method*), 69
- get_deposit_address() (*binance.client.Client method*), 128
- get_deposit_history() (*binance.client.AsyncClient method*), 70
- get_deposit_history() (*binance.client.Client method*), 128

`get_depth_cache()` (*binance.depthcache.BaseDepthCacheManager method*), 186
`get_dust_log()` (*binance.client.AsyncClient method*), 70
`get_dust_log()` (*binance.client.Client method*), 129
`get_exchange_info()` (*binance.client.AsyncClient method*), 72
`get_exchange_info()` (*binance.client.Client method*), 130
`get_fiat_deposit_withdraw_history()` (*binance.client.AsyncClient method*), 73
`get_fiat_deposit_withdraw_history()` (*binance.client.Client method*), 131
`get_fiat_payments_history()` (*binance.client.AsyncClient method*), 73
`get_fiat_payments_history()` (*binance.client.Client method*), 132
`get_fixed_activity_project_list()` (*binance.client.AsyncClient method*), 73
`get_fixed_activity_project_list()` (*binance.client.Client method*), 132
`get_historical_klines()` (*binance.client.AsyncClient method*), 73
`get_historical_klines()` (*binance.client.Client method*), 133
`get_historical_klines_generator()` (*binance.client.AsyncClient method*), 73
`get_historical_klines_generator()` (*binance.client.Client method*), 133
`get_historical_trades()` (*binance.client.AsyncClient method*), 73
`get_historical_trades()` (*binance.client.Client method*), 133
`get_isolated_margin_account()` (*binance.client.AsyncClient method*), 74
`get_isolated_margin_account()` (*binance.client.Client method*), 134
`get_isolated_margin_symbol()` (*binance.client.AsyncClient method*), 74
`get_isolated_margin_symbol()` (*binance.client.Client method*), 136
`get_klines()` (*binance.client.AsyncClient method*), 74
`get_klines()` (*binance.client.Client method*), 136
`get_lending_account()` (*binance.client.AsyncClient method*), 75
`get_lending_account()` (*binance.client.Client method*), 137
`get_lending_daily_quota_left()` (*binance.client.AsyncClient method*), 75
`get_lending_daily_quota_left()` (*binance.client.Client method*), 137
`get_lending_daily_redemption_quota()` (*binance.client.AsyncClient method*), 75
`get_lending_daily_redemption_quota()` (*binance.client.Client method*), 137
`get_lending_interest_history()` (*binance.client.AsyncClient method*), 75
`get_lending_interest_history()` (*binance.client.Client method*), 137
`get_lending_position()` (*binance.client.AsyncClient method*), 75
`get_lending_position()` (*binance.client.Client method*), 137
`get_lending_product_list()` (*binance.client.AsyncClient method*), 75
`get_lending_product_list()` (*binance.client.Client method*), 137
`get_lending_purchase_history()` (*binance.client.AsyncClient method*), 75
`get_lending_purchase_history()` (*binance.client.Client method*), 137
`get_lending_redemption_history()` (*binance.client.AsyncClient method*), 75
`get_lending_redemption_history()` (*binance.client.Client method*), 137
`get_margin_account()` (*binance.client.AsyncClient method*), 75
`get_margin_account()` (*binance.client.Client method*), 137
`get_margin_all_assets()` (*binance.client.AsyncClient method*), 76
`get_margin_all_assets()` (*binance.client.Client method*), 138
`get_margin_all_pairs()` (*binance.client.AsyncClient method*), 76
`get_margin_all_pairs()` (*binance.client.Client method*), 139
`get_margin_asset()` (*binance.client.AsyncClient method*), 76
`get_margin_asset()` (*binance.client.Client method*), 140
`get_margin_force_liquidation_rec()` (*binance.client.AsyncClient method*), 76
`get_margin_force_liquidation_rec()` (*binance.client.Client method*), 140
`get_margin_interest_history()` (*binance.client.AsyncClient method*), 76
`get_margin_interest_history()` (*binance.client.Client method*), 140
`get_margin_loan_details()` (*binance.client.AsyncClient method*), 76
`get_margin_loan_details()` (*binance.client.Client method*), 141
`get_margin_oco_order()` (*binance.client.AsyncClient method*), 76
`get_margin_oco_order()` (*binance.client.Client method*), 141

method), 142
get_margin_order() (*binance.client.AsyncClient method*), 76
get_margin_order() (*binance.client.Client method*), 142
get_margin_price_index() (*binance.client.AsyncClient method*), 76
get_margin_price_index() (*binance.client.Client method*), 143
get_margin_repay_details() (*binance.client.AsyncClient method*), 76
get_margin_repay_details() (*binance.client.Client method*), 143
get_margin_symbol() (*binance.client.AsyncClient method*), 76
get_margin_symbol() (*binance.client.Client method*), 144
get_margin_trades() (*binance.client.AsyncClient method*), 76
get_margin_trades() (*binance.client.Client method*), 144
get_max_margin_loan() (*binance.client.AsyncClient method*), 76
get_max_margin_loan() (*binance.client.Client method*), 145
get_max_margin_transfer() (*binance.client.AsyncClient method*), 76
get_max_margin_transfer() (*binance.client.Client method*), 145
get_my_trades() (*binance.client.AsyncClient method*), 76
get_my_trades() (*binance.client.Client method*), 146
get_open_margin_oco_orders() (*binance.client.AsyncClient method*), 77
get_open_margin_oco_orders() (*binance.client.Client method*), 146
get_open_margin_orders() (*binance.client.AsyncClient method*), 77
get_open_margin_orders() (*binance.client.Client method*), 147
get_open_orders() (*binance.client.AsyncClient method*), 77
get_open_orders() (*binance.client.Client method*), 148
get_order() (*binance.client.AsyncClient method*), 77
get_order() (*binance.client.Client method*), 148
get_order_book() (*binance.client.AsyncClient method*), 78
get_order_book() (*binance.client.Client method*), 149
get_orderbook_ticker() (*binance.client.AsyncClient method*), 78
get_orderbook_ticker() (*binance.client.Client method*), 149
get_orderbook_tickers() (*binance.client.AsyncClient method*), 79
get_orderbook_tickers() (*binance.client.Client method*), 150
get_products() (*binance.client.AsyncClient method*), 80
get_products() (*binance.client.Client method*), 151
get_recent_trades() (*binance.client.AsyncClient method*), 80
get_recent_trades() (*binance.client.Client method*), 151
get_server_time() (*binance.client.AsyncClient method*), 80
get_server_time() (*binance.client.Client method*), 151
get_sub_account_assets() (*binance.client.AsyncClient method*), 80
get_sub_account_assets() (*binance.client.Client method*), 151
get_sub_account_futures_transfer_history() (*binance.client.AsyncClient method*), 80
get_sub_account_futures_transfer_history() (*binance.client.Client method*), 152
get_sub_account_list() (*binance.client.AsyncClient method*), 80
get_sub_account_list() (*binance.client.Client method*), 153
get_sub_account_transfer_history() (*binance.client.AsyncClient method*), 81
get_sub_account_transfer_history() (*binance.client.Client method*), 153
get_subaccount_deposit_address() (*binance.client.AsyncClient method*), 81
get_subaccount_deposit_address() (*binance.client.Client method*), 154
get_subaccount_deposit_history() (*binance.client.AsyncClient method*), 81
get_subaccount_deposit_history() (*binance.client.Client method*), 155
get_subaccount_futures_details() (*binance.client.AsyncClient method*), 81
get_subaccount_futures_details() (*binance.client.Client method*), 156
get_subaccount_futures_margin_status() (*binance.client.AsyncClient method*), 81
get_subaccount_futures_margin_status() (*binance.client.Client method*), 156
get_subaccount_futures_positionrisk() (*binance.client.AsyncClient method*), 81
get_subaccount_futures_positionrisk() (*binance.client.Client method*), 157
get_subaccount_futures_summary() (*binance.client.AsyncClient method*), 81

- `get_subaccount_futures_summary()` (*binance.client.Client method*), 157
`get_subaccount_margin_details()` (*binance.client.AsyncClient method*), 81
`get_subaccount_margin_details()` (*binance.client.Client method*), 158
`get_subaccount_margin_summary()` (*binance.client.AsyncClient method*), 81
`get_subaccount_margin_summary()` (*binance.client.Client method*), 159
`get_subaccount_transfer_history()` (*binance.client.AsyncClient method*), 81
`get_subaccount_transfer_history()` (*binance.client.Client method*), 160
`get_symbol()` (*binance.depthcache.BaseDepthCacheManager method*), 186
`get_symbol_info()` (*binance.client.AsyncClient method*), 81
`get_symbol_info()` (*binance.client.Client method*), 161
`get_symbol_ticker()` (*binance.client.AsyncClient method*), 81
`get_symbol_ticker()` (*binance.client.Client method*), 161
`get_system_status()` (*binance.client.AsyncClient method*), 82
`get_system_status()` (*binance.client.Client method*), 162
`get_ticker()` (*binance.client.AsyncClient method*), 82
`get_ticker()` (*binance.client.Client method*), 162
`get_trade_fee()` (*binance.client.AsyncClient method*), 83
`get_trade_fee()` (*binance.client.Client method*), 163
`get_universal_transfer_history()` (*binance.client.AsyncClient method*), 83
`get_universal_transfer_history()` (*binance.client.Client method*), 163
`get_withdraw_history()` (*binance.client.AsyncClient method*), 84
`get_withdraw_history()` (*binance.client.Client method*), 164
`get_withdraw_history_id()` (*binance.client.AsyncClient method*), 84
`get_withdraw_history_id()` (*binance.client.Client method*), 165
- I**
`index_price_socket()` (*binance.streams.BinanceSocketManager method*), 194
`individual_symbol_ticker_futures_socket()` (*binance.streams.BinanceSocketManager method*), 194
`INITIALISING` (*binance.streams.WSListenerState attribute*), 203
`interval_to_milliseconds()` (*in module binance.helpers*), 189
`isolated_margin_socket()` (*binance.streams.BinanceSocketManager method*), 194
`isolated_margin_stream_close()` (*binance.client.AsyncClient method*), 85
`isolated_margin_stream_close()` (*binance.client.Client method*), 166
`isolated_margin_stream_get_listen_key()` (*binance.client.AsyncClient method*), 85
`isolated_margin_stream_get_listen_key()` (*binance.client.Client method*), 166
`isolated_margin_stream_keepalive()` (*binance.client.AsyncClient method*), 85
`isolated_margin_stream_keepalive()` (*binance.client.Client method*), 166
- K**
`KeepAliveWebsocket` (*class in binance.streams*), 201
`kline_futures_socket()` (*binance.streams.BinanceSocketManager method*), 194
`KLINE_INTERVAL_12HOUR` (*binance.client.BaseClient attribute*), 95
`KLINE_INTERVAL_15MINUTE` (*binance.client.BaseClient attribute*), 95
`KLINE_INTERVAL_1DAY` (*binance.client.BaseClient attribute*), 95
`KLINE_INTERVAL_1HOUR` (*binance.client.BaseClient attribute*), 95
`KLINE_INTERVAL_1MINUTE` (*binance.client.BaseClient attribute*), 95
`KLINE_INTERVAL_1MONTH` (*binance.client.BaseClient attribute*), 95
`KLINE_INTERVAL_1WEEK` (*binance.client.BaseClient attribute*), 95
`KLINE_INTERVAL_2HOUR` (*binance.client.BaseClient attribute*), 95
`KLINE_INTERVAL_30MINUTE` (*binance.client.BaseClient attribute*), 95
`KLINE_INTERVAL_3DAY` (*binance.client.BaseClient attribute*), 95
`KLINE_INTERVAL_3MINUTE` (*binance.client.BaseClient attribute*), 95
`KLINE_INTERVAL_4HOUR` (*binance.client.BaseClient attribute*), 95
`KLINE_INTERVAL_5MINUTE` (*binance.client.BaseClient attribute*), 95

- KLINE_INTERVAL_6HOUR (*binance.client.BaseClient attribute*), 95
- KLINE_INTERVAL_8HOUR (*binance.client.BaseClient attribute*), 95
- kline_socket() (*binance.streams.BinanceSocketManager method*), 195
- ## M
- make_subaccount_futures_transfer() (*binance.client.AsyncClient method*), 85
- make_subaccount_futures_transfer() (*binance.client.Client method*), 166
- make_subaccount_margin_transfer() (*binance.client.AsyncClient method*), 85
- make_subaccount_margin_transfer() (*binance.client.Client method*), 167
- make_subaccount_to_master_transfer() (*binance.client.AsyncClient method*), 85
- make_subaccount_to_master_transfer() (*binance.client.Client method*), 167
- make_subaccount_to_subaccount_transfer() (*binance.client.AsyncClient method*), 85
- make_subaccount_to_subaccount_transfer() (*binance.client.Client method*), 168
- make_subaccount_universal_transfer() (*binance.client.AsyncClient method*), 85
- make_subaccount_universal_transfer() (*binance.client.Client method*), 168
- make_universal_transfer() (*binance.client.AsyncClient method*), 85
- make_universal_transfer() (*binance.client.Client method*), 168
- MARGIN_API_URL (*binance.client.BaseClient attribute*), 95
- MARGIN_API_VERSION (*binance.client.BaseClient attribute*), 95
- MARGIN_CROSS_TO_SPOT (*binance.client.BaseClient attribute*), 95
- MARGIN_CROSS_TO_USDT_FUTURE (*binance.client.BaseClient attribute*), 95
- margin_socket() (*binance.streams.BinanceSocketManager method*), 196
- margin_stream_close() (*binance.client.AsyncClient method*), 86
- margin_stream_close() (*binance.client.Client method*), 169
- margin_stream_get_listen_key() (*binance.client.AsyncClient method*), 86
- margin_stream_get_listen_key() (*binance.client.Client method*), 169
- margin_stream_keepalive() (*binance.client.AsyncClient method*), 86
- margin_stream_keepalive() (*binance.client.Client method*), 169
- MAX_QUEUE_SIZE (*binance.streams.ReconnectingWebsocket attribute*), 201
- MAX_RECONNECT_SECONDS (*binance.streams.ReconnectingWebsocket attribute*), 201
- MAX_RECONNECTS (*binance.streams.ReconnectingWebsocket attribute*), 201
- MIN_RECONNECT_WAIT (*binance.streams.ReconnectingWebsocket attribute*), 201
- MINING_TO_FIAT (*binance.client.BaseClient attribute*), 95
- MINING_TO_SPOT (*binance.client.BaseClient attribute*), 95
- MINING_TO_USDT_FUTURE (*binance.client.BaseClient attribute*), 95
- miniticker_socket() (*binance.streams.BinanceSocketManager method*), 196
- multiplex_socket() (*binance.streams.BinanceSocketManager method*), 196
- ## N
- new_transfer_history() (*binance.client.AsyncClient method*), 86
- new_transfer_history() (*binance.client.Client method*), 169
- NO_MESSAGE_RECONNECT_TIMEOUT (*binance.streams.ReconnectingWebsocket attribute*), 201
- NotImplementedException, 189
- ## O
- OPTIONS (*binance.streams.BinanceSocketType attribute*), 201
- options_account_info() (*binance.client.AsyncClient method*), 86
- options_account_info() (*binance.client.Client method*), 170
- OPTIONS_API_VERSION (*binance.client.BaseClient attribute*), 95
- options_bill() (*binance.client.AsyncClient method*), 86
- options_bill() (*binance.client.Client method*), 170
- options_cancel_all_orders() (*binance.client.AsyncClient method*), 86
- options_cancel_all_orders() (*binance.client.Client method*), 170

- `options_cancel_batch_order()` (*binance.client.AsyncClient method*), 86
`options_cancel_batch_order()` (*binance.client.Client method*), 170
`options_cancel_order()` (*binance.client.AsyncClient method*), 86
`options_cancel_order()` (*binance.client.Client method*), 170
`options_depth_socket()` (*binance.streams.BinanceSocketManager method*), 197
`options_exchange_info()` (*binance.client.AsyncClient method*), 86
`options_exchange_info()` (*binance.client.Client method*), 171
`options_funds_transfer()` (*binance.client.AsyncClient method*), 86
`options_funds_transfer()` (*binance.client.Client method*), 171
`options_historical_trades()` (*binance.client.AsyncClient method*), 86
`options_historical_trades()` (*binance.client.Client method*), 171
`options_index_price()` (*binance.client.AsyncClient method*), 86
`options_index_price()` (*binance.client.Client method*), 171
`options_info()` (*binance.client.AsyncClient method*), 86
`options_info()` (*binance.client.Client method*), 171
`options_kline_socket()` (*binance.streams.BinanceSocketManager method*), 197
`options_klines()` (*binance.client.AsyncClient method*), 86
`options_klines()` (*binance.client.Client method*), 171
`options_mark_price()` (*binance.client.AsyncClient method*), 86
`options_mark_price()` (*binance.client.Client method*), 172
`options_multiplex_socket()` (*binance.streams.BinanceSocketManager method*), 197
`options_order_book()` (*binance.client.AsyncClient method*), 86
`options_order_book()` (*binance.client.Client method*), 172
`options_ping()` (*binance.client.AsyncClient method*), 86
`options_ping()` (*binance.client.Client method*), 172
`options_place_batch_order()` (*binance.client.AsyncClient method*), 86
`options_place_batch_order()` (*binance.client.AsyncClient method*), 172
`options_place_order()` (*binance.client.AsyncClient method*), 86
`options_place_order()` (*binance.client.Client method*), 172
`options_positions()` (*binance.client.AsyncClient method*), 86
`options_positions()` (*binance.client.Client method*), 173
`options_price()` (*binance.client.AsyncClient method*), 86
`options_price()` (*binance.client.Client method*), 173
`options_query_order()` (*binance.client.AsyncClient method*), 86
`options_query_order()` (*binance.client.Client method*), 173
`options_query_order_history()` (*binance.client.AsyncClient method*), 86
`options_query_order_history()` (*binance.client.Client method*), 173
`options_query_pending_orders()` (*binance.client.AsyncClient method*), 86
`options_query_pending_orders()` (*binance.client.Client method*), 173
`options_recent_trades()` (*binance.client.AsyncClient method*), 86
`options_recent_trades()` (*binance.client.Client method*), 174
`options_recent_trades_socket()` (*binance.streams.BinanceSocketManager method*), 197
`OPTIONS_TESTNET_URL` (*binance.client.BaseClient attribute*), 95
`options_ticker_socket()` (*binance.streams.BinanceSocketManager method*), 197
`options_time()` (*binance.client.AsyncClient method*), 86
`options_time()` (*binance.client.Client method*), 174
`OPTIONS_URL` (*binance.client.BaseClient attribute*), 95
`options_user_trades()` (*binance.client.AsyncClient method*), 86
`options_user_trades()` (*binance.client.Client method*), 174
`OptionsDepthCacheManager` (*class in binance.depthcache*), 188
`order_limit()` (*binance.client.AsyncClient method*), 86
`order_limit()` (*binance.client.Client method*), 174
`order_limit_buy()` (*binance.client.AsyncClient method*), 87
`order_limit_buy()` (*binance.client.Client method*), 175

- `order_limit_sell()` (*binance.client.AsyncClient method*), 87
`order_limit_sell()` (*binance.client.Client method*), 175
`order_market()` (*binance.client.AsyncClient method*), 88
`order_market()` (*binance.client.Client method*), 176
`order_market_buy()` (*binance.client.AsyncClient method*), 88
`order_market_buy()` (*binance.client.Client method*), 176
`order_market_sell()` (*binance.client.AsyncClient method*), 89
`order_market_sell()` (*binance.client.Client method*), 177
`order_oco_buy()` (*binance.client.AsyncClient method*), 89
`order_oco_buy()` (*binance.client.Client method*), 177
`order_oco_sell()` (*binance.client.AsyncClient method*), 90
`order_oco_sell()` (*binance.client.Client method*), 178
`ORDER_RESP_TYPE_ACK` (*binance.client.BaseClient attribute*), 95
`ORDER_RESP_TYPE_FULL` (*binance.client.BaseClient attribute*), 95
`ORDER_RESP_TYPE_RESULT` (*binance.client.BaseClient attribute*), 95
`ORDER_STATUS_CANCELED` (*binance.client.BaseClient attribute*), 95
`ORDER_STATUS_EXPIRED` (*binance.client.BaseClient attribute*), 95
`ORDER_STATUS_FILLED` (*binance.client.BaseClient attribute*), 95
`ORDER_STATUS_NEW` (*binance.client.BaseClient attribute*), 95
`ORDER_STATUS_PARTIALLY_FILLED` (*binance.client.BaseClient attribute*), 95
`ORDER_STATUS_PENDING_CANCEL` (*binance.client.BaseClient attribute*), 95
`ORDER_STATUS_REJECTED` (*binance.client.BaseClient attribute*), 95
`ORDER_TYPE_LIMIT` (*binance.client.BaseClient attribute*), 96
`ORDER_TYPE_LIMIT_MAKER` (*binance.client.BaseClient attribute*), 96
`ORDER_TYPE_MARKET` (*binance.client.BaseClient attribute*), 96
`ORDER_TYPE_STOP_LOSS` (*binance.client.BaseClient attribute*), 96
`ORDER_TYPE_STOP_LOSS_LIMIT` (*binance.client.BaseClient attribute*), 96
`ORDER_TYPE_TAKE_PROFIT` (*binance.client.BaseClient attribute*), 96
`ORDER_TYPE_TAKE_PROFIT_LIMIT` (*binance.client.BaseClient attribute*), 96
- ## P
- `ping()` (*binance.client.AsyncClient method*), 90
`ping()` (*binance.client.Client method*), 178
`PRIVATE_API_VERSION` (*binance.client.BaseClient attribute*), 96
`PUBLIC_API_VERSION` (*binance.client.BaseClient attribute*), 96
`purchase_lending_product()` (*binance.client.AsyncClient method*), 91
`purchase_lending_product()` (*binance.client.Client method*), 179
- ## Q
- `query_subaccount_spot_summary()` (*binance.client.AsyncClient method*), 91
`query_subaccount_spot_summary()` (*binance.client.Client method*), 179
`query_universal_transfer_history()` (*binance.client.AsyncClient method*), 91
`query_universal_transfer_history()` (*binance.client.Client method*), 179
- ## R
- `random()` (*in module binance.streams*), 203
`RECONNECTING` (*binance.streams.WSListenerState attribute*), 203
`ReconnectingWebsocket` (*class in binance.streams*), 201
`recv()` (*binance.depthcache.BaseDepthCacheManager method*), 186
`recv()` (*binance.streams.ReconnectingWebsocket method*), 201
`redeem_lending_product()` (*binance.client.AsyncClient method*), 91
`redeem_lending_product()` (*binance.client.Client method*), 180
`repay_margin_loan()` (*binance.client.AsyncClient method*), 91
`repay_margin_loan()` (*binance.client.Client method*), 180
`REQUEST_TIMEOUT` (*binance.client.BaseClient attribute*), 96
`round_step_size()` (*in module binance.helpers*), 189
- ## S
- `SIDE_BUY` (*binance.client.BaseClient attribute*), 96
`SIDE_SELL` (*binance.client.BaseClient attribute*), 96
`sort_depth()` (*binance.depthcache.DepthCache static method*), 187

SPOT (<i>binance.streams.BinanceSocketType</i> attribute), 201	start_kline_futures_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
SPOT_TO_COIN_FUTURE (<i>binance.client.BaseClient</i> attribute), 96	start_kline_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
SPOT_TO_FIAT (<i>binance.client.BaseClient</i> attribute), 96	start_margin_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
SPOT_TO_MARGIN_CROSS (<i>binance.client.BaseClient</i> attribute), 96	start_miniticker_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
SPOT_TO_MINING (<i>binance.client.BaseClient</i> attribute), 96	start_multiplex_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
SPOT_TO_USDT_FUTURE (<i>binance.client.BaseClient</i> attribute), 96	start_options_depth_socket () (<i>binance.depthcache.ThreadedDepthCacheManager</i> method), 188
start_aggtrade_futures_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 201	start_options_depth_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
start_aggtrade_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 201	start_options_kline_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
start_all_mark_price_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 201	start_options_multiplex_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
start_all_ticker_futures_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 201	start_options_recent_trades_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
start_book_ticker_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202	start_options_ticker_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
start_coin_futures_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202	start_symbol_book_ticker_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
start_depth_cache () (<i>binance.depthcache.ThreadedDepthCacheManager</i> method), 188	start_symbol_mark_price_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
start_depth_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202	start_symbol_miniticker_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
start_futures_depth_socket () (<i>binance.depthcache.ThreadedDepthCacheManager</i> method), 188	start_symbol_ticker_futures_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
start_futures_multiplex_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202	start_symbol_ticker_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
start_futures_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202	start_symbol_ticker_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
start_index_price_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202	start_ticker_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
start_individual_symbol_ticker_futures_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202	start_trade_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202
start_isolated_margin_socket () (<i>binance.streams.ThreadedWebsocketManager</i> method), 202	

- start_user_socket() (*binance.streams.ThreadedWebsocketManager method*), 202
 stream_close() (*binance.client.AsyncClient method*), 91
 stream_close() (*binance.client.Client method*), 181
 stream_get_listen_key() (*binance.client.AsyncClient method*), 92
 stream_get_listen_key() (*binance.client.Client method*), 181
 stream_keepalive() (*binance.client.AsyncClient method*), 92
 stream_keepalive() (*binance.client.Client method*), 181
 STREAM_TESTNET_URL (*binance.streams.BinanceSocketManager attribute*), 190
 STREAM_URL (*binance.streams.BinanceSocketManager attribute*), 190
 STREAMING (*binance.streams.WSListenerState attribute*), 203
 symbol_book_ticker_socket() (*binance.streams.BinanceSocketManager method*), 197
 symbol_mark_price_socket() (*binance.streams.BinanceSocketManager method*), 198
 symbol_miniticker_socket() (*binance.streams.BinanceSocketManager method*), 198
 symbol_ticker_futures_socket() (*binance.streams.BinanceSocketManager method*), 198
 symbol_ticker_socket() (*binance.streams.BinanceSocketManager method*), 199
 SYMBOL_TYPE_SPOT (*binance.client.BaseClient attribute*), 96
- ## T
- ThreadedDepthCacheManager (*class in binance.depthcache*), 188
 ThreadedWebsocketManager (*class in binance.streams*), 201
 ticker_socket() (*binance.streams.BinanceSocketManager method*), 199
 TIME_IN_FORCE_FOK (*binance.client.BaseClient attribute*), 96
 TIME_IN_FORCE_GTC (*binance.client.BaseClient attribute*), 96
 TIME_IN_FORCE_IOC (*binance.client.BaseClient attribute*), 96
 TIMEOUT (*binance.depthcache.BaseDepthCacheManager attribute*), 185
 TIMEOUT (*binance.streams.ReconnectingWebsocket attribute*), 201
 toggle_bnb_burn_spot_margin() (*binance.client.AsyncClient method*), 92
 toggle_bnb_burn_spot_margin() (*binance.client.Client method*), 181
 trade_socket() (*binance.streams.BinanceSocketManager method*), 200
 transfer_dust() (*binance.client.AsyncClient method*), 92
 transfer_dust() (*binance.client.Client method*), 182
 transfer_history() (*binance.client.AsyncClient method*), 93
 transfer_history() (*binance.client.Client method*), 182
 transfer_isolated_margin_to_spot() (*binance.client.AsyncClient method*), 93
 transfer_isolated_margin_to_spot() (*binance.client.Client method*), 183
 transfer_margin_to_spot() (*binance.client.AsyncClient method*), 93
 transfer_margin_to_spot() (*binance.client.Client method*), 183
 transfer_spot_to_isolated_margin() (*binance.client.AsyncClient method*), 93
 transfer_spot_to_isolated_margin() (*binance.client.Client method*), 183
 transfer_spot_to_margin() (*binance.client.AsyncClient method*), 93
 transfer_spot_to_margin() (*binance.client.Client method*), 184
- ## U
- universal_transfer() (*binance.client.AsyncClient method*), 93
 universal_transfer() (*binance.client.Client method*), 184
 USD_M_FUTURES (*binance.streams.BinanceSocketType attribute*), 201
 USDT_FUTURE_TO_FIAT (*binance.client.BaseClient attribute*), 96
 USDT_FUTURE_TO_MARGIN_CROSS (*binance.client.BaseClient attribute*), 96
 USDT_FUTURE_TO_SPOT (*binance.client.BaseClient attribute*), 96
 user_socket() (*binance.streams.BinanceSocketManager method*), 200

V

VSTREAM_TESTNET_URL (*binance.streams.BinanceSocketManager* attribute), 190
VSTREAM_URL (*binance.streams.BinanceSocketManager* attribute), 190

W

WEBSITE_URL (*binance.client.BaseClient* attribute), 96
WEBSOCKET_DEPTH_10 (*binance.streams.BinanceSocketManager* attribute), 190
WEBSOCKET_DEPTH_20 (*binance.streams.BinanceSocketManager* attribute), 190
WEBSOCKET_DEPTH_5 (*binance.streams.BinanceSocketManager* attribute), 190
withdraw() (*binance.client.AsyncClient* method), 93
withdraw() (*binance.client.Client* method), 184
WSListenerState (*class in binance.streams*), 202